

Everything DLED3

A lot of items are not listed yet on our webstore. [Call](#) or [email](#) us with the item references listed below for a price.

Items listed in blue are available through our webstore.

Qty	DLED7	
	DLED3-BI	Focusing 90W TURBO LED light head, bicolor
	DT3-BI-BAT	DT3-BI-BAT: DC dimmable ballast with digital display for Kelvin values for DLED3-BI TURBO light heads with 0.5mm male Jack connector (11 - 18v DC). Requires DLPS12-60 AC power supply or DDCC battery cable.
	DT3-BI-DMX	AC dimmable ballast with Manual/DMX control for DLED3-BI TURBO LED light head (100-240V AC). Digital display for dimmer & Kelvins.
	DLED3-D	Focusing 90W TURBO LED light head, daylight
	DT3-BAT	DC dimmable ballast with digital display for DLED3-D TURBO light heads, 0.5mm male Jack connector (11 - 18v DC). Requires DLPS12-60 AC power supply or DDCC battery cable.
Power solutions		
	DLPS12-60	AC power supply - 12V 60W for DT3(-BI)-BAT & DT4(-BI)-BAT ballasts. Female Jack to US 100-240V AC
	DDCC-DTAPS	DC cable 11" long (small). Female jack Ø5.5 mm/2.5 mm to Anton/Bauer D-TAP connector.
	DDCC-EXT5	DC Extension cable Male/Female jack Ø5.5 mm/2.5mm. 16ft (5m) long for DLPS-12/12-30/12-60 power supplies.
	DDCC-CAR	Cigarette Lighter adapter & 6FT cable with Female jack Ø5.5 mm/2.5mm
	DLBCA-AB	Belt adapter for Anton/Bauer battery mounts. D-TAP power out connector
	DLBCA2-AB	Belt adapter for Anton/Bauer battery mounts with holding plate for LED BAT power supplies. D-TAP power out connector
	DLBCA-V	Belt adapter for V-Mount batteries. D-TAP power out connector
	DLBCA2-V	Belt adapter for V-Mount batteries with holding plate for LED BAT power supplies. D-TAP power out connector
	DTHC	Power supply holder incl. CLAMP-C, fits DT3(-BI)-BAT). Max. clamp opening 1" (25.4mm).
	DTHD	Power supply holder incl. CLAMP-D, fits DT3(-BI)-BAT).. Max clamp opening 2" (52mm)
Barn doors & head cables		
	DBDS8	DBDS8 Barn door, 8 leaves for DLED2 & DLED3.
	DBDS	Barn door, with 8 rotatable leaves for DLED2 & DLED3.
	DPLSS	Light shield ring for DLED2 & DLED3
	DPOW6LEM-10	Extension cable Lemo6 Female to Lemo6 male head to ballast. Custom length up to 30 ft long.
Beam Enhancement		
	DLWARS	Wide angle attachment with rotating barn door leaves (DLED2 & DLED3)
	DWAFXS	Directional beam spreader with holder for accessory slot (DLED2 & DLED3)
Parallel Beam Technology		
	DPBA-610	Parallel beam attachment, 6cm dia. Fits: DLED3-BI (x5), DLED3-D/T (x6) light heads. 6° (8° in Bicolor) beam angle in flood position. Ouput x 5 to x6 over native spot. May be used with DPBA-7HON honeycomb.
	DPBA-BI6	Parallel beam attachment, 6cm dia. Fits: DLED3-BI (x5), DLED3-D/T (x6) light heads. 6° (8° in Bicolor) beam angle in flood position. Ouput x 2 to x3 over native spot. May be used with DPBA-7HON honeycomb. Also fits also DLED2
	DPBA-7HON	Honeycomb for DPBA-610 attachment. Also fits DPBA-7.
	SLR7R-4	Lightstream Mini Reflectors kit of 4. Includes in each: 4 reflectors 7x10cm (2.75"x4") #1, #2, #3, #4. 2x Clamp-D, 2x DLR-LOCK, 2x DLGA160, 1x DLRP10 Soft Pouch for 7x10 reflectors.
	SLR25-4	Lightstream Medium Reflectors Kit of 4. 25x25cm (10"): 1 each: #1, #2, #3, #4. 2x Clamp-D, 2x DLR-LOCK, 2x DLGA160, 2x Clamp-D, 2x DLR-LOCK, 2x DLGA160, 1x DLRP25 Pouch for 25x25 reflectors.
	SLR50-4	Lightstream Large Reflectors Kit of 4. 50x50cm (20"): 1 each: #1, #2, #3, #4. 2x Clamp-D, 2x DLR-LOCK, 2x DLGA240, 1x DLRP50 Pouch for 50x50 reflectors.
Imager/Projection System		
	DP1S	Small Imager/projection attachment with 60mm lens & DPGHS gobo holder (fits DLED3 & DLED2)
	DP1S-0	Small Imager/projection attachment & DPGHS gobo holder (fits DLED3 & DLED2). No lens included
	DP2S	Small Imager/projection attachment with built-in framing shutters and 60 mm lens
	DP2S-0	Small Imager/projection attachment with built-in framing shutters (fits DLED3 & DLED2). No lens included
	DP1S-A	Asymetrical Small Imager/projection attachment with 60mm lens & DPGHS gobo holder (fits DLED3 & DLED2)
	DP1S-AO	Asymetrical Small Imager/projection attachment & DPGHS gobo holder (fits DLED3 & DLED2). No lens included
	DPL30M	30mm projection lens for DP1.1, DP2.1, DP1S and DP2S imagers, f 1.8
	DPL50M	50mm projection lens for DP1.1, DP2.1, DP1S and DP2S imagers, f 2.8
	DPL60M	Replacement Imager lens, 60 mm, f 2.4 for DP1.1, DP2.1, DP1S and DP2S imagers, f 2.8
	DPL85M	Imager lens, 85 mm, f 2.8

Dedolight California. Burbank CA. Tel: 818 760 7715. Toll Free: 833 CAL DEDO.

www.dedolightcalifornia.com. info @dedolightcalifornia.com

DPLZ120M	Imager zoom lens, 70-120 mm (NB: 85-150mm is not compatible with DP1S/2S)
DPX	Imager extension tube: between projection attachment & lens. Extend by 60 to 100mm for short distances & small subjects
DPEYESET	Eye filter attachment (fits all Classic Series imager lenses except 30mm and zooms) with 3 filters
DPEYEP	Pouch for DPEYESET
DPIRS	Small Imager iris
Soft Box	
DLSR67	Speed ring for dedoflex mini soft box silver dome (DSBSXS) for DLED3.
DSBSXS	dedoflex mini soft box 30 x 30 x 23 cm (12 x 12 x 9"), fits DLED3
DLGRIDXS	Grid (40°), fits dedoflex mini soft box (DSBSXS)
Gobos, Filters & Gels	
DPGHS	Steel gobo/glass filter holder (size 'S') for DLED2/3.
DPGSETS	Gobo set (six popular steel gobos, size 'S' 50mm) for DP1S imagers
DFCCMGS-1/2	Minus green color correction filter S size (59 x 59 mm) for DLED2 (& DLED3), 1/2 intensity
DFCCMGS-1/4	Minus green color correction filter S size (59 x 59 mm) for DLED2 (& DLED3), 1/4 intensity
DFCCMGS-1/8	Minus green color correction filter S size (59 x 59 mm) for DLED2 (& DLED3), 1/8 intensity
DFCCMGS-1/16	Minus green color correction filter S size (59 x 59 mm) for DLED2 (& DLED3), 1/16 intensity
DFCCPGS-1/2	Plus green color correction filter S size (59 x 59 mm) for DLED2 (& DLED3), 1/2 intensity
DFCCPGS-1/4	Plus green color correction filter S size (59 x 59 mm) for DLED2 (& DLED3), 1/4 intensity
DFCCPGS-1/8	Plus green color correction filter S size (59 x 59 mm) for DLED2 (& DLED3), 1/8 intensity
DFCCPGS-1/16	Plus green color correction filter S size (59 x 59 mm) for DLED2 (& DLED3), 1/16 intensity
DGRADFS03	Dichroic graduated ND grey glass filter: minus one stop. S size (59 x 59 mm) for DLED2 (& DLED3). Fits filter slot
DGRADFS06	Dichroic graduated ND grey glass filter: minus two stops. S size (59 x 59 mm) for DLED2 (& DLED3). Fits filter slot
DGRADFS09	Dichroic graduated ND grey glass filter: minus three stops. S size (59 x 59 mm) for DLED2 (& DLED3). Fits filter slot
DGRADFS12	Dichroic graduated ND grey glass filter: minus four stops. S size (59 x 59 mm) for DLED2 (& DLED3). Fits filter slot
Stands, Brackets, Cases, Etc...	
DST	dedolight stand 19" to 7 ft
DSTM	dedolight Micro stand 15" to 47"
DSTFX	Flexible stand extension 20" (510 mm)
DSTFX40	Flexible stand extension 16" (400 mm)
DSTFXS	Flexible stand extension 8" (210 mm)
CLAMP1	dedolight clamp
CLAMP-S	Scissors clamp with long 5/8" (16mm) stud
CLAMP-C	Clamp with 1/4" internal thread and hex. receptacle, fits diameter from 0.51" (13 mm) to 1" (25,4 mm)
CLAMP-D	Clamp with 1/4" internal thread and hex. receptacle, fits diameter from 0.98" (25 mm) to 2" (52 mm)
DH2	Wall holder
DV6B	Vacuum mount, 152 mm (6") diameter suction cup with articulated arm
DLHAND	dedolight handle
STUD6L	Baby stud 16mm (5/8") with hex. rod 6" (150 mm) long
STUD6M	Baby stud 16mm (5/8") with hex. rod 4-1/3" (110 mm) long
STUD6S	Baby stud 16mm (5/8") with hex. rod 2.5" (65 mm) long
STUDL	Baby stud, 5/8" (16mm) with 1/4" internal thread
STUDS	Stud, 5/8" (16mm) with 1/4" internal thread
STUDL90	Baby stud angle attachment, 5/8" (16mm) with hex. rod
DSCST4	Soft bag for 4x DST stands
DSCM	Soft DSCM Soft case, mono. 11" x 6.7" x 10". Cube shape with top handle & shoulder strap.
DSCSTM3	Soft bag for 3x micro stands (DSTM) + 2x 16" Extensions (DSTFX40)
DSCS	Soft case, small (16"L x 8"W x 10"H) with 3 external pockets.
PELDP400	Pelican Air 1557 case w Trekpak divider set. Outside dimensions:19.18"x 15.79"x 10.50"D (LxWxH) weight empty: 7 lb
Dedo Cali Solo kit	1x DLED3-BI, 1x DT3-BI-BAT, 1x DBDS8, 1x DDCC-DTAPS
SLT3-3-BI-S	Soft case Micro kit including: (Items marked in green above) 3x DLED3-BI Turbo focusing bicolor LED light heads, DP1S projection & micro-stands: 3x DLED3-BI, 3x DT3-BI-BAT, 3x DDCC-DTAPS, 3x DLPS12-EXT5, 3x DLPS12-60, DBDS8, 2x DSBSXS, 2x DLSR67, 1x DP1S, 1x DPGHS, 1x DPGSETS, x 3x DSTM, 2x DSTFX40, 1x DSCSTM3, 1x DSCS