

EverBlock® Systems, LLC. 844-422-5625 790 Madison Avenue, Suite 506, New York, NY 10065 www.everblockflooring.com

EverBase 2 Modular Flooring

SPECIFICATION SHEET

EverBaseTM **2** is a modular, interlocking, general purpose flooring system. It can be used for a variety of applications at all types of venues and facilities.

The **EverBase 2** is an **18" x 24"** flooring tile that interconnects with adjacent tiles to create a seamless floor surface and a solid support base for all types of activities. From on-field concerts to tent flooring at events and from shelter flooring to exhibition flooring, the **EBF2** is the workhorse of the EverBlock Flooring line.

MODULE SIZES

 Item
 Description
 Length
 Width

 EBF2
 EverBase 2
 24" (60.96 cm)
 18" (45.72 cm)

 Thickness
 Weight

 *3 sq/ft per tile (0.28 sqm per tile)
 1.1" (2.79 cm)
 3.81 lb. per tile

 (2.23 kg)

COLORS * Custom colors available with minimum order sizes.

Light Grey standard on Solid Top
(ST version)

TRANSLUCENT/ MILKY WHITE (No Color)

Translucent standard for grass protection (DT version)

MATERIAL

Hi-Impact **Polypropylene Co-Polymer** ("no-break") with UV Inhibitors added for outdoor use.

VERSIONS

Solid Top (ST)Features a flat top surface

Drainage Top (DT)

Contains a series of drainage, light, and aeration holes

Connector Lug Tile

Contains lug connectors on top to integrate with EverBlock building blocks

Arena Flooring (AF)

Contains a bottom plastic layer that encloses each flooring module for greater insulation









EverBlock® Systems, LLC. 844-422-5625 790 Madison Avenue, Suite 506, New York, NY 10065 www.everblockflooring.com

FIRE RATING (A)

UL94HB (Underwriters Laboratory Test):

*This test signifies that **EverBlock** does not flare up when exposed to an open flame and has a slow burn rate of 2" per minute for a 2" wide, 0.5 millimeter thickness test sample. EverBlock meets all applicable standards for temporary floor covers.

Hot wire ignition rating: 3

ASTM 2859 (Flammability Of Finished Textile Floor Covering Materials): PASS

SHIPPING QUANTITIES		
Standard Pallet:	40" x 48" x 84 smaller quantities may be ordered	840 sq/ft
53ft Truckload Quantity:	26 Pallets	21,840 sq/ft
20ft Ocean Container:	10 Pallets	8,400 sq/ft
40ft Ocean Container:	20 Pallets	16,800 sq/ft
40ft High Cube Ocean Container:	20 Extra Tall Pallets	16,800 sq/ft
Military 463L Pallet (88" x 98" x 96"):	2,400 sq/ft maximum loading	

WEIGHT LOADING CAPACITY: 8,500 lbs. sq/ft

*On a solid subsurface, non-moving (static) weight, with equal distribution of load across the tile surface. **Support Structure:** Intersecting bi-directional support ribs provide structure, torsional strength, and additional weight distribution and weight loading capabilities.



AVAILABLE ACCESSORIES

Transition Edging: Male Edge, Female Edge, Corner Piece

Transition Edging is recommended for pedestrian access points and areas where wheeled equipment or pedestrians are expected to come on to the floor.

Transition Cart:

Heavy duty wheeled cart that allows for easy transport and storage of flooring.



EverBlock® Systems, LLC. 844-422-5625 790 Madison Avenue, Suite 506, New York, NY 10065 www.everblockflooring.com

USES OF EBF2:

EverBase 2 may be used for numerous applications

- Tent Flooring
- Natural Turf Protection
- Synthetic Turf Protection
- Ice Arena Floors
- Military Shelter Flooring
- General Event Flooring
- Exhibition Flooring
- · Base for EverBlock Building Blocks
- Raised Flooring and Risers (over EverBlock modular blocks)

EVERBASE 2 FEATURES

EverBase 2 incorporates unique functional features that distinguish it from competitors

- · Unique modular design allows sections to be connected to create nearly any sized floor
- Proprietary connection system allows for quick installation and removal WITHOUT any tools
- Lightweight construction for easy handling and transport
- Durable cross ribs add structural support, increase weight loading capacity and provide torsional stability
- Integrated cable channels allow for networking and power cables to be run underneath the flooring
- · May be installed on top of EverBlock modular building blocks, allowing floors to be raised
- UV protected
- Fully waterproof and chemical resistant and may be used indoors and outside
- 100% recyclable
- Drainage (DT) version allows water and light through to facilitate photosynthesis and create a moisture canopy that protects grass for several day

WARRANTY



Standard 3 year warranty against manufacturer's defects.