

# CENTER BRAKE LIGHT FOR TOUR PAK

# Parts Included:

- l Genter Run/Brake Light for Tour Pak
- Wiring Kib Including:
  - 1 Run/Brake Adapter for Tour Pak
  - 4 6" Cable Ties
  - 1 Dielectric Grease Packet

# Installation Instructions

- 1. Park on a level surface and shub off the motorcycle. Ensure that the engine has time to cool before installation.
- 2. Remove seat.
- 3. Use an ammonia-based glass cleaner to remove any wax or contaminants on Tour Pak. This will ensure a strong bond between the light and Tour Pak.
- 4. Test fit by holding light up to the Tour Pak. When in correct centered position, mark the sides of the light on the Tour Pak with painter's tape for reference once adhesive backing is removed.



- 5. Activate adhesive by rubbing with fingernail. Remove adhesive backing and push bottom of light up against underside of Tour Pak, then slide forward for adhesive to reach Tour Pak. Make sure wire does not interfere with fitment. Align light with painter's tape mark for proper center placement. Press and hold firmly for 60 seconds. Adhesive fully cures within 24 hours.
- 6. Feed wire for light up through left underside of Tour Pak to reach under-seat area. Locate and disconnect the black lighting connector at the rear of the under-seat area. Apply a small amount of the included dielectric grease on electrical connections and plug the Ciro run/brake adapter in line with it. Secure all wiring with included cable ties.



7. Turn on the accessory power to verify that lighting is functioning correctly, then reinstall seat.

#### WARNING:

This indication alerts you to the fact that ignoring the contents described herein can result in potential serious injury or death if not followed.

### **CAUTION:**

This indication alerts you to the fact that ignoring the contents described herein can or will result in material damage and/or personal injury.

#### **ATTENTION:**

This indication alerts you to the fact if you ignore this detail you will affect the performance or functionality of the product.

All Ciro products are designed for "easy assembly" and/or "plug and play". We recommend a competent mechanic install our products, using standard mechanical procedures to assure a safe and successful installation.

# NOTE:

Ciro products are designed and manufactured under very strict quality control. Ciro warrants that products sold to the original purchaser shall be free from any defects in materials and workmanship for a period of 3 (three) years from the date of purchase, and a lifetime warranty against LEO failure.

Ciro will have no obligation if

Ciro will have no obligation if the customer cannot show proof of purchase.

Warranty will not be granted unless the part is properly installed and maintained. Giro will not be liable for any consequential and incidental damages, including labor, or non-Ciro products.

Please visit our website Ciro3d.com for our complete warranty policy.

CIRO.3D.COM