



CALLING/TALKING

- ➔ HAC
- ➔ Adjustable receiving volume : up to 30dB
- ➔ Speaker phone
- ➔ Adjustable speaker volume
- ➔ Phonebook up to 50 numbers
- ➔ Redial function for last 10 outgoing calls
- ➔ P/T dialing mode
- ➔ R button for call waiting
- ➔ Hotkey to phonebook
- ➔ Hotkey to menu
- ➔ Flash function (100ms/300ms/600ms)
- ➔ Large keys

HANDSET LCD DISPLAY

- ➔ White backlight
- ➔ Choice of 7 languages (English, German, French, Italian, Dutch, Spanish and Russian)
- ➔ Dimensions : 40x40mm
- ➔ Display : Alphanumeric / 4 lines / Characters size : 7mm
- ➔ Clock
- ➔ Alarm
- ➔ Key lock
- ➔ Message waiting icon
- ➔ Communication time indication

CALLER ID *

- ➔ Name presentation in hook mode (type 1) and conversation mode (type 2)
 - 20 incoming numbers
 - 10 outgoing numbers
- ➔ Caller ID also for Call waiting
- ➔ Possibility to transfer a call received to the directory
- ➔ Indicator call waiting
- ➔ Indicator new call

ANSWERING MACHINE

- ➔ 15 minutes of recording time
- ➔ 2 announcements
- ➔ 2 answering machine modes (simple answering machine and answering machine recorder)
- ➔ Visual info. on the base about number of messages
- ➔ 4-digit user selectable remote codes
- ➔ Remote control for messages on handset
- ➔ Erase each/all messages
- ➔ Audible time & date stamp on recorded messages
- ➔ 3 languages (English, German and French)

MULTI HANDSET

- ➔ Handset locator
- ➔ 3-way conference with privacy protection
- ➔ Up to 4 bases and up to 5 handsets
- ➔ Call transfer of external calls (when using several handsets)
- ➔ Intercom between handset



Twin version available
AMPLIDECT295-2

RINGER

- ➔ 5 polyphonic ringtones and 5 normal
- ➔ Adjustable ring volume (Mute + 5 positions)
- ➔ Customizable ringtones for phonebook contacts
- ➔ Ringer indicator

TECHNICAL SPECIFICATIONS

- ➔ 1 battery ni-Mh 2.4V 500mA (included)
- ➔ Memory storage
- ➔ Power supply by AC adapter (supplied)
- ➔ Dial/Decimal voice frequency
- ➔ Standby time : 2 days
- ➔ Continuous talk time : 8 hours
- ➔ GAP compliant
- ➔ Range :
 - Indoor : up to 50m
 - Open field : up to 300m
- ➔ Dimensions :
 - Handset : 172x55x25 mm
 - Base : 136x91x105 mm

OPTIONAL EXTRA

- ➔ AmpliDect295 AD
- ➔ PhotoDect295



AmpliDect295 AD

PhotoDect295

FAMILY PRODUCTS

- ➔ AmpliDect295 DUO
- ➔ AmpliDect Combi 295
- ➔ AmpliDect Combi Photo 295
- ➔ AmpliDect295 SOS-PRO
- ➔ AmpliDect295 Photo

*To use the CID facility it will be necessary to subscribe to your network provider's CID service
Items pictured and details are subject to change at the manufacturer's discretion.