


W2-SVP-630L COMBINED STROBE & VIBRATING PAD

Battery Type

Rechargeable 5 year NI-MH battery



BS 5446-3:2005
KM 594270

- Compatible with and activated by any Wi-Safe 2 product.
- Mains powered with rechargeable battery back-up.
- Designed to provide additional protection to those with hearing loss, who may not hear the audible alarm from a smoke, heat or carbon monoxide alarm.
- The flashing strobe provides a visual warning for waking hours, while the vibrating pad may be placed under a pillow or mattress, and is suitable for waking someone to alert them when a smoke, heat or CO alarm sounds.
- Will activate if smoke / heat or CO triggers any alarm in the network.
- Will detect and indicate a low battery warning with any smoke, heat or CO alarm within the network.
- Can be wall mounted or free-standing, offering flexibility in positioning.
- Enables low level testing of all interlinked products in the network, avoiding the need to reach up to ceiling mounted alarms to test.

Technical Specification

Dimensions	Strobe: 102mm (width) x 150mm (height) x 39.3mm (depth) Pad: 98mm (diameter) x 34mm (depth)
Supply voltage	230V AC, 50Hz
Battery back-up	Rechargeable 5 year NI-MH battery
Technology	Wi-Safe 2
Alarm sound level	N/A
Installation positions	Flashing strobe: wall or free-standing Vibrating pad: under pillow, mattress or seating cushion
Operating temperature	+4°C to +38°C
Operating humidity	Up to 90% RH non-condensing
Storage temperature	-20°C to 60°C
Storage humidity	Up to 93% RH non condensing
Plastic material	ABS, UL94 VO fire retardant
Warranty	5 years
Weight	460g
Certified to	BS 5446-3:2005
Independently tested to	EN 300 220-2 V 2.4.1 EN 301 489-3 V 1.6.1 EN 301 489-1 V 1.9.2
Maximum number of connected units	50 wireless units
Operating frequency	868 MHz
Range	35m (over 200m in clear air)