


Standard Mesh Liquid Filter Bags

Steel-Ring bags have a Galvanized Steel Ring (Stainless Steel optional) sewn into the top of the bag. They are supplied with sewn seams standard. Plastic Flange bags have a specially-designed flange sewn to the top of the bag. They are supplied with sewn seams standard (welded collars available upon request).

Features

- Micron ratings from 1 to 1500
- All industry standard and custom sizes available
- High flow/Low pressure drop media
- Surface retention filtration
- Wide chemical compatibility
- Economical removal of non-deformable contaminants
- Non-fiber releasing
- Good removal efficiencies
- Temperature ratings up to 350°F
- Silicone-free construction
- Monofilament and Multifilament options
- Polyester & Nylon Materials meet FDA regulations for contact under CFR21, section 177.1520.



Multifilament Mesh media is woven from threads made of smaller fibers. Bags made from this material are low cost and disposable.



Monofilament Mesh is woven from single-fiber threads. The openings are square and uniform. Bags made from this material have excellent strength.

Ordering Information

Media Type	Micron Rating				Bag Dimensions			Ring/Flange Size	Options
	NMO	POMO	NMU	PEMU	Size	Diam.	Length		
NMO - Nylon Monofilament	1	100	100	100	P1 =	7.06"	16.5"	S = Galvanized Steel	H = Handle (Standard on all ring style bags)
POMO = Polypropylene Monofilament	5	150	150	150	P2 =	7.06"	32.0"	SS = Stainless Steel	EB = Edge Binding
NMU = Nylon Multifilament	10	200	200	200	P3 =	4.12"	8.0"	PP = Polypropylene Ring	A = Auto Seams
PEMU = Polyester Multifilament	25	250	250	250	P4 =	4.12"	14.0"	T = Titanium	TTA = Turn, top stitch, auto seam
	35	300	300	300	P5 =	4.12"	24.0"	P = P Flange	RC = Reverse Collar
	45	400	400	400	P7 =	5.50"	15.0"	F = F Flange	
	50	600	600	600	P8 =	5.50"	21.0"	OSS = OSS	
	75	800	800	800	P9 =	5.50"	31.0"	DS = Draw String	
	100		1500	1500	P11 =	8.50"	16.0"	NR = No Ring	
	125				P12 =	8.50"	30.0"		
	150				C1 =	7.31"	16.5"		
	175				C2 =	7.31"	32.5"		
	200				RP-1 =	8.0"	30.0"		
	250				RP-2 =	8.0"	40.0"		
	300				PC-1 =	9.0"	20.0"		
	400				PC-2 =	9.0"	30.0"		
	600				X1 =	4.35"	8.0"		
	800				X2 =	4.35"	14.0"		
	1000				X01 =	6.0"	22.0"		

Example: NMO300P1SSH