



# TREATMENT INSTRUCTIONS

## Aircraft Engine Treatment

**\*\*\*NOTE: Read through the entire instruction sheet before installing any Microlon Products.**

### To Install the Microlon Products-

- 1. Change your oil and oil filter. Change your fuel filter if possible.**
- 2. After the fueling and pre-flight inspection have been completed, bring the engine to operating temperature and shut the engine down.**
- 3. Shake the Microlon containers for at least one minute.**
- 4. Add the Microlon Engine Treatment but do not exceed 20% of the total oil volume at any one time. It may be necessary to add the remaining product after the cleaners have done their job and left the engine.**
- 5. If your aircraft has multiple fuel tanks, add the Microlon Fuel Treatment to a 1/2 tank of fuel or less. Run that tank as low as possible during the run-in time before switching. If your aircraft has a single fuel tank, add the fuel treatment to that tank.**
- 6. Start up the engine and immediately fly for at least 2 hours. If any remaining engine treatment needs to be added later, repeat these steps and operate the engine for another two hours.**

**\*\*\*NOTE: Do not change your oil for at least 15 flying hours after treatment to make sure that you get the full benefits of a Microlon Engine Treatment.**

**\*\*\*NOTE: Microlon is compatible with all oils & fuels including synthetics.**

Microlon, Inc. | 10718 N. Lamar, Suite C | Austin, TX 78753 USA

Order Desk/Tech Support: (512) 490-6460 • Fax: (844) 272-9829

[www.Microlon.com](http://www.Microlon.com)