

AAT-4400 IRD

Professional Receiver / Decoder



OVERVIEW

The new AAT-4400 Receiver Decoder is the latest in American Amplifier Technologies long line of professional integrated receiver/decoders for distribution and monitoring applications. Latest-generation components ensure that the AAT-4400 provides the most complete feature set and the best value for a broad swath of common receiver/decoder applications. The product supports decoding of SD or HD video, encoded as HEVC, H.264 or MPEG2, as well as up to four audio services.

The additional audio handling capability makes the AAT-4400 the perfect solution for video distributors looking to meet upcoming descriptive video requirements, while continuing to support surround, stereo, and SAP services. As customer demands evolve, units purchased for SD decoding can be upgraded to HD via a simple software license, and with the included digital video output, video monitoring is as easy as finding the nearest standard consumer television or PC monitor.

With built-in ASI input/output capability, as well as available satellite and IP interfaces, the AAT-4400 is adaptable to most decoder use cases. The receiver also has a web interface accessible via all major browsers and complete control of the unit via the front panel keypad.

KEY FEATURES

- Support for All Common Video Formats
 - HEVC, H.264, MPEG2 HD, or SD video
 - All formats auto-detected and switchable on-the-fly
- Up to 4 services of audio decoding or SDI pass-through with support for all major audio formats
- Dual SD auto-switching outputs
- Built-in ASI I/O for maximum value and flexibility
- Available 8VSB/Q AM-B, IP, RF satellite and DVB-T/T2/C/C2/ISBD-T inputs
- Full complement of ancillary data output in ANC and VBI
- Closed-caption or auto-scaling subtitle overlays for monitoring or burn-in applications
- Intuitive, straightforward web interface
- Full control, status, and alarm monitoring via SNMP

APPLICATIONS

- **Turn-around and Back-haul Distribution Feeds**
Receive network and live feeds via RF, ASI or IP, and simultaneously demodulate, de-encapsulate, encapsulate, and decode for local processing and re-encode requirements.
- **Upgrade Existing Installations**
Replace existing receiver decoders to meet emerging video distribution challenges, including the need for more audio services or the transition to HEVC Experience industry-leading ease of use and interoperability coupled with low cost of ownership.
- **Monitor Any Video Feed**
Leverage quick set-up and automatic, decode-anything operation to monitor video feeds operationally or in an engineering lab.



SPECIFICATIONS

Professional Receiver/Decoder AAT-4400

AVAILABLE VIDEO DECODER MODULES

ASI I/O, SDI and Analog Outputs, Discrete Audio, Genlock Support
ASI I/O, SDI and Analog Outputs, Discrete Audio
ASI I/O, SDI Outputs, and Genlock Support
ASI I/O and SDI Outputs

Additional Discrete Interfaces (available on AAT44041 and 44040)

Composite Video Output: 1x 75Ω BNC
NTSC, PAL-B/G/I/D/M/N
AES Audio Outputs: 4x 75Ω BNC
Analog Audio Outputs: 2x 15 pin D-Sub (4 Stereo Services)
4x XLR Breakout Cable Available
4x BNC Breakout Cable Available
Terminal Block Cable Available

Genlock Interface (available on AAT44041 and 44001)
Genlock Input: 1x 75Ω BNC

COMMON VIDEO DECODER FEATURES

Base Decoding (SD 4:2:0)

Video Profile/Levels: MPEG2 MP@ML
H.264 up to MP@L3

HEVC Decode License

Enables HEVC Decoding: Requires AAT44265 Option

HD Decoding License

Additional Profile/Levels: MPEG2 MP@HL
H.264 up to HP@L4.2
HEVC up to MP@MT L4 (with License)
Additional Output Formats: 1920x1080i @ 25, 29.97, 30
1920x1080p @ 23.97, 24, 25, 29.97, 30
1280x720p @ 50, 59.94, 60

Additional Base Video Features

Frame Synchronization Modes: PCR-Recovered Clock
Genlock Reference (If Supported)
Aspect Ratio Conversion
Manual Selection: Letterbox, Center-Cut, Anamorphic
Automatic Selection: Follows AFD Codes

Output Formats: 720x576i @ 25
720x480i @ 29.97

Output Interfaces:
SD/HD-SDI: 2x 75Ω BNC
SDI Format Support: Determined by Decode License
Digital Video: 1x HDMI-type Connector

Simultaneous SD Video Output Module

Mirrored SD SDI Outputs: 2x 75Ω BNC
Composite Video Output: 1x 75Ω BNC
NTSC, PAL-B/G/I/D/M/N

Simultaneous SD Video Output Module with Genlock

Mirrored SD SDI Outputs: 2x 75Ω BNC
Composite Video Output: 1x 75Ω BNC
NTSC, PAL-B/G/I/D/M/N

HEVC Decoding Daughter Board

Enables HEVC Licensing: Requires AAT44765 License for decoding functionality

Video Overlay Support

Closed Caption Overlays: CEA-608, CEA-708, or SCTE-20
DVB-Subtitle Overlays: HD/SD with Auto Scaling (EN 300743)

Base Audio Decoding Features

Number of Audio Services: 2 Standard, Up to 4 Available
Audio Codecs Supported: Dolby Digital (AC-3) & Plus (EAC-3)
AAC-LC, HE-AAC, & HE-AACv2
MPEG1L2 & MPEG2L2
Output Formats: Linear PCM & Dolby E (Pass-through)
Digital Pass-through
PCM (Downmixed for 5.1 Sources)
Analog (Downmixed for 5.1 Sources)

Discrete Channel Audio Output License

Adds Output Formats: PCM (Decoded Discrete channels for 5.1 Sources)
Analog (Decoded Discrete channels for 5.1 Sources)

4 Service Audio Decode License

Additional Audio Services: 2 Services (Total of 4 Services)

Base Audio Output Features

SDI Embedded Audio Output: 4 Audio Pairs

Ancillary Data Support

SDI ANC Data Types: AFD (SMPTE 2016)
Closed Captions (CEA-708)
OP-47 (SMPTE RDD-08)
SMPTE RDD-11
SCTE 127 (SMPTE 2031)
EN301775 (SMPTE 2031)
Time Code (SMPTE 12M-2)
SCTE 104 (SMPTE 2010 with License)
VBI Waveforms (SDI/Composite): Line 21 Captions (CEA-608)
TVG2X, AMOL-48/96 (SCTE-127)
Teletext/WSS/VPS (EN301775)

SCTE 35 to SCTE 104/Relay Output License

Cablelabs ESAM POIS Interface License

Included Transport Stream Input/Output Features

ASI Input/Output: 2 x 75Ω BNC (selectable in/out)
Supported Bitrate: 250 Kbps to 200 Mbps

BISS Descrambling License

Supported Modes: Mode 1, Mode E, Injected ID
Multi-BISS Support: Up to 12 Separate Keys

DVB-CI Multi-Service License

With DVB-CI Module: Enables Multi-service Descrambling

PID/Service Filtering License

Filtering: 10 Independent TS (MPTS or SPTS) created; output via IP or ASI

Table Regeneration (DVB Mode): PAT regeneration
Table Pass-through (DVB Mode): PMT, CAT, NIT pass-through Table
Regeneration (DVB Mode): PAT, SDT
Table Pass-through (DVB Mode): PMT, CAT, NIT, EIT, RST, TDT, TOT



SPECIFICATIONS CONTINUED

Professional Receiver/Decoder AAT-4400

AAT

8VSB/QAM-B INPUT MODULE AAT44101

Physical Interface: 75Ω F-Type
 Frequency Range: 50-1000 MHz
 Sensitivity: -34 to +40 dBmV (A74 Compliant)
 8VSB Standard: ATSC A/53E
 8VSB Channel Plans: Broadcast
 QAM Standard: ITU Annex B/SCTE DVS-031
 QAM Channel Plans: FCC, IRC, HRC
 QAM Constellations: QAM64, QAM25

DVB-CI DESCRAMBLING MODULE AAT44421

Physical Interface: Adds two DVB-CI CAM Slots
 Without Multi-Service License: Descrambles Decoded Service Only
 With Multi-Service License: Number of Services limited by CAM

IP INPUT/OUTPUT MODULE AAT44127

Physical Interface: 2x RJ45, 10/100/1000 Auto-Negotiate
 Input Format: UDP or RTP
 Constant Bitrate or Null-Stripped
 RTP Header Extensions Supported
 SMPTE 2022/CoP3 FEC Supported
 Output Format: UDP, RTP (with License)
 MPE De-encapsulation: Up to 2 PIDs
 Up to 60Mbps per MPE PID
 IP Encapsulation: 1 to 7 TS Packets per IP Packet
 Addressing: Unicast or Multicast
 IGMP compatibility: Version 1, 2 & 3
 Per TS Bitrate: 250 Kbps to 200 Mbps
 MPEG/IP FEC Output License AAT44925
 Additional Output Formats: RTP and Header Extensions
 SMPTE 2022/CoP3 FEC Supported

DVB-S/S2 INPUT MODULE AAT44116

Physical Interface: 4x 75Ω F-Type
 Frequency Range: 950-2150 MHz
 Symbol Rates: 1-60 Msps
 DVB-S Modulation Modes: QPSK (All FEC Rates)
 DVB-S2 Modulation Modes: QPSK/8PSK (All FEC Rates)
 16/32APSK with License
 LNB Power: Off/13/14/18/19VDC @ 450mA
 Control Tone Support: 22 kHz On/Off
 Supported Roll-off Factors: 0.35, 0.25, 0.20, 0.15, 0.10, 0.05

DVB-S2 Advanced Feature License AAT44916

Additional Modulation Modes: 16ASPK/32APSK (All FEC Rates)
 VCM Demodulation Support
 Multistream Support (Single ISI)

BROADCOM TURBOPSK INPUT MODULE AAT44111

Physical Interface: 1x 75Ω F-Type
 Frequency Range: 950-2150 MHz
 Symbol Rates: 1-30 Msps
 DVB-S Modulation Modes: QPSK (All FEC Rates)
 TurboPSK Modulation Modes: QPSK /8PSK (All FEC Rates)

DVB-T/T2/C/C2/ISDB-T INPUT MODULE AAT44115

Physical Interface: 1x 75Ω F-Type
 Frequency Range: 42-1002 MHz
 Bandwidth: 1.7MHz, 5 MHz, 6MHz, 7MHz, 8MHz
 Constellations:
 DVB-T: QPSK, QAM16, QAM64 (All FEC Rates)
 DVB-T2: QPSK, QAM16, QAM64, QAM256 (All FEC Rates)
 DVB-C: QAM16, QAM32, QAM64, QAM128, QAM256 (All FEC Rates)
 DVB-C2: QAM16, QAM64, QAM256, QAM1024, QAM4096 (All FEC Rates)
 ISDB-T: QPSK, QAM16, QAM64 (All FEC Rates)

MANAGEMENT

Connector: RJ-45 10/100 - Auto Negotiating
 Protocols: HTTP and SNMP
 User Interfaces: Full control via web GUI
 Full control via front panel
 Automation Interfaces: Full status and control via SNMP
 Configurable SNMP traps
 Web services API available
 Syslog message logging
 Firmware Updates: Via Web GUI

DIMENSIONS/POWER

Height: 1 RU, 1.72" (44 mm)
 Width: 1 RU, 17.2" (437 mm)
 Depth: 14.6" (370 mm)
 Power: 100-240 VAC 50/60 Hz
 36-72 VDC
 Supply Options: Single AC Power Supply (Standard)
 Dual AC Power Supply
 Single DC Power Supply

ENVIRONMENTAL CONDITIONS

Operating Temp: 0° to 50°C
 Storage Temp: -40°C to 65°C
 Relative Operating Humidity: <95% (non-condensing)