

DefendItYourself.com

MODEL **NC328-VDZ**

Camera

Image Sensor 1/2.5" Progressive Scan CMOS

Min. Illumination 0.01 Lux @ (F1.2, AGC On), 0.0 Lux with IR
0.014 Lux @ (F1.4, AGC On), 0.0 Lux with IR

Shutter Speed 1/3 s to 1/100,000 s

Lens 2.8 - 12mm @ F1.4 Motorized Zoom

Lens Mount M14

Day & Night IR Cut Filter With Auto Switch

Digital Noise Reduction 3D DNR

Wide Dynamic Range 120dB

Compression Standard

Video Compression H.265+ / H.264 / MJPEG

H.265 Type Main Profile

Video Bit-Rate 32 Kbps - 16 Mbps

Audio Compression G.711 / G.722.1 / G.726 / MP2L2

Image

Max. Resolution 3840 x 2160

Frame Rate 50 Hz: 20 FPS (3840x2160), 25 FPS (2560x1920, 2048x1536, 1920x1080)
60 Hz: 20 FPS (3840x2160), 30 FPS (2560x1920, 2048x1536, 1920x1080)

Image Enhancement BLC, 3D DNR, ROI

Image Setting Rotate Mode, Saturation, Brightness, Contrast, Sharpness

Day/Night Switch Auto / Schedule / Triggered by Alarm In

Network

Network Storage NAS (Support NFS, SMB/CIFS), ANR

Alarm Trigger Intrusion Detection, Line Crossing Detection, Motion Detection, Tampering Alarm

Protocols TCP/IP, HTTP, DHCP, DNS, DDNS, RTP, RTSP, PPPoE, SMTP, NTP

Standard ONVIF, PSIA, CGI, ISAPI

General One-key reset, Dual stream, Privacy mask, User Authentication, Watermark

General

Operating Conditions -30°C ~ 60°C (-22°F ~ 140°F)

Power Supply 12VDC, PoE (802.3af)

Power Consumption Max. 11.5W

Ingress Protection IP67

IR Range Approx. 100 FT

Dimension 6.04" x 5.24"

Weight 5 LBS