

# Operating Instructions

## — UL Listed Mechanical Locks —

### SAFE COMBINATION INSTRUCTIONS

Each AMSEC safe is professionally hand-crafted with quality materials and is equipped with a precision-quality, high-security combination lock. To become familiar with the lock, operate the lock (as outlined below) several times before closing the door and locking the safe.

To unlock the safe, turn the dial in the direction of the arrow for each number, stopping at the opening index mark located at the top (12 o'clock position) of the dial ring. You must dial the combination precisely without backing up. (See figure A).



#### STEP 1

Turn the dial **LEFT** (counter clockwise), stopping when the 1st number comes to the opening index mark the 4th time.



#### STEP 2

Turn the dial **RIGHT** (clockwise), stopping when the 2nd number comes to the opening index mark the 3rd time.



#### STEP 3

Turn the dial **LEFT** (counter clockwise), stopping when the 3rd number comes to the opening index mark the 2nd time.



#### STEP 4

Turn the dial slowly to the **RIGHT** (clockwise) until it stops. Turn the handle and open the door.




Figure A

**TO LOCK:** Close the door and turn the handle. Turn the dial to the LEFT (counter clockwise) at least 4 full revolutions.

**KEY LOCKING DIAL (OPTIONAL):** Set the combination lock on "0". Using the key found in the bag hanging on the handle of the safe, turn the key to the left (counterclockwise) approx. 1/2 turn to lock. To unlock, turn the key to the right until it stops and remove. Dial the combination as instructed above.



American Security Products Co. | 11925 Pacific Avenue, Fontana, CA 92337

Main: 951.685.9680 | Fax: 951.685.9685 | [www.amsecusa.com](http://www.amsecusa.com)