

# DVR-4CH-H265-BP

4-Channel CCTV  
H.265 Compression  
DVR System

# blupont



## Professional-Grade DVR Storage & Playback Systems



Staff & worker  
security



Warehouse &  
factory security



Remote &  
out of bounds



Residential  
security

## Advanced H.265 Multi-Channel DVR System With 4K Video Output

Need an advanced DVR system using the most up to date video compression H.265 codecs for faster and more fluid video playback?

The exciting range of **Blupont™** 4, 8 and 16-channel RCA BNC analog CCTV DVRs are the ideal partner for your professional CCTV applications. With a choice of 4K HDMI resolution output together with legacy VGA output, the DVRs come with a choice of storage up to around 8TB\*

With advanced smart recording and playback both from iOS™, Android™ and of course the DVR itself, you have complete control the world over, thanks to its Ethernet (RJ45) interface connected to your existing network.

Robust Linux™ runtime for both security and privacy for your system together with flexibility for the video cameras used, including control of PTZ camera systems as standard.

Advanced motion detection, push notification and smart playback functionality means you'r always in control.

**blupont**

H.265 Faster Loading  
Smoothly Playing



High-speed broadband needed to watch high-definition monitoring

Smooth coding technology HD remote without pressure

## specifications:

4-Channel RCA BNC Analog CCTV Input

**Advanced H.265 Compression - Faster & Smoother Replay**

Embedded Linux™ runtime for secure and advanced control

**Network: Ethernet (RJ45) 10/100 Interface with DHCP**

Signal Input: x4 Analog (AHD/TVI/CVI) 1080p/720p

IP 5MP, 4MP, 3MP, 1080p, 960p, 720p

**Signal Output: Analog/AHD/CVI/TVI 2.0 or 3.0/Network**

Audio Input: 4 Channel RCA: Audio Output: 1 Channel RCA

**Alarms: Motion Detection, Recording, Push Notifications**

Recording & Playback: H.265/H.265+/H.264/H.264+ via Web (IP)

iPhone™, Android™ App or DVR Smart Playback

**PTZ: Optional control using RS485 with PELCO™ Protocol**

Display Option: VGA & HD (4K) Interfaces:

3840x2160, 2560x1440, 1920x1080, 1280x1024 @ 30Hz etc

**On Screen Display: Title, Video Loss, Zones, Motion Detection**

Storage Capability: Up to 8TB Max (2.5/3.5 SATA Interface)\*

**USB Interfaces: x2 USB 2.0 for control or additional data backup**

Power Consumption: DC12V < 6W (without fitted HDU)\*

**Dimensions (WxDxH): 260mm x 215mm x 43mm**

Working Environment: -10C to 55C approx (nominal)



\*Hard Disk Not Supplied  
Custom Options Available