

# EcoNetCab

Co-Location  
2 & 4 compartment  
Enclosures



Available in 2 or 4 compartment  
42U 1000mm deep

### FREE FITTED ENCLOSURE ACCESSORIES:

- ROOF-MOUNTED FAN TRAY
- CASTORS & JACKING FEET
- FITTED VENTED SHELF(S)
- SECURING BOLTS



Server, Blade or UPS



PBX, CCTV or VoIP



Data patching and multi-media

## Securely sharing computing and networking resources in one locale

Are you looking to host different company computing resources in one location? Or, do you wish to allow staff to only access non-critical devices on a regular basis?

The new LMS Data CoLo (co-location) series of 2 and 4-compartment enclosures fit the need for co-hosting or restricted access maintenance and operation of your system resources such as computing, CCTV, VoIP or secure applications.

Available as a standard 42U vertical design and with a deep, 1000mm form-factor means you can accommodate a host of rack-mount servers, SAN, UPS and other rack-mount computing devices, all with the knowledge of ease-of-maintenance and of course, cool airflow throughout the chassis. A single, fitted 4-way Fan Tray is located in the raised roof space to help vent away heated air generated within.

And with robust security for each compartment, fitted vented shelving and transportation accessories, means the LMS Data CoLo range is your ideal choice for your multi access needs.

## specifications:

### 42u CAB-CL-42U-6100-2

2-compartment CoLo design

**All compartments independently bolted to aid security**  
600x1000x2050mm (inc. castors)

**ETSI 19" front/rear profiles (adjustable)**

Universal server design

**Up to 1000Kg static load bearing\*\***

Front & rear mesh high venting doors (lockable)

**Left/right hinged front/rear doors**

Removable side panels for easy access

**U-numbered uprights for alignment**

Multiple cable entry glands

**Fitted 4-way fan tray in roof space**

**Fitted vented shelf**

Powder-coated RAL 9005 finish

## specifications:

### 42u CAB-CL-42U-6100-4

4-compartment CoLo design

**All compartments independently bolted to aid security**  
600x1000x2050mm (inc. castors)

**ETSI 19" front/rear profiles (adjustable)**

Universal server design

**Up to 1000Kg static load bearing\*\***

Front & rear mesh high venting doors (lockable)

**Left/right hinged front/rear doors**

Removable side panels for easy access

**U-numbered uprights for alignment**

Multiple cable entry glands

**Fitted 4-way fan tray in roof space**

**Fitted vented shelf**

Powder-coated RAL 9005 finish

\* server product may need specific vendor mount rails  
\*\* actual loading dependent on weight distribution

enclosures - power distribution - cabling

EcoNetCab

LMS DATA

Copyright 2013 LMS Data Group  
All trademarks acknowledged E&OE.  
Details subject to change



Corporate & government  
secure access



ISP co-hosting & shared  
resource access



CCTV and VoIP and  
backup scheduling