

EcoNetCab

Universal Server,
SAN & UPS
Enclosures



27U, 42U & 47U X1000MM VERSIONS

FREE FITTED ENCLOSURE ACCESSORIES:
FRONT CABLE MANAGEMENT*
ROOF-MOUNTED FAN TRAY
CASTORS & JACKING FEET
FITTED VENTED SHELF
SECURING BOLTS



Server, Blade or VM machine



Switch, Routing or PBX



UPS and Power Generation

Redefining quality ergonomics for your server and networking needs

Looking to house your rack-mount server, SAN, UPS or other networking devices?

Rack-mount servers and computers are becoming more popular in all sizes of business, both public and private sector. LMS Data are market leaders in provide high-quality, best-in-class ergonomics and security for all your server, networking and broadcasting needs and the new EcoNetCab server range continues this tradition.

Offering a range of class-leading heights, ideal from the smallest IT 'closet' up to large-scale enterprise and data centres with the option for secure access, co-containment and multiple door option fittings, the LMS Data EcoNetCab is your ideal partner for your server, SAN and rack-mount UPS containment.

specifications:

27u CAB-FE-27U-6100

600x1000x1370mm (inc.castors)

ETSI 19" front/rear profiles (adjustable)

800Kg static load bearing

Front mesh high venting door (lockable)

Left or right hinged front/rear doors

Removable side panels for easy access

U-numbered uprights for alignment

Multiple cable entry gland plates

Powder-coated RAL 9005 finish

specifications:

27u CAB-FE-27U-8100*

800x1000x1370mm (inc.castors)

ETSI 19" front/rear profiles (adjustable)

800Kg static load bearing

Front mesh high venting door (lockable)

Left or right hinged front/rear doors

Removable side panels for easy access

U-numbered uprights for alignment

Multiple cable entry gland plates

Powder-coated RAL 9005 finish

specifications:

42u CAB-FE-42U-6100

600x1000x2050mm (inc.castors)

ETSI 19" front/rear profiles (adjustable)

800Kg static load bearing

Front mesh high venting door (lockable)

Left or right hinged front/rear doors

Removable side panels for easy access

U-numbered uprights for alignment

Multiple cable entry gland plates

Powder-coated RAL 9005 finish

specifications:

42u CAB-FE-42U-8100*

800x1000x2050mm (inc.castors)

ETSI 19" front/rear profiles (adjustable)

800Kg static load bearing

Front mesh high venting door (lockable)

Left or right hinged front/rear doors

Removable side panels for easy access

U-numbered uprights for alignment

Multiple cable entry gland plates

Powder-coated RAL 9005 finish

enclosures - power distribution - cabling



Copyright 2013 LMS Data
All trademarks acknowledged. E&OE
Specifications subject to change



Flat-pack only

specifications:

47u CAB-FE-47U-6100*

600x1000x2320mm (inc.castors)

ETSI 19" front/rear profiles (adjustable)

800Kg static load bearing

Front mesh high venting door (lockable)

Left or right hinged front/rear doors

Removable side panels for easy access

U-numbered uprights for alignment

Multiple cable entry gland plates

Powder-coated RAL 9005 finish

Flat-pack only

specifications:

47u CAB-FE-47U-8100*

800x1000x2320mm (inc.castors)

ETSI 19" front/rear profiles (adjustable)

800Kg static load bearing

Front mesh high venting door (lockable)

Left or right hinged front/rear doors

Removable side panels for easy access

U-numbered uprights for alignment

Multiple cable entry gland plates

Powder-coated RAL 9005 finish