

4 Port 10/100M POE Switch + 1 Port 10/100M Uplink Ports

Network Media	10BASE-T: UTP category 3, 4, 5 cable (maximum 100m) EIA/TIA-568 100Ω STP (maximum 100m) 100BASE-TX: UTP category 5, 5e cable (maximum 100m) EIA/TIA-568 100Ω STP (maximum 100m)
Interface	5 10/100Mbps RJ45 Ports AUTO Negotiation/AUTO MDI/MDIX
PoE Ports (RJ45)	4 (1~4ports)
Backbound Bandwidth	1.6Gbps
Internal Power Supply	Internal Power supply adapter (AC 100~240V, 52V/1.05A input)
Transmission Method	Store-And-Forward
Advanced Functions	Compatible With IEEE 802.3af /at Compliant PDs Priority Function Mac Address Auto-Learning And Auto-Aging IEEE802.3x Flow Control For Full-Duplex Mode And Backpressure For Half-Duplex Mode
Package Contents	Quick installation Guide, Power Cable
Consumption	User Port Power: >16~30Watts /3~600ma, 55W output total
Environment	Operating Temperature: 0°C~40°C 32°F~104°F) Storage Temperature: -40°C~70°C (-40°F~158°F) Operating Humidity: 10%~90% non-condensing Storage Humidity: 5%~90% non-condensing



© 2021 Dynamode
Details correct at going to press. E&OE
All Trademarks Acknowledged
Further product details available from
www.dynamode.com