

INSTRUCTIONS FOR USE

STEP 1 (Clean) :-

- Clean the KEG and other accessories with warm water

STEP 2 (Fix the hose):-

- Cut the hose according to the height of the KEG making sure that the hose reaches the bottom of the KEG
- Fix the hose at the bottom of the black cap
- Take the remaining hose and fix one end of the hose to the pouring tap
- Insert the 2 fasters on the hose with one end close to the tap and tighten with a screw driver
- Fix the other end of the hose to the black cap
- Pull the 2nd fastener close to the black cap and tighten
- Make sure both ends of the hose are tightly fastened

STEP 3 (Fix the regulator):-

- Ensure regulator is in 'OFF' position
- Fix the regulator on the brass thread on the black cap
- Fasten the co2 cartridge on the regulator and tighten, this will puncture the CO2 cartridge (ensure that the regulator is in 'OFF' position)

STEP 4 (Tap your drink):-

- Keep the keg in the freezer for a few minutes without the cap so the keg is chilled from within
- Loosely fasten the cap and release some CO2 inside the keg which will release any oxygen remaining in the keg
- Open the cap and fill the keg with your drink
- Align the threads and fasten the cap
- Slowly increase the pressure on the regulator to 3-5 psi and pour your drink

Safety Warnings:-

- Keep away from children
- Never point cartridge to face
- Do not heat the cartridge to over 50 degrees
- The cartridge will get punctured when tightened to the regulator, do not unscrew the cartridge unless empty
- Exterior of the cartridge may become frozen when in use, please do not touch as your finger may stick to the cartridge
- Please note that the CO2 cartridges are not allowed to be carried on any flight.

Please visit our FAQ's on WWW.KEGWERKS.IN for further information.