

# FMS-1655R

## Remote Display

### Data Sheet



FMS-1655R with Safety Halo™

Triatek's FMS-1655R Remote Display is powered by its corresponding FMS-1655 Room Pressure Controller, and provides a secondary location to monitor critical environments.

Applications for the FMS-1655R include isolation rooms with adjacent anterooms, nurse's station displays for a single isolation room or patient room, surgical suites with dual displays (one inside the controlled space, one outside), and remotely displaying the room temperature or relative humidity.

The FMS-1655R features a user-friendly touchscreen with modern graphics, intuitive menus, and Triatek's signature color-coded Safety Halo™ edge lighting.

It instantly updates as room conditions change and immediately alerts staff of unsafe conditions with both visual and audible alarms.

#### FEATURES INCLUDE

- Full-color, user-friendly touchscreen
- Available in surface or stainless steel flush mount
- Intuitive control menus, easy to set up
- Safety Halo™ edge lighting for 180° visibility
- Up to 10 user passwords
- Powered by the FMS-1655
- Audible and visual alarms
- Display any one of the six parameters monitored by the companion FMS-1655
- Status-only display mode available

# FMS-1655R

## Remote Display

### Data Sheet

FMS-1655R Specifications	
Monitoring Capacity	One of six parameters monitored at FMS-1655
Interface Cable	Belden 3107A, 22 AWG
Power Supply	12-36Vdc, 150mA (supplied by FMS-1655)
LCD Size and Type	3.2" diagonal, transmissive
Resolution	240 pixels by 320 pixels, portrait
Viewing Area	50.60 mm x 66.80 mm
Color Depth	18-bit or 262K colors
Backlight Color	White LED
Luminous Intensity	min 2500 cd/m <sup>2</sup>
FMS-1655R Mounting Options	Plastic surface mount Stainless steel flush mount
Plastic Surface Mount Housing Dimensions	3"W x 5"H x 1.13"D
Stainless Steel Flush Mount Housing Dimensions	5.1"W x 8"H x .75"D
Operating Temperature	32°F to 125 °F
Operating Humidity	10% to 95% RH, non-condensing
Agency Listings	FCC Part 15
Password Protection	Up to 10 user passwords
Alarm Indication	Safety Halo™ 180° visual indication Industry standard status colors with action icons
Alarm Silence	Touchscreen, auto-reset

Product specifications are subject to change without notice. Triatek is a registered trademark of Triatek LLC. 10212013



Color-coded screens immediately alert users of the room status



Sleek stainless steel flush mount, perfect for busy hallways



The flush mount option is great for shallow wall cavities

## Part Number Guide

FMS1655R -

### Mounting Option

F = Flush Mount

S = Surface Mount

