


HMS-1655L

Fume Hood Controller

Data Sheet



HMS-1655L with Safety Halo™

Triatek's HMS-1655L Fume Hood Controller controls and monitors a fume hood's airflow and exhaust, providing scientists with confidence that they are protected from toxic vapors and dusts during experiments.

It utilizes a closed-loop system to regulate air entering and exiting the fume hood and communicates with a sidewall sensor and sash position sensor to monitor the airflow with a higher degree of reliability.

It features a user-friendly touchscreen with modern graphics and intuitive menus, and the innovative Safety Halo™ edge lighting allows users to easily monitor any fume hood from across the lab. It instantly updates as conditions change, and immediately alerts users of unsafe conditions with both visual and audible alarms.

The home screen simultaneously displays the current fume hood status, sash height, face velocity, and air flow rate.

The HMS-1655L provides more confidence than systems reporting on sash height alone which do not account for obstructions in front of an open sash.

FEATURES INCLUDE

- LonWorks® compatible for easy BAS integration
- Safety Halo™ edge lighting
- User-friendly touchscreen with intuitive menus
- Bold, modern graphics
- Visual and audible alarms
- Easy to install and customize
- Password protection with four access levels
- Multiple alarms for sidewall and sash position sensors
- Zone Presence Sensor support
- Non-volatile memory
- Multi-trigger emergency purge option
- Available in plastic surface mount

HMS-1655L

Fume Hood Controller

Data Sheet

HMS-1655L Specifications	
Face Velocity Range	0-200 fpm
Alarm Range	0-200 fpm
Display Range	0-200 fpm
Accuracy	±2 fpm at 60-140 fpm, ±5 fpm outside this range
Sidewall Sensor	Digital ultra-low differential pressure
Sash Position Sensor	Vertical height up to 50"
Control Resolution	±2 fpm
Control Capability	Sash position with sidewall sensing feedback for closed-loop Control
Analog Inputs	4 universal (4-20mA, 0-5Vdc, 0-10Vdc)
Digital Inputs	4 active-high or active-low (0-5Vdc or 0-24Vdc)
Relay Outputs	4 sets of N.O. contacts (1A at 24Vdc)
Communication Protocols	LonWorks® FTT-10A
Operating Temperature	32° to 125° F operating
Operating Humidity	10-95% relative humidity, non-condensing
Exterior Dimensions	Plastic surface mount housing: 3" W x 5" H x 1.13" D
Mounting Styles	Surface (no cutout required)
Agency Listings	SGS Listing FCC Part 15, ICES-003
Power Requirements	24Vac ±10%, 30VA
Password Protection	Up to 10 user passwords with 4 access levels
Display	18-bit (262K) color TFT, 3.2" diagonal, resistive touchscreen, 2500 cd/m ²
Alarm Indication	Safety Halo™ 180° visual indication Industry standard status colors with action icons
Alarm Silence	Touchscreen, auto-reset

Product specifications are subject to change without notice. Triatek is a registered trademark of Triatek LLC.



Part Number Guide

HMS1655L - -

Sensor Type

1 = single smart sidewall sensor
2 = dual smart sidewall sensor

Options for Sash Sensor

blank = sash sensor not included
S = sash position sensor included



Normal Mode



Warning Mode



Alarm Mode

