



HOW TO INSTALL TROLMASTER CONTROLLER WITH PANTHRX SERIES FOR COMMERCIAL GROW SPACE

Trolmaster® is a registered trademark of the TrolMaster Agro Instruments Co., Ltd. (Trolmaster). This Document is not endorsed or approved by TrolMaster Agro Instruments Co., Ltd. This Document is for Instruction purpose only.

Step 1: Choose Right Controller & Accesories

1. Trolmaster Hydro-X Environment Control System (HCS-1)

Required QTY – 1



**Controls total 512 light
(256 lights per Channel)**

2. Lighting Control Adapter F (LMA-14)

Required QTY – 1 (if using 1 per channel – 256 lights)

Required QTY – 2 (If using 2 channels – 512 lights)



3. RJ12 to 3.5 Jack Extension Cable Set (ECS-2)

Required per Light



Each Light Require 1 ECS-2 Connector


Step 2 : Install Trolmaster HCS-1 on wall using instruction

- 1) Install Trolmaster HCS-1 on wall with power plug
- 2) Connect LMA-14 Adapter to Line 1
- 3) Connect 3 in 1 sensor to sensor on trolmaster controller



Step 3 : Connectivity of ECS-2 Cable Set to LMA-14 Connector

1) Plug 3.5mm Jack with Block terminal and another end of RJ12 connection to splitter.



Step 4 : Connectivity of ECS-2 Cable Set

- 1) Connect two-screw terminal block to connect to loose wires on the PanthrX II or PanthrX Mini II.




Black Wire of Fixture (DIM +) to (+) of Terminal Block

White Wire of Fixture (DIM -) to (-) of Terminal Block

NOTE: Use Screw Driver to Connect with Terminal Block

DIAGRAM



Trolmaster® is a registered trademark of the TrolMaster Agro Instruments Co., Ltd. (Trolmaster). This Document is not endorsed or approved by TrolMaster Agro Instruments Co., Ltd. This Document is for Instruction purpose only.