

MANUFACTURER: Creceer Lighting Inc

MODEL NUMBER: PanthrX Mini

PICTURE OF LUMINAIRE



TEST

Photosynthetically active radiation (PAR) & Electrical Measurement

TESTING CONDITIONS

Fixture is tested in Grow Tent as shown below. Ambient Temperature is at 25° C.

TEST METHOD

Ambient temperature is set to 25° C and is measured from the center of the fixture, within 1ft from the outside of the fixture. The sample is stabilized for at least 30mins and longer as necessary for the sample to achieve stabilization.

TEST EQUIPMENT

Asensetek Lighting Passport Pro, LLI 2M Sphere, Digital Power Meter

ELECTRICAL SUMMARY

Input Power: *319.86 W*

Input Current (Amp): *2.66 Amps*

Input Voltage (VAC/60HZ): *120.00 V*

Input Power Factor: *0.99*

Current ATHD @ 120V (%): *5%*

PHOTOMETRIC SUMMARY

Total PPF (umol/s): 793.25 umol/s

Total Lumens: 49,959.76 lm


Efficiency (umol/J): 2.48 umol/J

CCT color Temperature: 3600K

SPECTRUM COMPARED TO MCCREES ACTION SPECTRUM


Original Spectrum

Ref.: McCREEs ACTION SPECTRUM



CIE1931 & CIE1976 CHARTS

CIE1931



CIE1976

