

RIKON

18" Professional Model # 10-347

* Featuring NEW Patent Pending Technology



*** New**
Spring Loaded Tool-Less Guide System

No tools needed to quickly adjust your guide bearings



*** New**
Quick Adjust 6" Tall Rip Fence System

Easily adjust your fence to either side of the blade




Cast Iron Wheels

Precision balanced, cast iron wheels. Door has micro-switch for safety




Quick Adjust Trunnion System

Solid cast table trunnion with large handle for table tilting adjustments



Foot Brake With Micro-switch

Provides additional safety to quickly stop the machine



Specifications

MOTOR		BLADE		OVERALL DIMENSIONS	
Horsepower	4 HP	Width	1/4" - 1-3/8"	Height	84"
Amps	16	Length	162"	Width	39"
Volts	220V, 60Hz, 1Ph	Includes	162" x 3/4" x 4 TPI, Reg.	Depth	30"
Speed Range	4,920 FT/MIN			Base Size	29-15/16" x 18-1/8" x 2-7/16"
CUTTING CAPACITY		TABLE		Dust Port	2@4"
Height	19"	Size	25" x 19"	Net Weight	498 lbs.
Width	17-1/2"	Left Tilt	-5°	Gross Weight	536 lbs.
		Right Tilt	45°	Shipping Width	35-1/4"
		Miter Gauge Slot	(1) 3/4" x 3/8"	Shipping Depth	25"
		Height to Floor	33-1/2"	Shipping Height	84-1/4"
		Fence Size	18-3/4" x 1-3/4" x 6"		

Call today for more information **877-884-5167**
or visit **www.rikontools.com** for a dealer near you!



RIKON

18" Professional

Model # 10-347



BANDSAW BLADES


Length	Width	Gauge	TPI	Style	Item No.
162"	3/8"	.025"	4	Hook Tooth	19-1801
162"	1/2"	.025"	3	Hook Tooth	19-1802
162"	5/8"	.025"	3	Hook Tooth	19-1803
162"	3/4"	.032"	3	Hook Tooth	19-1804
162"	1"	.035"	2	Hook Tooth	19-1805

Accessories



12-201

LED Gooseneck
Worklight with
Magnetic Base and
Magnetic Clip




13-912

3/4" x 3/8"
T-Slot Miter Gauge



13-345

Mobility Kit



C10-326

10 Pack Guide
Bearings



C10-396

Replacement Table
Insert



C10-999

Replacement Drive
Belt

Call today for more information **877-884-5167**
or visit **www.rikontools.com** for a dealer near you!

