

## AGD1 Dial Indicators

- Graduation: Inch: 0.001" Metric: 0.01mm
- Dial face dia. 1.65"
- Jeweled bearings
- Lug Back



ASIMETO

Range	Dial Reading	Range per Rev	Stem Dia.	Code No.	Price \$
0 - 0.25"	0-100	0.1"	3/8	7401061	49.31

## Dial Indicators

- Reverse counter
- Stainless steel components
- Rotating bezel with clamp
- Lugback (1/4" hole)
- Interchangeable point
- Conforms to AGD 2 standards



Travel Range	Dial Reading	Grad.	Dial Colour	Code No.	Price \$
1/2"	0-100"	0.001"	White	200718	32.26
1"	0-100"	0.001"	White	200720	27.00
1"	0-50"	0.0005"	White	200755	36.99
2"	0-100"	0.001"	White	200725	71.19

### Magnetic Back

For AGD2 series	200722	16.45
-----------------	--------	-------

## Holding Bars

- Scaloped design
- Black oxide coating for corrosion resistance



ASIMETO

Shank Dia.	Length	Code No.	Price \$
1/4 x 1/2	4"	7500213	27.94
9mm x 9mm	50mm	7500210	30.75
9mm x 9mm	100mm	7500212	28.69

## Test Indicators

- Jeweled bearings
- Inch units come with 3/8" & 8mm dovetail stems
- Easy to read yellow face
- 32mm and 40mm face diameters available



Vertical

### Full Set

- Carbide tipped point  
Dia.  $\phi$ 2mm
- Steel point  
Dia.  $\phi$ 1mm
- Stem Dia.  
Metric 4mm  
Inch 0.157"
- Holding Bar  
Metric 9x9x100mm  
Inch 0.25"x0.5"x4"
- Swivel Clamp  
Metric for  $\phi$ 4mm, &  $\phi$ 8mm Dia.  
Inch for 3/8", & 0.157" Dia.

### Base Set

- Stem Dia.  
Metric  $\phi$ 8mm  
Inch  $\phi$ 3/8"
- Knurled Clamping Ring
- Wrench

Horizontal

Grad.	Range	Dial Reading	Accuracy	Type	Code No.	Price \$
<b>Inch</b>						
0.0001"	0.008"	0-4-0	$\pm$ 0.0001"	Horizontal	7501783	125.50
0.0001"	0.008"	0-4-0	$\pm$ 0.0001"	Vertical	7501785	127.30
0.0005"	0.03"	0-15-0	$\pm$ 0.0005"	Horizontal	7501733	108.30
0.0005"	0.03"	0-15-0	$\pm$ 0.0005"	Vertical	7501735	103.02
0.0005"	0.03"	0-15-0	$\pm$ 0.0005"	Horizontal/Long Point (1.25")	7501736	158.90
<b>Inch Sets</b>						
0.0001"	0.008"	0-4-0	$\pm$ 0.0001"	Horizontal	7501787	134.90
0.0005"	0.03"	0-15-0	$\pm$ 0.0005"	Horizontal	7501738	175.44

## AGD2 Dial Indicators

- Dial face dia. 2.20"
- Lug Back
- Easy to read dial face



7402265

7402267

ASIMETO

Range	Grad.	Dial Reading	Range per Rev.	Stem Dia.	Code No.	Price \$
<b>Inch</b>						
0-0.05"	0.0001"	0-50-0	0.01"	3/8	7402013	112.66
0-0.05"	0.0001"	10-0	0.01"	3/8	7402011	145.77
0-0.05"	0.0001"	0-5-0	0.01"	3/8	7402015	156.67
0-0.25"	0.0005"	0-25-0	0.05"	3/8	7402065	46.08
0-0.5"	0.0005"	0-50	0.05"	3/8	7402125	46.08
0-1"	0.0005"	0-50	0.05"	3/8	7402265	47.41
0-0.25"	0.001"	0-100	0.1"	3/8	7402061	40.66
0-0.25"	0.001"	0-50-0	0.1"	3/8	7402063	68.20
0-0.5"	0.001"	0-100	0.1"	3/8	7402121	42.37
0-0.5"	0.001"	0-50-0	0.1"	3/8	7402123	54.18
0-1"	0.001"	0-100	0.1"	3/8	7402261	39.52
0-1"	0.001"	0-50-0	0.1"	3/8	7402263	54.37
0-2"	0.001"	0-100	0.1"	3/8	7402511	93.86
<b>Metric</b>						
0-10mm	0.01mm	0-100	1mm	3/8	7402101	105.94
0-25mm	0.01mm	0-50-0	1mm	3/8	7402253	186.84
<b>IP54 Water Proof</b>						
0-0.4"	0.001"	0-100	0.1"	3/8	7402267	101.64
0-0.4"	0.0005"	0-50	0.05"	3/8	7402269	101.64

## Test Indicators and Sets

- Available in bezel or dial
- Contact point adjustable through 230°
- Fully jeweled movement
- Extremely light contact pressure
- Clear, easy to read, white face
- Dovetails on top and back for all-around positioning
- Sets include 5/32" and 3/8" mounting shanks and 3/8" bar



Dial Dia. (in.)	Grad. (in.)	Range (in.)	Reading (in.)	Point Length (in.)	Code No.	Price \$
1.250"	0.0005"	0.030"	0-15-0	0.700"	200730	64.38