

# **XK760X**





## **VSM CERAMICS**



		Materials	Features
Grain type	Ceramic		
Bonding	Full-resin bonded	Unalloyed — steel	Medium Medium pressure coated
Colour	Red-violet	STAINLESS	pressure coated
Backing	X-Polyester	STEEL	$\Diamond$
Flexibility	Sturdy	Stainless Wood Steel	Also for wet grinding
Production width	1,480 mm	_	

Self-sharpening ceramic-grain abrasive belt as an all-rounder for processing unalloyed steel, for example when descaling slabs or for flat grinding of steel plates. Also suitable for wet grinding, since it is oil- and water-resistant.


#### Grit sizes1):

16	20	24	30	36	40	50	60	80	100	120	150	180	220	240	280	320	360	400	500	600	800	1000	1200	

#### **Benefits**

- > Self-sharpening effect results in an extremely high stock removal rate thanks to constant recreation of sharp grain points
- > High wear resistance
- > Optimised price-performance ratio

## Wear pattern of the grain



The microcrystalline structure of the **VSM CERAMICS** series enables a much more subtle breaking down of the grain and constantly produces new sharp edges.

### VSM · Vereinigte Schmirgelund Maschinen-Fabriken AG

Siegmundstraße 17 · 30165 Hanover · Germany T +49 511 3526 479 · F +49 511 3521 315 sales@vsmabrasives.com · www.vsmabrasives.com











