# REVIVAL CYCLES

### 14-100 LI OPTIMIZED REG/REC FOR TYPE-B CHARGING SYSTEMS SYSTEMS W/ MO.UNIT

The14-100 Lithium Optimized TYPE-B Regulator/Rectifier provides a maximum charge voltage of 14.2V and is suitable for any Lead Acid, AGM, or Lithium motorcycle battery. The 14-100 connectors are intended to be plug and play with a specific OEM harness. We recommend removing these connectors and using a modern sealed connector suitable for high amperages. The APEX 2.8 connectors on our site that are ideal for this application.

If possible, before performing this installation, test the original charging system to confirm that the stator is in optimal operating condition. Eliminating this as a variable will simplify troubleshooting during the Reg/Rec install.

There is no substitute for knowledge or experience. Familiarize yourself with the bike, don't make assumptions and when in doubt hire a professional.

#### **RED TO BATTERY+**

LG GREEN TO GROUND -

# BLACK TO AUX 1 OUT YELLOWS TO STATOR WHITE TO FIELD COIL

**SM GREEN TO FIELD COIL** 

## WIRE GAUGE MAX AMPERAGE QUICK REFERENCE

AWG	<b>AMPS</b>
22	5
22 20 18 16 14	10 15 20 30
18	15
16	20
14	30
12	40
6	100+



