

RUST CONVERTER INSTRUCTIONS

GEMPLERS

DESCRIPTION:

Rust converter instantly bonds with rust, stops its growth, transforms it into a non-rusting paintable surface, and prevents future rust formation. It provides an excellent primer coating for the application of quality oil-based paints. Surfaces protected with this primer and an oil-based paint system resist the effects of weather, rain, sun and salt spray without peeling or cracking. This easy-to-use product is the first step in providing long-term protection of steel and iron surfaces. Ideal for use on machinery, equipment, structures, vehicles, railings, marine applications and more. Non-flammable, water-based, low VOC, non-toxic, and emits no harmful fumes.

BRUSH ON

DIRECTIONS:

SURFACE PREPERATION: Remove large rust and scale particles with a wire brush or sandpaper. Clean the surface thoroughly to remove dirt, dust and grease.

APPLICATION: Shake or stir well before using. This product is ready-to-use. Do not dilute. Apply this product using a brush or roller. Apply a second coat to ensure complete transformation of rusty surfaces.

COVERAGE: 500 square feet per gallon on a smooth, non-porous surface. Irregular, porous or textured surfaces may require more product.

DRYING TIME: The resulting coat will dry to a smooth, dark finish in 20 minutes. Apply a second coat to ensure complete transformation of rusty surfaces. Allow 48 hours of cure time before the application of the finished paint coat. For long-lasting protection of iron surfaces, the cured rust converter should be sealed with two coats of a high quality oil-based paint. No other primer is required.

CLEAN-UP: Application equipment should be cleaned immediately with soap and water.

****IMPORTANT:** Do NOT return unused material to original containers. **

NOTE: This product has a nine-month shelf life.



SPRAYABLE

DIRECTIONS:

SURFACE PREPARATION: Remove large rust and scale particles with a wire brush or sandpaper. Clean the surface thoroughly to remove dirt, dust and grease.

APPLICATION: Shake or stir well before using. Do not dilute. Do not apply this product if the surface temperatures are below 50°F. Spray with an airless sprayer with 0.11-0.13 tip at 800-1200 psi. Adjust pressure as needed. One gallon will cover 200-300 square feet on a smooth, non-porous surface. Irregular, porous or textured surfaces may require more product. **DRYING**

TIME: The resulting coat will dry to a smooth, dark finish in 20 minutes. Apply a second coat to ensure complete transformation of rusty surfaces. Allow 48 hours of



cure time before the application of the finished paint coat. For long-lasting protection of iron surfaces, the cured rust converter coating should be sealed with two coats of a high quality oil-based paint. No other primer is required.

CLEAN-UP: Application equipment should be cleaned immediately with soap and water.

****IMPORTANT:** Do NOT return unused material to original containers. **

NOTE: This product has a nine-month shelf life.

AEROSOL

DIRECTIONS:

SURFACE PREPARATION: For best results prepare surface by brushing the loose rust from the surface using a wire brush or sand paper. Clean the surface to remove grease and grime.

APPLICATION: Shake well before use. Hold can 8-12 inches from surface and spray a thin coat onto the surface. After the surface has dried, it will turn black. Then apply a second thin coat. Allow 48 hours to completely cure before painting while protecting it from rain or dew. For long lasting protection, seal with two coats of a high quality oil based paint. Do not apply if the surface temperature is below 50°F or above 90°F. Store in a cool dry place, protected from freezing or temperatures above 100°F.

****CAUTION:** Use with adequate ventilation. Intentional misuse by concentrating and inhaling the product can be harmful or fatal. Extremely flammable aerosol. Causes serious eye irritation. May cause drowsiness or dizziness. Keep away from heat/sparks/open flames/hot surfaces. No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Avoid breathing gas. Wash thoroughly after handling. Use only outdoors or in a well-ventilated area. Wear eye/face protection. Store in a well-ventilated place. Keep container tightly closed. Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 49°C/120°F. Dispose of contents/container in accordance with local/regional/national/international regulations.

NOTE: This product has a nine-month shelf life.



MORE QUESTIONS?

Contact our Product Support Specialists @
1(800) 382-8473