



## HUSQVARNA T535i XP® - Skin Only

For professional users who want a lightweight, extremely easy-to-use top handle chainsaw with high performance. Perfect for arborists. A robust chainsaw with excellent ergonomics, high performance and high chainspeed.



### **Gear up for nonstop operation**

Our battery accessories allow you to carry on and get the job done as quickly and efficiently as possible.

### **savE™**

Choose between normal or savE™ mode, depending on conditions, for maximum power or maximum runtime. Either way, you'll always get a perfect result.

### **Inertia chain brake**

Effective inertia-activated chain brake



### **Flip-up tank cap**

The flip-up tank cap is easy to open.



## FEATURES

- Increased safety, inertia activated chain brake
- Choose savE™ mode for maximum runtime
- Gear up for nonstop operation
- The flip-up tank cap is easy to open.
- High chain speed
- The retaining function prevents losing the bar nuts.
- Petrol performance
- In-house developed brushless motor provides a high and consistent torque.
- Allows you to quickly switch the same battery between different product applications and keep working.
- Rope eyelet in rear handle
- The key pad is very easy to operate.
- Quick connection to the climbing harness

Technical specifications	
<b>BATTERY</b>	
Battery charger model name	--
Battery model name	--
Battery type	Li-Ion
Battery voltage	36 V
<b>CAPACITY</b>	
Chain speed at max power	20 m/s
<b>DIMENSIONS</b>	
Article gross weight	3932 g
Article net weight	3120 g
Bar length (inch)	12"
Product size height	23 cm
Product size length	26.5 cm
Product size width	21.5 cm
Recommended bar length, max	35 cm
Recommended bar length, min	25 cm
Size	12"
Weight (excl. battery and cutting equipment)	2.4 kg
<b>ENGINE</b>	
Motor type	BLDC (brushless)
<b>EQUIPMENT</b>	
Bar mount	Small
Bar mount type	Small
Chain type	SP21G
Chainsaw sub-group	Tree-care saws
Gauge	1.1 mm
Handle type	Standard
Pitch	.325" mini
Sprocket type	Spur 7
<b>LUBRICANTS</b>	
Oil pump capacity Max	8 ml/min
Oil pump type	Automatic
Oil tank volume	0.2 l
Power source	Battery
Power/fuel type	Battery
<b>SOUND AND NOISE</b>	
Sound power level, guaranteed (LWA)	106 dB(A)
Sound power level, measured	104 dB(A)
Sound pressure level at operators ear	93 dB(A)
<b>VIBRATIONS</b>	
Daily Vibration (Aeqv)	2.5 m/s <sup>2</sup>
Daily Vibration Exposure (A8)	1.25 m/s <sup>2</sup>
Daily Vibration Time (Time factor)	2 h
Equivalent vibration level (ahv, eq) front handle	2 m/s <sup>2</sup>
Equivalent vibration level (ahv, eq) rear handle	2.4 m/s <sup>2</sup>
<b>PACKAGING</b>	
Packaging height	269 mm
Packaging length	472 mm
Packaging volume	0.032 m <sup>3</sup>
Packaging volume	31.996 dm <sup>3</sup>
Packaging width	252 mm
Quantity in Master pack	1