

# Aftek Flex Pro MS Sealant

**RLA Polymers Pty Ltd** 

Chemwatch: 13-64945 Version No: 2.1.1.1 Safety Data Sheet according to WHS and ADG requirements Chemwatch Hazard Alert Code: 0

Issue Date: **13/09/2018**Print Date: **18/09/2018**S.GHS.AUS.EN

# SECTION 1 IDENTIFICATION OF THE SUBSTANCE / MIXTURE AND OF THE COMPANY / UNDERTAKING

#### **Product Identifier**

Product name	Aftek Flex Pro MS Sealant
Synonyms	620527
Other means of identification	Not Available

# Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses Sealing compound.

#### Details of the supplier of the safety data sheet

Registered company name	RLA Polymers Pty Ltd
Address	215 Colchester Road Kilsyth VIC 3137 Australia
Telephone	+61 3 9728 1644
Fax	+61 3 9728 6009
Website	www.rlagroup.com.au
Email	sales@rlagroup.com.au

# Emergency telephone number

Association / Organisation Not Available		Not Available
	Emergency telephone numbers	+61 3 9728 1644 (RLA Group Technical Manager) business hours
	Other emergency telephone numbers	132766 (Security Monitoring Service)

#### **SECTION 2 HAZARDS IDENTIFICATION**

# Classification of the substance or mixture

#### NON-HAZARDOUS CHEMICAL. NON-DANGEROUS GOODS. According to the WHS Regulations and the ADG Code.

Poisons Schedule	Not Applicable	
Classification [1]	Acute Aquatic Hazard Category 3, Chronic Aquatic Hazard Category 3	
Legend:	1. Classified by Chemwatch; 2. Classification drawn from HSIS; 3. Classification drawn from Regulation (EU) No 1272/2008 - Annex VI	
Label elements		
Hazard pictogram(s)	Not Applicable	
SIGNAL WORD	NOT APPLICABLE	
Hazard statement(s)		
mazaru statement(s)		
H412	Harmful to aquatic life with long lasting effects.	
Precautionary statement(s) Pr	revention	
P273	Avoid release to the environment.	

# Precautionary statement(s) Response

Not Applicable

# Precautionary statement(s) Storage

Not Applicable

# Precautionary statement(s) Disposal

P501 Dispose of contents/container in accordance with local regulations.

Chemwatch: **13-64945** Page **2** of **7** 

Aftek Flex Pro MS Sealant

Issue Date: **13/09/2018**Print Date: **18/09/2018** 

#### **SECTION 3 COMPOSITION / INFORMATION ON INGREDIENTS**

#### **Substances**

Version No: 2.1.1.1

See section below for composition of Mixtures

#### Mixtures

CAS No	%[weight]	Name	
52829-07-9	0.1-<2.5	bis(2,2,6,6-tetramethyl-4-piperidinyl)sebacate	
54068-28-9	0.1-<1	dioctyltinbis(acetylacetonate)	

#### **SECTION 4 FIRST AID MEASURES**

#### Description of first aid measures

Eye Contact	If this product comes in contact with eyes:  • Wash out immediately with water.  • If irritation continues, seek medical attention.  • Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.
Skin Contact	If skin or hair contact occurs:  ► Flush skin and hair with running water (and soap if available).  ► Seek medical attention in event of irritation.
Inhalation	<ul> <li>If fumes, aerosols or combustion products are inhaled remove from contaminated area.</li> <li>Other measures are usually unnecessary.</li> </ul>
Ingestion	<ul> <li>Immediately give a glass of water.</li> <li>First aid is not generally required. If in doubt, contact a Poisons Information Centre or a doctor.</li> </ul>

#### Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

# **SECTION 5 FIREFIGHTING MEASURES**

#### **Extinguishing media**

- ▶ There is no restriction on the type of extinguisher which may be used.
- Use extinguishing media suitable for surrounding area.

# Special hazards arising from the substrate or mixture

Fire Incompatibility	None known.	
Advice for firefighters		
Fire Fighting	<ul> <li>Alert Fire Brigade and tell them location and nature of hazard.</li> <li>Wear breathing apparatus plus protective gloves in the event of a fire.</li> <li>Prevent, by any means available, spillage from entering drains or water courses.</li> <li>Use fire fighting procedures suitable for surrounding area.</li> </ul>	
Fire/Explosion Hazard	<ul> <li>Non combustible.</li> <li>Not considered a significant fire risk, however containers may burn.</li> </ul>	
HAZCHEM	Not Applicable	

#### **SECTION 6 ACCIDENTAL RELEASE MEASURES**

# Personal precautions, protective equipment and emergency procedures

See section 8

#### **Environmental precautions**

See section 12

#### Methods and material for containment and cleaning up

Minor Spills	Clean up all spills immediately. Avoid contact with skin and eyes. Wear impervious gloves and safety goggles. Trowel up/scrape up.
Major Spills	Minor hazard.  ► Clear area of personnel.  ► Alert Fire Brigade and tell them location and nature of hazard.  ► Control personal contact with the substance, by using protective equipment as required.

Personal Protective Equipment advice is contained in Section 8 of the SDS.

#### **SECTION 7 HANDLING AND STORAGE**

## Precautions for safe handling

Chemwatch: 13-64945 Page 3 of 7 Version No: 2.1.1.1

Aftek Flex Pro MS Sealant

Issue Date: 13/09/2018 Print Date: 18/09/2018

▶ Limit all unnecessary personal contact. Wear protective clothing when risk of exposure occurs. Safe handling Use in a well-ventilated area. Avoid contact with incompatible materials. Store in original containers. Keep containers securely sealed. Other information Store in a cool, dry, well-ventilated area. Store away from incompatible materials and foodstuff containers. Conditions for safe storage, including any incompatibilities ► Polyethylene or polypropylene container.

Suitable container

- Packing as recommended by manufacturer
- Check all containers are clearly labelled and free from leaks.

Storage incompatibility

#### **SECTION 8 EXPOSURE CONTROLS / PERSONAL PROTECTION**

#### **Control parameters**

OCCUPATIONAL EXPOSURE LIMITS (OEL)

INGREDIENT DATA

Not Available

#### **EMERGENCY LIMITS**

Ingredient	Material name	TEEL-1	TEEL-2	TEEL-3	
Aftek Flex Pro MS Sealant	Not Available	Not Available	Not Available	Not Available	
Ingredient	Original IDLH		Revised IDLH		
bis(2,2,6,6-tetramethyl- 4-piperidinyl)sebacate	Not Available		Not Available		
dioctyltinbis(acetylacetonate)	Not Available	Not Available		Not Available	

#### Exposure controls

#### Appropriate engineering controls

Engineering controls are used to remove a hazard or place a barrier between the worker and the hazard. Well-designed engineering controls can be highly effective in protecting workers and will typically be independent of worker interactions to provide this high level of protection.

The basic types of engineering controls are:

Process controls which involve changing the way a job activity or process is done to reduce the risk.

Enclosure and/or isolation of emission source which keeps a selected hazard "physically" away from the worker and ventilation that strategically "adds" and "removes" air in the work environment.

### Personal protection









#### Eye and face protection

- Safety glasses with side shields
- Chemical goggles.
- Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing the wearing of lenses or restrictions on use, should be created for each workplace or task. This should include a review of lens absorption and adsorption for the class of chemicals in use and an account of injury experience.

Skin protection Hands/feet protection See Hand protection below

Wear general protective gloves, eg. light weight rubber gloves.

No special equipment needed when handling small quantities.

**Body protection** 

See Other protection below

Other protection

OTHERWISE:

#### ▶ Overalls. Barrier cream.

► Eyewash unit.

#### Respiratory protection

Type A-P Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

Selection of the Class and Type of respirator will depend upon the level of breathing zone contaminant and the chemical nature of the contaminant. Protection Factors (defined as the ratio of contaminant outside and inside the mask) may also be important

Required minimum protection factor	Maximum gas/vapour concentration present in air p.p.m. (by volume)	Half-face Respirator	Full-Face Respirator
up to 10	1000	A-AUS / Class1 P2	-
up to 50	1000	-	A-AUS / Class 1 P2
up to 50	5000	Airline *	-
up to 100	5000	-	A-2 P2
up to 100	10000	-	A-3 P2
100+			Airline**

<sup>\* -</sup> Continuous Flow \*\* - Continuous-flow or positive pressure demand

# Page 4 of 7

Issue Date: 13/09/2018 Print Date: 18/09/2018 Aftek Flex Pro MS Sealant

chemicals, K = Ammonia(NH3), Hg = Mercury, NO = Oxides of nitrogen, MB = Methyl bromide, AX = Low boiling point organic compounds(below 65 degC)

# **SECTION 9 PHYSICAL AND CHEMICAL PROPERTIES**

#### Information on basic physical and chemical properties

Appearance	Various colour paste with characteristic odour; not miscible with water.		
Physical state	Free-flowing Paste	Relative density (Water = 1)	1.6
Odour	Not Available	Partition coefficient n-octanol / water	Not Available
Odour threshold	Not Available	Auto-ignition temperature (°C)	Not Available
pH (as supplied)	Not Applicable	Decomposition temperature	Not Available
Melting point / freezing point (°C)	Not Available	Viscosity (cSt)	Not Available
Initial boiling point and boiling range (°C)	Not Available	Molecular weight (g/mol)	Not Applicable
Flash point (°C)	Not Available	Taste	Not Available
Evaporation rate	Not Available	Explosive properties	Not Available
Flammability	Not Available	Oxidising properties	Not Available
Upper Explosive Limit (%)	Not Available	Surface Tension (dyn/cm or mN/m)	Not Available
Lower Explosive Limit (%)	Not Available	Volatile Component (%vol)	2
Vapour pressure (kPa)	Not Available	Gas group	Not Available
Solubility in water (g/L)	Immiscible	pH as a solution (1%)	Not Available
Vapour density (Air = 1)	Not Available	VOC g/L	Not Available

#### **SECTION 10 STABILITY AND REACTIVITY**

Reactivity	See section 7
Chemical stability	Product is considered stable and hazardous polymerisation will not occur.
Possibility of hazardous reactions	See section 7
Conditions to avoid	See section 7
Incompatible materials	See section 7
Hazardous decomposition products	See section 5

# **SECTION 11 TOXICOLOGICAL INFORMATION**

#### Information on toxicological effects

Inhaled	The material is not thought to produce adverse health effects or irritation of the respiratory tract (as classified by EC Directives using animal models). Nevertheless, good hygiene practice requires that exposure be kept to a minimum and that suitable control measures be used in an occupational setting.		
Ingestion	The material has <b>NOT</b> been classified by EC Directives or other classification systems as "harmful by ingestion". This is because of the lack of corroborating animal or human evidence.		
Skin Contact	The material is not thought to produce adverse health effects or skin irritation following contact (as classified by EC Directives using animal models).  Nevertheless, good hygiene practice requires that exposure be kept to a minimum and that suitable gloves be used in an occupational setting.		
Eye	Although the material is not thought to be an irritant (as classified by EC Directives), direct contact with the eye may produce transient discomfort characterised by tearing or conjunctival redness (as with windburn).		
Chronic	Long-term exposure to the product is not thought to produce chronic effects adverse to the health (as classified by EC Directives using animal models); nevertheless exposure by all routes should be minimised as a matter of course.		
Aftek Flex Pro MS Sealant	TOXICITY	IRRITATION	
	Not Available	Not Available	
	TOXICITY	IRRITATION	
bis(2,2,6,6-tetramethyl-	Dermal (rabbit) LD50: >3100 mg/kg <sup>[2]</sup>	Eye (rabbit): Severe	
4-piperidinyl)sebacate	Inhalation (rat) LC50: 0.5 mg/l/4H <sup>[2]</sup>	Skin (rabbit): Irritant	
	Oral (rat) LD50: 3700 mg/kg <sup>[2]</sup>	Skin sensitisation: Negative	
dioctyltinbis(acetylacetonate)	TOXICITY	IRRITATION	
	dermal (rat) LD50: >2000 mg/kg <sup>[1]</sup>	Not Available	
Legend:	Value obtained from Europe ECHA Registered Substance     data extracted from RTECS - Register of Toxic Effect of cher	s - Acute toxicity 2.* Value obtained from manufacturer's SDS. Unless otherwise specified	

Chemwatch: 13-64945 Page 5 of 7 Issue Date: 13/09/2018
Version No: 2.1.1.1 Print Date: 18/09/2018

#### Aftek Flex Pro MS Sealant

# BIS(2,2,6,6-TETRAMETHYL-4-PIPERIDINYL)SEBACATE

Asthma-like symptoms may continue for months or even years after exposure to the material ends. This may be due to a non-allergic condition known as reactive airways dysfunction syndrome (RADS) which can occur after exposure to high levels of highly irritating compound. Main criteria for diagnosing RADS include the absence of previous airways disease in a non-atopic individual, with sudden onset of persistent asthma-like symptoms within minutes to hours of a documented exposure to the irritant. Other criteria for diagnosis of RADS include a reversible airflow pattern on lung function tests, moderate to severe bronchial hyperreactivity on methacholine challenge testing, and the lack of minimal lymphocytic inflammation, without eosinophilia.

Contact allergies quickly manifest themselves as contact eczema, more rarely as urticaria or Quincke's oedema. The pathogenesis of contact

eczema involves a cell-mediated (T lymphocytes) immune reaction of the delayed type. Other allergic skin reactions, e.g. contact urticaria, involve

#### DIOCTYLTINBIS(ACETYLACETONATE)

inflammation, without eosinophilia.

The following information refers to contact allergens as a group and may not be specific to this product.

antibody-mediated immune reactions.

No significant acute toxicological data identified in literature search.

Acute Toxicity	0	Carcinogenicity	0
Skin Irritation/Corrosion	0	Reproductivity	0
Serious Eye Damage/Irritation	0	STOT - Single Exposure	0
Respiratory or Skin sensitisation	0	STOT - Repeated Exposure	0
Mutagenicity	0	Aspiration Hazard	0

Legend:

★ - Data available but does not fill the criteria for classification

Data available to make classification

Not Available to make classification

#### **SECTION 12 ECOLOGICAL INFORMATION**

#### Toxicity

Aftek Flex Pro MS Sealant	ENDPOINT	TEST DURATION (HR)	SPECIES	VALUE	SOURCE
	Not Available	Not Available	Not Available	Not Available	Not Available
bis(2,2,6,6-tetramethyl- 4-piperidinyl)sebacate	ENDPOINT	TEST DURATION (HR)	SPECIES	VALUE	SOURCE
	LC50	96	Fish	4.4mg/L	2
	EC50	72	Algae or other aquatic plants	1.1mg/L	2
	NOEC	72	Algae or other aquatic plants	0.05mg/L	2
	ENDPOINT	TEST DURATION (HR)	SPECIES	VALUE	SOURCE
dioctyltinbis(acetylacetonate)	EC50	48	Crustacea	>22mg/L	2
	NOEC	48	Crustacea	>=22mg/L	2

# Legend:

Extracted from 1. IUCLID Toxicity Data 2. Europe ECHA Registered Substances - Ecotoxicological Information - Aquatic Toxicity 3. EPIWIN Suite V3.12 (QSAR) - Aquatic Toxicity Data (Estimated) 4. US EPA, Ecotox database - Aquatic Toxicity Data 5. ECETOC Aquatic Hazard Assessment Data 6. NITE (Japan) - Bioconcentration Data 7. METI (Japan) - Bioconcentration Data 8. Vendor Data

 $Harmful\ to\ aquatic\ organisms,\ may\ cause\ long-term\ adverse\ effects\ in\ the\ aquatic\ environment.$ 

Do NOT allow product to come in contact with surface waters or to intertidal areas below the mean high water mark. Do not contaminate water when cleaning equipment or disposing of equipment wash-waters.

Wastes resulting from use of the product must be disposed of on site or at approved waste sites.

# Persistence and degradability

Ingredient	Persistence: Water/Soil	Persistence: Air
bis(2,2,6,6-tetramethyl- 4-piperidinyl)sebacate	HIGH	нівн

# Bioaccumulative potential

Ingredient	Bioaccumulation
bis(2,2,6,6-tetramethyl- 4-piperidinyl)sebacate	HIGH (LogKOW = 6.5004)

#### Mobility in soil

Ingredient	Mobility
bis(2,2,6,6-tetramethyl- 4-piperidinyl)sebacate	LOW (KOC = 609900)

#### **SECTION 13 DISPOSAL CONSIDERATIONS**

#### Waste treatment methods

Product / Packaging disposal

- ▶ Recycle wherever possible or consult manufacturer for recycling options.
- ► Consult State Land Waste Management Authority for disposal.
- Bury residue in an authorised landfill.

# Page 6 of 7 Aftek Flex Pro MS Sealant

Issue Date: 13/09/2018 Print Date: 18/09/2018

▶ Recycle containers if possible, or dispose of in an authorised landfill.

#### **SECTION 14 TRANSPORT INFORMATION**

#### **Labels Required**

Marine Pollutant	NO
HAZCHEM	Not Applicable

Land transport (ADG): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Air transport (ICAO-IATA / DGR): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Sea transport (IMDG-Code / GGVSee): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Transport in bulk according to Annex II of MARPOL and the IBC code

Not Applicable

#### **SECTION 15 REGULATORY INFORMATION**

Safety, health and environmental regulations / legislation specific for the substance or mixture

BIS(2,2,6,6-TETRAMETHYL-4-PIPERIDINYL)SEBACATE(52829-07-9) IS FOUND ON THE FOLLOWING REGULATORY LISTS

Australia Hazardous Chemical Information System (HCIS) - Hazardous Chemicals

Australia Inventory of Chemical Substances (AICS)

DIOCTYLTINBIS(ACETYLACETONATE)(54068-28-9) IS FOUND ON THE FOLLOWING REGULATORY LISTS

Not Applicable

#### **National Inventory Status**

National Inventory	Status
Australia - AICS	N (dioctyltinbis(acetylacetonate))
Canada - DSL	N (dioctyltinbis(acetylacetonate))
Canada - NDSL	N (dioctyltinbis(acetylacetonate); bis(2,2,6,6-tetramethyl-4-piperidinyl)sebacate)
China - IECSC	N (dioctyltinbis(acetylacetonate))
Europe - EINEC / ELINCS / NLP	N (dioctyltinbis(acetylacetonate))
Japan - ENCS	N (dioctyltinbis(acetylacetonate))
Korea - KECI	N (dioctyltinbis(acetylacetonate))
New Zealand - NZIoC	Υ
Philippines - PICCS	N (dioctyltinbis(acetylacetonate))
USA - TSCA	N (dioctyltinbis(acetylacetonate))
Legend:	Y = All ingredients are on the inventory N = Not determined or one or more ingredients are not on the inventory and are not exempt from listing(see specific ingredients in brackets)

#### **SECTION 16 OTHER INFORMATION**

Revision Date	13/09/2018
Initial Date	13/09/2018

#### Other information

Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

The SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering controls must be considered.

#### **Definitions and abbreviations**

PC-TWA: Permissible Concentration-Time Weighted Average

PC-STEL: Permissible Concentration-Short Term Exposure Limit

IARC: International Agency for Research on Cancer

ACGIH: American Conference of Governmental Industrial Hygienists

STEL: Short Term Exposure Limit

TEEL: Temporary Emergency Exposure Limit。

IDLH: Immediately Dangerous to Life or Health Concentrations

OSF: Odour Safety Factor

NOAEL: No Observed Adverse Effect Level

LOAEL: Lowest Observed Adverse Effect Level

TLV: Threshold Limit Value

LOD: Limit Of Detection OTV: Odour Threshold Value

BCF: BioConcentration Factors

BEI: Biological Exposure Index

This document is copyright.

Apart from any fair dealing for the purposes of private study, research, review or criticism, as permitted under the Copyright Act, no part may be reproduced by any process without written permission from CHEMWATCH.

Chemwatch: 13-64945 Page 7 of 7 Issue Date: 13/09/2018 Version No: 2.1.1.1 Print Date: 18/09/2018

# Aftek Flex Pro MS Sealant

TEL (+61 3) 9572 4700.