Revision Date: 01/09/21

Revision: 3

Supersedes Date: 23/06/2011



## SAFETY DATA SHEET LIGHT FAST STAINS

## SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

#### 1.1. Product identifier

Product Name Monster Premiere Wood Stain

## 1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Consumer / Private Households / General Public

## 1.3. Details of the supplier of the safety data sheet

Supplier:

Monstercolors 28 rogart Street Glasgow G40 2 AA United Kingdom

Info@monstercolors.com www.monstercolors.com

1.4. Emergency telephone number

(0141)328 4034 (during office hours)

## **SECTION 2: HAZARDS IDENTIFICATION**

## 2.1. Classification of the substance or mixture

Classification (EC 1272/2008)

Physical Flam. Liq. 2 - H225

Health Acute Tox. 4 - H302;Acute Tox. 4 - H312;Acute Tox. 4 - H332;Eye Irrit. 2 - H319;STOT

Single 2 - H371

Environmental Not classified.

**Classification (1999/45)** Xn;R20/21/22, R68/20/21/22. Xi;R36. F;R11.

## 2.2. Label elements

Contains: METHANOL Label In Accordance With (Ec) No. 1272/2008







Signal Word	Danger
Hazard Statements	

H225 Highly flammable liquid and vapour.

H302 Harmful if swallowed.
 H312 Harmful in contact with skin.
 H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H371 May cause damage to organs .

**Precautionary Statements** 

P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

P260 Do not breathe dust/fume/gas/mist/vapours/spray.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P305+351+338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P313 Get medical advice/attention.

**Supplementary Precautionary Statements** 

P233 Keep container tightly closed.

P240 Ground/bond container and receiving equipment.

P241 Use explosion-proof electrical/ventilating/lighting/.../equipment.

P242 Use only non-sparking tools.

P243 Take precautionary measures against static discharge.
P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P264 Wash ... thoroughly after handling.

P270 Do not eat, drink or smoke when using this product.
P271 Use only outdoors or in a well-ventilated area.

P301+312 IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell.

P302+352 IF ON SKIN: Wash with plenty of soap and water.

P303+361+353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin

with water/shower.

P304+340 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for

breathing.

P309+311 IF exposed or if you feel unwell: Call a POISON CENTER or doctor/physician.

P312 Call a POISON CENTER or doctor/physician if you feel unwell.

P322 Specific measures (see ... on this label).

P330 Rinse mouth.

P337 If eye irritation persists:

P363 Wash contaminated clothing before reuse.

P370+378 In case of fire: Use ... for extinction.

P403+235 Store in a well-ventilated place. Keep cool.

P405 Store locked up.

P501 Dispose of contents/container to ...

## 2.3. Other hazards

## **SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS**

## 3.2. Mixtures

4-HYDROXY-4-METHYLPENTAN-2-ONE 10-30%

CAS-No.: 123-42-2 EC No.: 204-626-7

Classification (EC 1272/2008)

Eye Irrit. 2 - H319

Classification (67/548)

Xi;R36

ETHANOL 60-100%

CAS-No.: 64-17-5 EC No.: 200-578-6

Classification (EC 1272/2008) Classification (67/548)

Flam. Liq. 2 - H225 F;R11

METHANOL 5-10%

CAS-No.: 67-56-1 EC No.: 200-659-6

Classification (EC 1272/2008)

Flam. Liq. 2 - H225

Acute Tox. 3 - H301

Acute Tox. 3 - H311

Acute Tox. 3 - H331

STOT Single 1 - H370

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16

## **SECTION 4: FIRST AID MEASURES**

#### 4.1. Description of first aid measures

#### **General Information**

NOTE! Keep affected person away from heat, sparks and flames! Move the exposed person to fresh air at once. Get medical attention if any discomfort continues.

#### Inhalation.

Move the exposed person to fresh air at once. For breathing difficulties oxygen may be necessary. If breathing stops, provide artificial respiration. Keep the affected person warm and at rest. Get prompt medical attention.

#### Ingestion

DO NOT INDUCE VOMITING! Remove victim immediately from source of exposure. Rinse mouth thoroughly. Provide rest, warmth and fresh air. Get medical attention immediately! If vomiting occurs, keep head low so that stomach content doesn't get into the lungs.

#### Skin Contact

Remove affected person from source of contamination. Remove contaminated clothing. Wash the skin immediately with soap and water. Get medical attention if irritation persists after washing.

#### **Eye Contact**

Make sure to remove any contact lenses from the eyes before rinsing. Promptly wash eyes with plenty of water while lifting the eye lids. Continue to rinse for at least 15 minutes. Contact physician if irritation persists.

#### 4.2. Most important symptoms and effects, both acute and delayed

## 4.3. Indication of any immediate medical attention and special treatment needed

## **SECTION 5: FIREFIGHTING MEASURES**

## 5.1. Extinguishing media

## **Extinguishing Media**

Fire can be extinguished using: Foam. Dry chemicals, sand, dolomite etc.

## 5.2. Special hazards arising from the substance or mixture

## 5.3. Advice for firefighters

#### Special Fire Fighting Procedures

Avoid breathing fire vapours. Cool containers exposed to flames with water until well after the fire is out. Keep run-off water out of sewers and water sources. Dike for water control.

## SECTION 6: ACCIDENTAL RELEASE MEASURES

## 6.1. Personal precautions, protective equipment and emergency procedures

## 6.2. Environmental precautions

## 6.3. Methods and material for containment and cleaning up

Extinguish all ignition sources. Avoid sparks, flames, heat and smoking. Ventilate. Clean-up personnel should use respiratory and/or liquid contact protection. Absorb in vermiculite, dry sand or earth and place into containers.

## 6.4. Reference to other sections

## **SECTION 7: HANDLING AND STORAGE**

## 7.1. Precautions for safe handling

Avoid spilling, skin and eye contact. Keep away from heat, sparks and open flame. Ventilate well, avoid breathing vapours. Use approved respirator if air contamination is above accepted level. Use explosion proof electric equipment.

#### 7.2. Conditions for safe storage, including any incompatibilities

Flammable/combustible - Keep away from oxidisers, heat and flames. Store in tightly closed original container in a dry, cool and well-ventilated place. Keep in original container.

## Storage Class

Flammable liquid storage.

## 7.3. Specific end use(s)

## SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

## 8.1. Control parameters

Name	STD	TWA	- 8 Hrs	STEL - 15 Min		Notes
4-HYDROXY-4-METHYLPENTAN-2-ONE	WEL	50 ppm	241 mg/m3	75 ppm	362 mg/m3	
ETHANOL	WEL	1000 ppm	1920 mg/m3			
METHANOL	WEL	200 ppm	266 mg/m3	250 ppm	333 mg/m3	

WEL = Workplace Exposure Limit.

## **Ingredient Comments**

WEL = Workplace Exposure Limits

## 8.2. Exposure controls

## **Protective Equipment**





#### **Engineering Measures**

Provide adequate general and local exhaust ventilation.

## Respiratory Equipment

Respiratory protection must be used if air contamination exceeds acceptable level.

#### **Hand Protection**

Use protective gloves.

## **Eye Protection**

Use approved safety goggles or face shield.

#### Other Protection

Wear appropriate clothing to prevent any possibility of liquid contact and repeated or prolonged vapour contact.

#### **Hygiene Measures**

DO NOT SMOKE IN WORK AREA! Wash at the end of each work shift and before eating, smoking and using the toilet. Wash promptly with soap & water if skin becomes contaminated. Promptly remove any clothing that becomes contaminated. Use appropriate skin cream to prevent drying of skin. When using do not eat, drink or smoke.

## **SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES**

## 9.1. Information on basic physical and chemical properties

**Appearance** Coloured liquid Colour Varying 78

Initial Boiling Point and Boiling

Range:

Flash Point (°C) 12

9.2. Other information

Volatile Organic Compound (VOC) 810 g/litre

## **SECTION 10: STABILITY AND REACTIVITY**

## 10.1. Reactivity

## 10.2. Chemical stability

Stable under normal temperature conditions.

## 10.3. Possibility of hazardous reactions

## 10.4. Conditions to avoid

Avoid heat. Avoid contact with oxidisers or reducing agents.

#### 10.5. Incompatible materials

## 10.6. Hazardous decomposition products

Fire creates: Toxic gases/vapours/fumes of: Carbon monoxide (CO). Carbon dioxide (CO2).

#### **SECTION 11: TOXICOLOGICAL INFORMATION**

## 11.1. Information on toxicological effects

#### **General Information**

Prolonged and repeated contact with solvents over a long period may lead to permanent health problems.

#### Inhalation

Vapours may cause headache, fatigue, dizziness and nausea. Vapour may irritate respiratory system or lungs.

#### Ingestion.

Harmful: may cause lung damage if swallowed. Pneumonia may be the result if vomited material containing solvents reaches the lungs. Narcotic effect.

#### Skin Contact

Acts as a defatting agent on skin. May cause cracking of skin, and eczema. Prolonged or repeated exposure may cause severe irritation.

#### Eye Contact

Irritating to eyes. Vapour or spray may cause temporary (reversible) eye damage.

## Route of entry

Inhalation. Ingestion. Skin and/or eye contact.

#### **Target Organs**

Respiratory system, lungs

#### **Medical Symptoms**

High concentrations of vapours may irritate respiratory system and lead to headache, fatigue, nausea and vomiting.

#### **SECTION 12: ECOLOGICAL INFORMATION**

#### **Ecotoxicity:**

The product components are not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.

## **12.1. Toxicity**

## 12.2. Persistence and degradability

#### 12.3. Bioaccumulative potential

#### 12.4. Mobility in soil

#### 12.5. Results of PBT and vPvB assessment

## 12.6. Other adverse effects

## **SECTION 13: DISPOSAL CONSIDERATIONS**

## **General Information**

When handling waste, consideration should be made to the safety precautions applying to handling of the product. The packaging must be empty (drop-free, when inverted)

## 13.1. Waste treatment methods

Dispose of waste and residues in accordance with local authority requirements.

## **SECTION 14: TRANSPORT INFORMATION**

## 14.1. UN number

 UN No. (ADR/RID/ADN)
 1263

 UN No. (IMDG)
 1263

 UN No. (ICAO)
 1263

## 14.2 UN Proper Shipping Name

Proper Shipping Name PAINT OR PAINT RELATED PRODUCTS

Proper Shipping Name FLAMMABLE LIQUID, NOS

## 14.3 Transport hazard class(es)

ADR/RID/ADN Class 3

ADR/RID/ADN Class Class 3: Flammable liquids.

ADR Label No. 3
IMDG Class 3.2
ICAO Class/Division 3

**Transport Labels** 



#### 14.4. Packing group

ADR/RID/ADN Packing group 5(c)

#### 14.5. Environmental hazards

**Environmentally Hazardous Substance/Marine Pollutant** 

No.

#### 14.6. Special precautions for user

Hazard No. (ADR) 33
Tunnel Restriction Code (D/E)

## 14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

#### **SECTION 15: REGULATORY INFORMATION**

## 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### **Uk Regulatory References**

The Control of Substances Hazardous to Health Regulations 2002 (S.I 2002 No. 2677) with amendments.

## **Statutory Instruments**

The Classification, Labelling and Packaging of substances and mixtures Regulations EC 1272/2008 (CLP) and amendments

## Approved Code Of Practice

Classification and Labelling of Substances and Preparations Dangerous for Supply.

## **Guidance Notes**

Workplace Exposure Limits EH40. Introduction to Local Exhaust Ventilation HS(G)37. Spraying of Highly Flammable Liquids EH9.

## 15.2. Chemical Safety Assessment

No chemical safety assessment has been carried out.

## **SECTION 16: OTHER INFORMATION**

**Issued By** HS&E Manager.

Revision Date 01/09/21

Revision 3

Supersedes Date 23/06/2011 Safety Data Sheet Status Approved.

Risk Phrases In Full

R11 Highly flammable.

R23/24/25 Toxic by inhalation, in contact with skin and if swallowed.

R36 Irritating to eyes.

R39/23/24/25 Toxic: danger of very serious irreversible effects through inhalation, in contact with skin and if swallowed.

Hazard Statements In Full

H225 Highly flammable liquid and vapour.

H301 Toxic if swallowed.
 H311 Toxic in contact with skin.
 H319 Causes serious eye irritation.

H331 Toxic if inhaled.

H370 Causes damage to organs << Organs>>.



Page 1/11

# Safety data sheet according to 1907/2006/EC, Article 31

Printing date 25.08.2021 Revision: 03.06.2021

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier For Consumer/Private Households/General Public/Consumers
- · Trade name: Diamond Lacquer / Matt / Satin / gloss / Clear Varnish Topcoat
- · 1.2 Relevant identified uses of the substance or mixture and uses advised against Surface Coating
- · Application of the substance / the mixture Surface Coating
- · 1.3 Details of the supplier of the safety data sheet
- · Supplier:

MONSTERCOLORS 28 ROGART STREET GLASGOW G40 2AA

**UNITED KINGDOM** 

TEL: +44 (0) 141 328 4034

EMAIL: info@monstercolors.com

- · Further information obtainable from: info@monstercolors.com
- · 1.4 Emergency telephone number: +44 (0)141 328 4034 (business hours)

## **SECTION 2: Hazards identification**

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272 /2008

Flam. Lig. 3 H226 Flammable liquid and vapour.

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2 H319 Causes serious eye irritation.

STOT SE 3 H335 May cause respiratory irritation.

STOT RE 2 H373 May cause damage to the hearing organs through prolonged or repeated exposure.

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008 The product is classified and labelled according to the CLP regulation.
- · Hazard pictograms







GHS02

502 GHS07

GHS08

- · Signal word Warning
- Hazard-determining components of labelling: Xylene (mix)
- · Hazard statements

H226 Flammable liquid and vapour.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H335 May cause respiratory irritation.

H373 May cause damage to the hearing organs through prolonged or repeated exposure.

(Contd. on page 2)

Printing date 25.08.2021 Revision: 03.06.2021

(Contd. of page 1)

· Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

P241 Use explosion-proof [electrical/ventilating/lighting] equipment.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with

water [or shower].

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

· Additional information:

Contains 2-butanone oxime, methyl methacrylate. May produce an allergic reaction.

- · 2.3 Other hazards
- · Results of PBT and vPvB assessment

· PBT:	
108-88-3	Toluene
· vPvB:	

108-88-3 Toluene

## SECTION 3: Composition/information on ingredients

- · 3.2 Chemical characterisation: Mixtures
- · Description: Mixture of substances listed below with nonhazardous additions.

· Dangerous components:		
CAS: 1330-20-7 EINECS: 215-535-7 Reg.nr.: 01-2119488216-32-xxxx	Xylene (mix)  ◆ Flam. Liq. 3, H226; ◆ STOT RE 2, H373; Asp. Tox. 1, H304; ◆ Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335	>25-≤50%
CAS: 100-41-4 EINECS: 202-849-4 Reg.nr.: 01-2119489370-35	ethylbenzene  Flam. Liq. 2, H225; STOT RE 2, H373; Asp. Tox. 1, H304; Acute Tox. 4, H332	>2.5- ≤10%
CAS: 108-65-6 EINECS: 203-603-9 Reg.nr.: 01-2119475791-29	2-methoxy-1-methylethyl acetate  Flam. Liq. 3, H226;  STOT SE 3, H336	>2.5- ≤10%
CAS: 100-42-5 EINECS: 202-851-5 Reg.nr.: 01-2119457861-32-XXXX	styrene Flam. Liq. 3, H226; Repr. 2, H361d; STOT RE 1, H372; Asp. Tox. 1, H304; Nature Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335; Aquatic Chronic 3, H412	≤1%
CAS: 108-88-3 EINECS: 203-625-9 Reg.nr.: 01-2119471310-51-xxxx	Toluene Flam. Liq. 2, H225; Repr. 2, H361d; STOT RE 2, H373; Asp. Tox. 1, H304; Skin Irrit. 2, H315; STOT SE 3, H336; Aquatic Chronic 3, H412 PBT; vPvB	≤1%
CAS: 96-29-7 EINECS: 202-496-6 Reg.nr.: 01-2119539477-28	2-butanone oxime • Carc. 2, H351; • Eye Dam. 1, H318; • Acute Tox. 4, H312; Skin Sens. 1, H317	<i>≤</i> 1%
CAS: 80-62-6 EINECS: 201-297-1 Reg.nr.: 01-2119452498-28-xxxx	methyl methacrylate  Flam. Liq. 2, H225; Skin Irrit. 2, H315; Skin Sens.  1, H317; STOT SE 3, H335	<i>≤</i> 1%

· Additional information: For the wording of the listed hazard phrases refer to section 16.

Printing date 25.08.2021 Revision: 03.06.2021

(Contd. of page 2)

## **SECTION 4: First aid measures**

- · 4.1 Description of first aid measures
- · General information: remove any clothing soiled by the product.
- · After inhalation:

In case of unconsciousness place patient stably inside position for transportation.

Supply fresh air; consult doctor in case of case of complaints.

· After skin contact:

Immediately wash with water and soap and rinse thoroughly. Remove contaminated clothing. Immediately rinse with water.

· After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

· After swallowing:

Do not induce vomiting; call for medical help immedately and show safety datasheet or label.

- · 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.
- · 4.3 Indication of any immediate medical attention and special treatment neededTreat symptomatically.

## **SECTION 5: Firefighting measures**

- · 5.1 Extinguishing media
- · Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- · For safety reasons unsuitable extinguishing agents: Water with full jet
- · 5.2 Special hazards arising from the substance or mixture

During heating or in case of fire poisonous gases are produced.

- · 5.3 Advice for firefighters
- · Protective equipment:Mount respiratory protective device.

## **SECTION 6: Accidental release measures**

· 6.1 Personal precautions, protective equipment and emergency procedures

Mount respiratory protective device.

Wear protective equipment. Keep unprotected persons away.

6.2 Environmental precautions:

Prevent seepage into sewage system, workpits and cellars.

Do not allow to enter sewers/ surface or ground water.

· 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatome it, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according titem 13.

Ensure adequate ventilation.

· 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

## **SECTION 7: Handling and storage**

· 7.1 Precautions for safe handling

Keep receptacles tightly sealed.

Ensure good ventilation/extraction at the workplace

Prevent formation of aerosols.

Hygiene measures:

Wash hands before breaks and at the end of workday.

· Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.

(Contd. on page 4)

Printing date 25.08.2021 Revision: 03.06.2021

(Contd. of page 3)

Protect against electrostatic charges.

Keep respiratory protective device available.

- · 7.2 Conditions for safe storage, including any inco mpatibilities
- Storage
- · Requirements to be met by storerooms and receptacles:

Materials such as cleaning rags, paper wipes and protective clothing, which are contaminated with the product may spontaneously self-ignite some hours later To avoid the risk of fires, all contaminated materials should be [stored in purpose-built containers or immetal containers with tight-fitting self-closing lids.] or [laid out flat in a single layer to dry] or [placed in a metal container soaked with water] or [washedout well with warm soapy water before disposal.] Contaminated materials should be removed from the workplace at the end of each working day and stored outside.

- $\cdot \ \, \text{Information about storage in one common storage fa} \ \, \text{dity: Not required.}$
- · Further information about storage conditions: Keep receptacle tightly sealed and in a well-ventilited place. Keep away from heat.
- · 7.3 Specific end use(s) No further relevant information available.

		nation about design of technical facilities: No further data; see item 7.
_		imit values that require monitoring at the workplace:
	-20-7 Xylene	
WEL	Short-term \ Long-term \ Sk; BMGV	value: 441 mg/m³, 100 ppm value: 220 mg/m³, 50 ppm
100-4	11-4 ethylber	nzene
WEL		value: 552 mg/m³, 125 ppm value: 441 mg/m³, 100 ppm
		oxy-1-methylethyl acetate
WEL	Short-term \ Long-term \ Sk	value: 548 mg/m³, 100 ppm value: 274 mg/m³, 50 ppm
100-4	12-5 styrene	
	Long-term v	value: 1080 mg/m³, 250 ppm value: 430 mg/m³, 100 ppm
	38-3 Toluene	
WEL		value: 384 mg/m³, 100 ppm value: 191 mg/m³, 50 ppm
96-29	9-7 2-butano	ne oxime
OEL	Long-term v	value: 1 mg/m³, 0.3 ppm
80-62	2-6 methyl m	nethacrylate
WEL		value: 416 mg/m³, 100 ppm value: 208 mg/m³, 50 ppm
DNEL	.S	
1330	-20-7 Xylene	(mix)
Derm	al DNEL	108 mg/day (Con)
		180 mg/day (Ind)
Inhal	ative DNEL	14.8 mg/m³ (Con)

Printing date 25.08.2021 Revision: 03.06.2021

		(Col	ntd. of page
		77 mg/m³ (Ind)	
108-65-6 2		oxy-1-methylethyl acetate	
Oral	DNEL	1.67 mg/day (Con)	
Dermal	DNEL	54.8 mg/day (Con)	
		153.5 mg/day (Ind)	
Inhalative	DNEL	33 mg/m³ (Con)	
		275 mg/m³ (Ind)	
100-42-5 s	tyrene		
Oral	DNEL	2.1 mg/day (Con)	
Dermal	DNEL	343 mg/day (Con)	
		406 mg/day (Wor)	
Inhalative	DNEL	10.2 mg/m³ (Con)	
		85 mg/m³ (Wor)	
108-88-3 T	oluene	e	
Oral	DNEL	8.13 mg/day (Con)	
Dermal	DNEL	226 mg/day (Con)	
		384 mg/day (Ind)	
Inhalative	DNEL	56.5 mg/m <sup>3</sup> (Con)	
		192 mg/m³ (Ind)	
96-29-7 2-	butanc	one oxime	
Dermal	DNEL	0.78 mg/day (Con)	
		1.3 mg/day (Ind)	
Inhalative	DNEL	2.7 mg/m³ (Con)	
		9 mg/m³ (Ind)	
80-62-6 m	ethyl n	methacrylate	
Dermal	DNEL	8.2 mg/day (Con)	
		13.67 mg/day (Ind)	
Inhalative	DNEL	74.3 mg/m³ (Con)	
		208 mg/m³ (Ind)	
· PNECs			

· PNECs

CAS No. 1330-20-7 Xylene mixed isomers

- Fresh water; 0.327 mg/l
- Marine water; 0.327 mg/l
- Intermittent release; 0.327 mg/l
- STP; 6.58 mg/l
- Sediment (Freshwater); 12.46 mg/kg
- Sediment (Marinewater); 12.46 mg/kg
- Soil; 2.31 mg/kg

## · Ingredients with biological limit values:

1330-20-7 Xylene (mix)

BMGV 650 mmol/mol creatinine

Medium: urine

Sampling time: post shift

Parameter: methyl hippuric acid

- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures: Keep away from foodstuffs, beverages and feed.

(Contd. on page 6)

Printing date 25.08.2021 Revision: 03.06.2021

(Contd. of page 5)

Immediately remove all soiled and contaminated clbtng

Wash hands before breaks and at the end of work.

Store protective clothing separately.

Avoid contact with the eyes and skin.

- · Respiratory protection: When spraying the product, use a respiratory protetive device.
- · Protection of hands:

When skin exposure may occur, advice should be sould from the glove supplier on appropriate types and usage times for this product.



Protective gloves

· Eye protection:



Tightly sealed goggles

## **SECTION 9: Physical and chemical properties**

· 9.1 Information on basic physical and chemical properties

· General Information

· Appearance:

Form: Liquid

Colour: According to product specification

Odour: CharacteristicOdour threshold: Not determined.

· pH-value: Not determined.

· Change in condition

Melting point/freezing point: Undetermined.

Initial boiling point and boiling range: 136 °C

· Flash point: 24 °C

· Flammability (solid, gas): Not applicable.

· Ignition temperature: 430 °C

· Decomposition temperature: Not determined.

· Auto-ignition temperature: Product is not selfigniting.

· Explosive properties: Product is not explosive. However, formation of explosive air

vapour mixtures are possible.

· Explosion limits:

Lower: 1.1 Vol % Upper: 7 Vol %

· Vapour pressure at 20 °C: 6.7-8.2 hPa

Density at 20 °C: 0.976 g/cm³
 Relative density Not determined.

Vapour density
 Evaporation rate
 Not determined.
 Not determined.

· Solubility in / Miscibility with

water: NOT MISCIBLE

· Partition coefficient: n-octanol/water: Not determined.

(Contd. on page 7)

Printing date 25.08.2021 Revision: 03.06.2021

	(Contd. of page
<ul> <li>Viscosity:</li> <li>Dynamic at 20 °C:</li> <li>Kinematic:</li> </ul>	200 mPas Not determined.
· Solvent content: Organic solvents:	55.2 %
Solids content:	44.8 %
· 9.2 Other information	No further relevant information available.

## **SECTION 10: Stability and reactivity**

- $\cdot$  10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- · Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · 10.3 Possibility of hazardous reactions No dangerous reactions known.
- · 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products:

No dangerous decomposition products when stored and handled correctly

	SECTION	11: Toxico	logical in	nformation
--	---------	------------	------------	------------

- · 11.1 Information on toxicological effects
- · Acute toxicity Based on available data, the classification criteria are not met.

· LD/LC50 v	alues relev	vant for classification:
1330-20-7	Xylene (m	nix)
Oral	LD50	5,000 mg/kg (Rat)
Dermal	LD50	2,000 mg/kg (rbt)
Inhalative	LC50/4 h	11 mg/l (Rat)
100-41-4 €	ethylbenze	ene
Oral	LD50	3,500 mg/kg (rat)
Dermal	LD50	17,800 mg/kg (rbt)
108-65-6 2		-1-methylethyl acetate
Oral	LD50	>5,000 mg/kg (rat)
Dermal	LD50	5,000 mg/kg (Rat)
Inhalative	LC50/4 h	>10.8 mg/l (Rat)
100-42-5 s	styrene	
Oral	LD50	5,000 mg/kg (Rat)
Dermal	LD50	>2,000 mg/kg (Rat)
Inhalative	LC50/4 h	11.8 mg/l (Rat)
108-88-3 7	Toluene	
Oral	LD50	636 mg/kg (Rat)
Dermal	LD50	5,000 mg/kg (Rab)
Inhalative	LC50/4 h	20 mg/l (Rat)
96-29-7 2-	butanone	oxime
Oral	LD50	2,326 mg/kg (rat)
Dermal	LD50	1,000 mg/kg (Rab)
		200-2,000 mg/kg (rat)
		(Contd. on page 8)

Printing date 25.08.2021 Revision: 03.06.2021

Based on available data, the classification criteria

| Contd. of page 7|
| Inhalative | LC50/4 h | >4.8 mg/l (rat) |
| 80-62-6 methyl methacrylate |
| Oral | LD50 | 7,900 mg/kg (Rat) |
| Inhalative | LC50/4 h | 29.8 mg/l (Rat) |

- · Primary irritant effect:
- · Skin corrosion/irritation

Causes skin irritation.

- · Serious eye damage/irritation Causes serious eye irritation.
- · Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- · Additional toxicological information:
- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- · Germ cell mutagenicity Based on available data, the classification criteria are not met
- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- · STOT-single exposure

May cause respiratory irritation.

- · STOT-repeated exposure
- May cause damage to the hearing organs through prohged or repeated exposure.
- · Aspiration hazard Based on available data, the classification criteria are not met.

## SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.
- · 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- $\cdot$  12.4 Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water Do not allow product to reach ground water, water gurse or sewage system.

Danger to drinking water if even small quantities ak into the ground.

· 12.5 Results of PBT and vPvB assessment

· PBT: 108-88-3 Toluene

· vPvB:

108-88-3 Toluene

· 12.6 Other adverse effects No further relevant information available.

## **SECTION 13: Disposal considerations**

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbaco not allow product to reach sewage system.

- Uncleaned packaging:
- · Recommendation: Disposal must be made according to official regulators.

GB

Printing date 25.08.2021 Revision: 03.06.2021

(Contd. of page 8)

SECTION 14: Transport information	
· 14.1 UN-Number · ADR, IMDG, IATA	UN1263
<ul><li>14.2 UN proper shipping name</li><li>ADR</li><li>IMDG, IATA</li></ul>	1263 PAINT RELATED MATERIAL PAINT RELATED MATERIAL
· 14.3 Transport hazard class(es)	
· ADR, IMDG, IATA	2 Florence ble lieuvide
· Class · Label	3 Flammable liquids. 3
· 14.4 Packing group · ADR, IMDG, IATA	III
· 14.5 Environmental hazards: · Marine pollutant:	No
<ul> <li>14.6 Special precautions for user</li> <li>Hazard identification number (Kemler code):</li> <li>EMS Number:</li> <li>Stowage Category</li> </ul>	Warning: Flammable liquids. 30 F-E,S <u>-E</u> A
<ul> <li>14.7 Transport in bulk according to Annex II of Marpol and the IBC Code</li> </ul>	Not applicable.
· Transport/Additional information:	
<ul><li>ADR</li><li>Limited quantities (LQ)</li><li>Excepted quantities (EQ)</li></ul>	5L Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
<ul> <li>Transport category</li> <li>Tunnel restriction code</li> </ul>	3 D/E
<ul><li>· IMDG</li><li>· Limited quantities (LQ)</li><li>· Excepted quantities (EQ)</li></ul>	5L Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
· UN "Model Regulation":	UN 1263 PAINT RELATED MATERIAL, 3, III

## **SECTION 15: Regulatory information**

- $\cdot$  15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso categoryP5c FLAMMABLE LIQUIDS
- · Qualifying quantity (tonnes) for the application of lower-tier requirements 5,000 t
- · Qualifying quantity (tonnes) for the application of upper-tier requirements 50,000 t

(Contd. on page 10)

Printing date 25.08.2021 Revision: 03.06.2021

(Contd. of page 9)

- · National regulations:
- · Technical instructions (air):

Class	Share in %
I	0.2
NK	55.2

- · Waterhazard class: Water hazard class 2 (Self-assessment): hazardous for water.
- · 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried ot.

## **SECTION 16: Other information**

This information is based on our present knowledge lowever, this shall not constitute a guarantee formy specific product features and shall not establish degally valid contractual relationship.

- · Full text of H-Statements referred to under sections 2 and 3:
- H225 Highly flammable liquid and vapour.
- H226 Flammable liquid and vapour.
- H304 May be fatal if swallowed and enters airways.
- H312 Harmful in contact with skin.
- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H318 Causes serious eye damage.
- H319 Causes serious eye irritation.
- H332 Harmful if inhaled.
- H335 May cause respiratory irritation.
- H336 May cause drowsiness or dizziness.
- H351 Suspected of causing cancer.
- H361d Suspected of damaging the unborn child.
- H372 Causes damage to organs through prolonged or preated exposure.
- H373 May cause damage to organs through prolonged prepeated exposure.
- H412 Harmful to aquatic life with long lasting effects.
- · Department issuing SDS: Product safety department: LABORATORY
- · Contact: Health & Safety Officer
- · Abbreviations and acronyms:

RID: Règlement international concernant le transpot des marchandises dangereuses par chemin de fer (ègulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goo ds

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial C hemical Substances

ELINCS: European List of Notified Chemical Substanc es

CAS: Chemical Abstracts Service (division of the American Chemical Society)

DNEL: Derived No-Effect Level (REACH)

PNEC: Predicted No-Effect Concentration (REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 2: Flammable liquids – Category 2

Flam. Liq. 3: Flammable liquids – Category 3

Acute Tox. 4: Acute toxicity - Category 4

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Dam. 1: Serious eye damage/eye irritation – Category 1

Eye Irrit. 2: Serious eye damage/eye irritation – C ategory 2

Skin Sens. 1: Skin sensitisation - Category 1

Carc. 2: Carcinogenicity – Category 2

Repr. 2: Reproductive toxicity – Category 2

STOT SE 3: Specific target organ toxicity (single e xposure) – Category 3

STOT RE 1: Specific target organ toxicity (repeated exposure) – Category 1

STOT RF 2: Specific target organ toxicity (repeated exposure) – Category 2

Page 11/11

# Safety data sheet according to 1907/2006/EC, Article 31

Printing date 25.08.2021 Revision: 03.06.2021

Asp. Tox. 1: Aspiration hazard – Category 1 Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3

(Contd. of page 10)