

Created On: 03/20/2014 Revision Date: 02/05/2015

Version: 2.0

1. Product and Company Identification

Product Name: Miracle Bond 1350 (Part A)

Company Identification: ADHESIVES TECHNOLOGY CORP. 450 East Copans Road Pompano Beach, FL 33064

Contact Phone: 1.800.892.1880 (9:00a.m. – 5:00p.m. EST)

**Product Use:** Concrete Repair

**Emergency Phone:** 

Chem-Tel: 1.800.255.3924 (24hrs)

1.000.200.0024 (241110)

2. Hazards Identification (Part A)

**GHS Classification** 

Health	Physical	Environmental
Skin Irritant Cat 2	Not Classified	Not Classified
Eye Irritant Cat 2B		
Skin Sensitizer Cat 1B		
Carcinogen Cat 1		

GHS Label:

## Danger:



Skin Sensitizer Eye Irritant Skin Irritant



Possible Carcinogen

## **Emergency Overview**

May cause an allergic skin reaction
Causes skin and eye irritation
May cause cancer
Wash skin thoroughly after handling
Avoid breathing fume/gas/mist/vapors/spray
Wear protective gloves/ protective clothing/ eye protection/ face protection
Use outdoors or in a well-ventilated area

# **Primary Route of Exposure**

Eyes, skin and oral

#### Carcinogenicity

This product or one of its ingredients present at 0.1% or more IS listed as a carcinogen or suspect carcinogen by NTP, IARC, Prop 65 or OSHA.



Created On: 03/20/2014 Revision Date: 02/05/2015

Version: 2.0

#### 3. Composition/Information on Ingredients (Part A)

CAS Number	<u>Content</u> %	<u>Chemical Name</u>
25085-99-8	40- 70	Diglycidyl Ether of Bisphenol A
14808-60-7	0.1 – 1	Quartz Silica Sand (Crystalline Silica)
13463-67-7	1 - 5	Titanium Dioxide
107-21-1	3 - 7	Ethylene Glycol
Proprietary	15 - 30	Non – Hazardous Proprietary Ingredients
68460-21-9	7 - 15	Trimethylol Ethane Triglycidyl Ether

#### 4. First Aid Measures (Part A)

Inhalation: Move to fresh air; give oxygen if breathing is difficult. Call a physician if symptoms persist.

Eyes: Immediately flush eyes with plenty of water for at least 15 minutes. Call a physician if symptoms persist. Skin: Remove contaminated clothing. Wash with mild soap and water. Get medical attention if skin irritation or dermatitis persists.

Ingestion: Give plenty of water. DO NOT induce vomiting. Call a physician immediately.

**Other:** Referral to a physician is recommended if there is any question about the seriousness of the injury/exposure. If sensitization occurs, future contact with the material should be avoided.

#### 5. Fire Fighting Measures (Part A)

Flash Point: 149 °C (>300 °F)

Flammable Limits: N/A

#### **Extinguisher Media**

Carbon Dioxide, Dry Chemical, Water Fog

# **Unusual Fire and Explosion Hazard**

None known. Thermal Decomposition can be formed.

#### **Special Fire Fighting Procedures**

Firefighters must wear self-contained breathing apparatus and full protective clothing to prevent contact with toxic and/or irritating fumes.

#### 6. Accidental Release Measures (Part A)

### **Personal Precautions:**

Avoid all personal contact. In enclosed areas, cleanup personnel should wear self-contained breathing apparatus.

#### **Environmental Precautions**

Cover spills with sawdust, vermiculite, or other absorbent material to minimize spreading of the material before collecting.



Created On: 03/20/2014 Revision Date: 02/05/2015

Version: 2.0

#### 7. Handling and Storage (Part A)

**Handling:** Avoid contact with eyes, skin and clothing. Avoid inhalation of vapors. Use with adequate ventilation. Use appropriate personal protection equipment (Section 8). Wash thoroughly after handling.

**Storage:** Store in a cool dry place away from direct sunlight. Keep from freezing. Recommended storage temperature range in between 4 °C and 35 °C (40°F and 95° F).

\_\_\_\_\_

## 8. Exposure Control and Personal Protection (Part A)

### **Exposure Guidelines**

Component	CAS#	OSHA PEL	TLV
Titanium Dioxide	13463- 67-7	15 mg/m <sup>3</sup>	10 mg/m <sup>3</sup>
Quartz Silica Sand (Crystalline Silica)	14808- 60-7	0.1 mg/m <sup>3</sup>	0.025 mg/m <sup>3</sup>

**Engineering Measures:** Use local and general exhaust ventilation to maintain airborne concentrations below TLV. Suitable respiratory equipment should be used in cases of insufficient ventilation or where operational procedures demand it.

#### **Personal Protective Equipment**

#### **Respiratory Protection**

None normally required. Use a NIOSH approved organic vapor chemical cartridge respirator when air movement is inadequate to control vapor build-up.

#### **Eye/Face Protection**

Wear splash proof chemical goggles/ full face shield if there is a potential for splashing.

### **Skin / Body Protection**

Wear Suitable gloves (neoprene, nitrile rubber or PVC) and protective clothing to mitigate exposure.

## **Other Protective Clothing or Equipment**

Use protective clothing which is chemical resistant to this material. Safety shoes and boots should also be chemical resistant.

#### 9. Physical and Chemical Properties (Part A)

Appearance: White Paste

Evaporation Rate: N/D

Odor: Slight Odor Solubility in Water: Insoluble Specific Gravity(g/cc): 1.27

Vapor Density(air = 1): Non-volatile

Vapor Pressure: N/D

VOC Content: 60 g/l (when mixed)



Created On: 03/20/2014 Revision Date: 02/05/2015

Version: 2.0

pH: N/D Boiling Point: N/D

\_\_\_\_\_

## 10. Stability and Reactivity (Part A)

Stability: Stable

Thermal Decomposition: Can yield CO, CO<sub>2</sub> and organic Nitrogen compounds.

Incompatibility: Strong acids, peroxides, and other oxidizing agents

Conditions to avoid: Exposure to excessive heat and storage above 35°C (95°F) will shorten shelf

life.

#### 11. Toxicological Information (Part A)

#### **Acute Oral Toxicity:**

**Not Determined** 

## **Acute Dermal Toxicity:**

**Not Determined** 

## **Acute Inhalation Toxicity:**

**Not Determined** 

### **Skin Irritation:**

Irritating to skin

The product has not been tested. The statement has been derived from the properties of the individual components.

### **Eye Irritation:**

Irritating to eyes.

The product has not been tested. The statement has been derived from the properties of the individual components.

## **Respiratory Irritation:**

Inhalation of vapors or mists may cause irritation to the respiratory system.

## Sensitization:

May cause allergic skin reaction and irritation to the respiratory system.

The product has not been tested. The statement has been derived from the properties of the individual components.

# STOT - single exposure

**Not Determined** 

# STOT - Repeated Exposure

**Not Determined** 



Created On: 03/20/2014 Revision Date: 02/05/2015

Version: 2.0

#### **Carcinogenicity Classification:**

**Quartz Silica Sand (Crystalline Silica):** 

IARC Group 1: Known human carcinogen based on human evidence.

**Titanium Dioxide:** 

IARC Group 2B: Possibly carcinogenic to humans.

This product contains a chemical or chemicals known to the State of California to cause cancer, birth defects or other reproductive harm.

# 12. Ecological Information (Part A)

#### Fish:

Diglycidyl Ether of Bisphenol A:

Fathead minnow/LC50 (96hrs): >3.1mg/l

#### **Aquatic Invertebrates:**

Diglycidyl Ether of Bisphenol A:

Water Flea Daphnis/EC 50 (48hrs): > 1.4mg/l

#### Algae:

No Data Available

## Microorganisms:

Diglycidyl Ether of Bisphenol A:

Bacteria, (Growth inhibition)/IC50 (18hrs): > 42.6mg/l

#### **Mobility:**

Considering the use of the substance, it is unlikely that significant environmental exposure in the air or water will arise.

## 13. Disposal Considerations (Part A)

If the material as supplied becomes a waste, dispose in accordance with federal, state and local regulations.

## 14. Transportation Information (Part A)

This product is not regulated as a hazardous material for transportation.

## 15. Regulatory Information (Part A)

HMIS Rating	
Health	2
Flammability	1



Created On: 03/20/2014 Revision Date: 02/05/2015

Version: 2.0

Physical Hazard	0
PPE	В

## **NFPA Rating**



Hazard Rating: 0 = minimal, 1 = Slight, 2 = moderate, 3 = severe, 4 = extreme

#### **Federal Regulations**

**CERCLA RQ** 

SARA Title 311/312 Not Determined

CA Prop 65 This product contains a chemical or chemicals known to the State of

California to cause cancer, birth defects or other reproductive harm.

TSCA Listed or Exempt

State Regulations:

State RTK NJ, MA, PA

CAS# Chemical Name

25085-99-8 Diglycidyl Ether of Bisphenol A

13463-67-7 Titanium Dioxide 107-21-1 Ethylene Glycol

## 16. Other Information (Part A)

**Hazard Communication:** This SDS has been prepared in accordance with the federal OSHA Hazard Communication Standard

To the best of our knowledge, the information contained herein is accurate. However, Adhesives Technology Corp. does not assume any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.

Additional information is available upon request.



Created On: 03/20/2014 Revision Date: 02/05/2015

Version: 2.0

1. Product and Company Identification

Product Name: Miracle Bond 1350 (Part B) Product Use: Concrete Repair

**Company Identification:**ADHESIVES TECHNOLOGY CORP.

450 East Copans Road Pompano Beach, FL 33064 Contact Phone: 1.800.892.1880 (9:00a.m. – 5:00p.m. EST) Emergency Phone: Chem-Tel: 1.800.255.3924 (24hrs)

2. Hazards Identification (Part B)

**GHS Classification** 

Health	Physical	Environmental
Skin Corrosion Cat 1 Serious Eye Damage Cat 1 Reproductive toxicity Cat 2 Carcinogen Cat 1	Not Classified	Toxic to Aquatic Life Cat-2

**GHS Label:** 

Danger:



Corrosive to skin and eyes

**Skin Irritant** 

Carcinogen

Reproductive toxicity

**Emergency Overview** 

Causes skin burns

Causes severe eye damage

Suspected of damaging fertility

May cause cancer

Wash skin thoroughly after handling

Avoid breathing fume/gas/mist/vapors/spray

Wear protective gloves/ protective clothing/ eye protection/ face protection

Use outdoors or in a well-ventilated area

Avoid contact during pregnancy/while nursing

**Primary Route of Exposure** 

Eyes, skin and oral

Carcinogenicity

This product or one of its ingredients present at 0.1% or more IS listed as a carcinogen or suspect carcinogen by NTP, IARC, Prop 65 or OSHA.



Created On: 03/20/2014 Revision Date: 02/05/2015

Version: 2.0

#### 3. Composition/Information on Ingredients (Part B)

CAS Number	Content%	<u>Chemical Name</u>
140-31-8	10 - 20	N- Aminoethylpiperazine
112-24-3	0.5 – 1.5	Triethylenetetramine
107-21-1	3 – 7	Ethylene Glycol
84852-15-3	10 - 20	Nonylphenol
100-51-6	1 – 5	Benzyl Alcohol
Proprietary	10 – 20	Non – Hazardous Proprietary Ingredient
14808-60-7	<1	Crystalline Silica

#### 4. First Aid Measures (Part B)

Inhalation: Move to fresh air; give oxygen if breathing is difficult. Call a physician if symptoms persist.

Eyes: Immediately flush eyes with plenty of water for at least 15 minutes. Call a physician if symptoms persist. **Skin:** Remove contaminated clothing. Wash with mild soap and water. Get medical attention if skin irritation or dermatitis persists.

Ingestion: Give plenty of water. DO NOT induce vomiting. Call a physician immediately.

Other: Referral to a physician is recommended if there is any question about the seriousness of the injury/exposure. If sensitization occurs, future contact with the material should be avoided.

#### 5. Fire Fighting Measures (Part B)

Flash Point: >93°C (200°F)

Flammable Limits: N/A

**Extinguisher Media** 

Carbon Dioxide, Dry Chemical, Water Fog

**Unusual Fire and Explosion Hazard** 

None known. Thermal Decomposition can be formed.

**Special Fire Fighting Procedures** 

Firefighters must wear self-contained breathing apparatus and full protective clothing to prevent contact with toxic and/or irritating fumes.

#### 6. Accidental Release Measures (Part B)

### **Personal Precautions:**

Avoid all personal contact. In enclosed areas, cleanup personnel should wear self-contained breathing apparatus.

#### **Environmental Precautions**

Cover spills with sawdust, vermiculite, or other absorbent material to minimize spreading of the material before collecting.



Created On: 03/20/2014 Revision Date: 02/05/2015

Version: 2.0

#### 7. Handling and Storage (Part B)

**Handling:** Avoid contact with eyes, skin and clothing. Avoid inhalation of vapors. Use with adequate ventilation. Use appropriate personal protection equipment (Section 8). Wash thoroughly after handling.

Storage: Store in a cool dry place away from direct sunlight. Keep from freezing. Recommended storage temperature range in between 4 °C and 35 °C (40°F and 95° F).

## 8. Exposure Control and Personal Protection (Part B)

#### **Exposure Guidelines**

Component	CAS#	OSHA PEL	TLV
Ethylene Glycol	107-21-1	50ppm (Ceiling)	100 mg/ m <sup>3</sup> (Ceiling)
Quartz Silica Sand (Crystalline Silica)	14808- 60-7	0.1 mg/m <sup>3</sup>	0.025 mg/m <sup>3</sup>
Benzyl Alcohol	100-51-6	50ppm (Ceiling)	100 mg/m <sup>3</sup>
Calcium Carbonate	471-34-1	5mg/m <sup>3</sup>	20mg/m <sup>3</sup>

**Engineering Measures:** Use local and general exhaust ventilation to maintain airborne concentrations below TLV. Suitable respiratory equipment should be used in cases of insufficient ventilation or where operational procedures demand it.

#### **Personal Protective Equipment**

# **Respiratory Protection**

None normally required. Use a NIOSH approved organic vapor chemical cartridge respirator when air movement is inadequate to control vapor build-up.

#### **Eye/Face Protection**

Wear splash proof chemical goggles/ full face shield if there is a potential for splashing.

#### **Skin / Body Protection**

Wear Suitable gloves (neoprene, nitrile rubber or PVC) and protective clothing to mitigate exposure.

#### **Other Protective Clothing or Equipment**

Use protective clothing which is chemical resistant to this material. Safety shoes and boots should also be chemical resistant.

#### 9. Physical and Chemical Properties (Part B)

Appearance: Black Paste

Evaporation Rate: N/A

Odor: Slight Odor
Solubility in Water: Insoluble
Specific Gravity(g/cc): 1.35



Created On: 03/20/2014 Revision Date: 02/05/2015

Version: 2.0

Vapor Density(air = 1): Non-Volatile

Vapor Pressure: N/A

VOC Content: 60g/I (when mixed)

pH: N/D Boiling Point: N/A

10. Stability and Reactivity (Part B)

Stability: Stable

Thermal Decomposition: Can yield CO, CO<sub>2</sub> and organic Nitrogen compounds.

Incompatibility: Strong acids, peroxides, and other oxidizing agents

Conditions to avoid: Exposure to excessive heat and storage above 35°C (95°F) will shorten shelf

life.

## 11. Toxicological Information (Part B)

### **Acute Oral Toxicity:**

Not Determined

# **Acute Dermal Toxicity:**

**Not Determined** 

## **Acute Inhalation Toxicity:**

**Not Determined** 

### **Skin Irritation:**

Corrosive to skin

The product has not been tested. The statement has been derived from the properties of the individual components.

## **Eye Irritation:**

Severe damage to eyes.

The product has not been tested. The statement has been derived from the properties of the individual components.

## **Respiratory Irritation:**

Inhalation of vapors or mists may cause irritation to the respiratory system.

## Sensitization:

May cause allergic skin reaction and irritation to the respiratory system.

The product has not been tested. The statement has been derived from the properties of the individual components.



Created On: 03/20/2014 Revision Date: 02/05/2015

Version: 2.0

**Carcinogenicity Classification:** 

**Quartz Silica Sand (Crystalline Silica):** 

IARC Group1: Known human carcinogen based on human evidence.

NTP (National Toxicology Program) has classified Crystalline Silica as a known human carcinogen.

## 12. Ecological Information (Part B)

At the present state of knowledge, no negative ecological effects are expected. Past experiences have shown this material to have no harmful effect on the environment.

### 13. Disposal Considerations (Part B)

If the material as supplied becomes a waste, dispose in accordance with federal, state and local regulations.

## 14. Transportation Information (Part B)

DOT (US)

**CARTRIDGE: Limited Quantity, LTD QTY** 

BULK - Corrosive Liquid, n.o.s. (aminoethylpiperazine, 4-Nonylphenol, branched), Class 8, UN

1760, PG III

IATA/ICAO

CARTRIDGE/BULK: Corrosive Liquid, n.o.s. (aminoethylpiperazine, 4-Nonylphenol, branched),

Class 8, UN 1760, PG III

**IMDG** 

CARTRIDGE/BULK: Corrosive Liquid, n.o.s. (aminoethylpiperazine, 4-Nonylphenol, branched) Class 8,

UN 1760, PG III Marine pollutant: yes

#### 15. Regulatory Information (Part B)

HMIS Rating	
Health	*3
Flammability	1
Physical Hazard	0
PPE	В



Hazard Rating: 0 = minimal, 1 = Slight, 2 = moderate, 3 = severe, 4 = extreme



Created On: 03/20/2014 Revision Date: 02/05/2015

Version: 2.0

Federal Regulations

CERCLA RQCASChemical Name5000 lbs107-21-1Ethylene Glycol

SARA Title 311/312 Chronic Health Hazard

CA Prop 65 This product contains a chemical or chemicals known to the State of

California to cause cancer, birth defects or other reproductive harm.

TSCA Listed

State Regulations:

State RTK NJ, MA, PA

<u>CAS#</u> <u>Chemical Name</u> 107-21-1 Ethylene Glycol

14808-60-7 Quartz Silica Sand (Crystalline Silica)

140-31-8 n-aminoethylpiperazine 14807-96-6 Hydrous Magnesium

### 16. Other Information

**Hazard Communication:** This SDS has been prepared in accordance with the federal OSHA Hazard Communication Standard

To the best of our knowledge, the information contained herein is accurate. However, Adhesives Technology Corp. does not assume any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.

Additional information is available upon request.