

CMX • CTX SINGLE IMPELLER





The **CMX** and **CTX** are non self-priming, single-stage, centrifugal pumps. They are designed for pressure boosting, water supply, treatment and irrigation, air-conditioning and general transfer applications, but can also pump moderately aggressive liquids*. Optional pump control and energy management systems are available (see pages 98 to 101).

*We strongly recommend that you provide our sales department with written details of your application so that the correct selection can be made.

Operating Conditions: Continuous duty | Max. ambient temp: 40°C | Max. suction lift (+ foot valve): 7 mtrs

Fluid: Clean water | Temperature: 0 - 90°C

Application: Industry | Processing | Agriculture | Transfer | Water supply | Light chemicals



CMX-CTX	Type	Impeller	Body
	End suction	Closed	Stainless steel

Pump	Pump body	Impeller	Mechanical seal
	S/S 304	S/S 304	Si-carbide/EPDM
	Shaft	Pump flange	Motor support
	S/S 304	S/S 304	Cast aluminium

Motor	Poles	Enclosure (CMX(T)60)	Enclosure	Insulation
	2 pole	IP44	IP55	Class F



CMX 60/0.37

item code	model	inlet (BSPF)	outlet (BSPF)	kW	volt	flow (l/min)	head (mtrs)	w x l x h (mm)	dry weight (kgs)
19-15-1265	CMX 60/0.37	1¼"	1"	0.37	230	100	19	216x333x227	10
19-15-1037	CTX 60/0.37	1¼"	1"	0.37	400	100	19	216x333x227	10
19-15-1266	CMX 60/0.75	1¼"	1"	0.75	230	120	29	216x333x227	14
19-15-1172	CTX 60/0.75	1¼"	1"	0.75	400	120	29	216x333x227	14
19-15-1138	CMX 100/1.1	1¼"	1"	1.1	230	200	30	216x360x227	16
19-15-1233	CTX 100/1.1	1¼"	1"	1.1	400	200	30	216x360x227	16
19-15-1059	CMX 160/1.1	1½"	1¼"	1.1	230	400	21	216x371x238	16
19-15-1262	CTX 160/1.1	1½"	1¼"	1.1	400	400	21	216x371x238	16
19-15-1117	CMX 250/1.5	1½"	1¼"	1.5	230	400	25	216x371x238	20
19-15-1038	CTX 250/1.5	1½"	1¼"	1.5	400	400	25	216x371x238	20
19-15-1105	CMX 250/2.2	1½"	1¼"	2.2	230	500	31	216x418x245	23
19-15-1202	CTX 250/2.2	1½"	1¼"	2.2	400	500	31	216x418x245	23
19-15-1047	CMX 330/1.5	2"	1¼"	1.5	230	500	21	216x371x238	20
19-15-1095	CTX 330/1.5	2"	1¼"	1.5	400	500	21	216x371x238	20
19-15-1230	CMX 330/2.2	2"	1¼"	2.2	230	550	24	216x418x245	23
19-15-1122	CTX 330/2.2	2"	1¼"	2.2	400	550	24	216x418x245	23

PREMIUM EFFICIENCY MOTORS (IE3) AVAILABLE FOR MODELS FROM 0.75kW 400v (P.O.A.)