

SUBMERSIBLE DRAINAGE

SXS


304 STAINLESS STEEL



SXS pumps, in 304 stainless steel and NBR, have a horizontal outlet and a wide pump casing for pumping waste containing fibrous material and suspended soft solids. With a removable stand, female BSP outlet and large free passage these pumps are suitable for drainage and sewage applications. They are not recommended for ponds or water features.

Fluid: Water, containing fibrous & suspended material | Temperature: 0 - 35°C

Application: Industry | Domestic | Processing | Septic tanks | Sewage



SXS	Impeller	Shaft seal	Level switch (automatic)
	Vortex	Single mechanical	Pendant (VA only)

Pump	Handle	Outlet	Pump casing	Impeller
	S/S 304 & technopolymer	S/S 304	S/S 304	S/S 304
	Suction cover	Shaft	Shaft seal	Lubrication
	S/S 304	S/S 304	Silicon carbide & NBR	Oil
	Stand	Level Switch		
S/S 304	Polypropylene			

Motor	Poles, protection	Insulation	Thermal protection	Starting 1ph/3ph
	2 pole, IP68	Class F	Integral	Internal capacitor/D.O.L
	Motor casing	Power cable (10mtr) & switch cable		
S/S 304	Rubber			



SXS 1000 auto



SXS 1000

item code	model	Manual or Auto	outlet (BSPF)	kW	volt	flow (l/min)	head (mtrs)	free passage (mm)	w x l x h (mm)	on level * (mm)	off level * (mm)	dry weight (kgs)
19-10-1003	SXS 1000-VA	A	2"	0.75	230	350	9	50	165x198x486	550	230	10.9
19-10-1001	SXS 2000 T-V	M	2"	1.5	400	550	12.5	50	165x198x486	-	-	12.6

* APPROXIMATE LIQUID LEVEL