

RSX(M)10

HORIZONTAL MULTI-STAGE




RSX(M)10 are non self-priming, multi-stage, horizontal centrifugal pumps with all the components that are in contact with the liquid constructed in 304 stainless steel. For the pumping of clean water only, they develop high pressures from comparatively small motors and operate virtually silent, hence they are suitable for domestic use, in addition to industrial, horticultural and processing applications. Optional pump control and energy management systems are available (see pages 100 to 101).

Operating Conditions: Continuous duty | Max. ambient temp: 40°C | Max. suction lift (+ foot valve): 7 mtrs

Fluid: Clean water | Temperature: 0 - 90°C

Application: Pressurisation units | Sprinklers | Washing | Irrigation | Water supply | Cooling



RSX(M)10	Type	Impellers	Body & Casing
	Horizontal multi-stage	Closed	Stainless steel

Pump	Pump body	Pump casing	Diffusers	Impellers
	S/S 304	S/S 304	S/S 304	S/S 304
	Mechanical seal	Outlet casing	Motor support	Shaft
	Carbon ceramic/Viton	S/S 304	Cast iron	S/S 304

Motor	Poles	Enclosure	Insulation
	2 pole	IP55	Class F



RSXM10-4

item code	model	inlet (BSPF)	outlet (BSPF)	kw	volt	flow (l/min)	head (mtrs)	w x l x h (mm)	dry weight (kgs)
19-15-1248	RSXM10-4	1½"	1½"	1.5	230	280	44	165x442x254	19
19-15-1259	RSX10-4	1½"	1½"	1.5	400	280	44	165x442x254	19
19-15-1237	RSXM10-5	1½"	1½"	2.2	230	300	54	170x515x235	27
19-15-1083	RSX10-5	1½"	1½"	2.2	400	300	54	170x515x235	27
19-15-1170	RSX10-6	1½"	1½"	3	400	300	65	170x562x235	30

PREMIUM EFFICIENCY MOTORS (IE3) AVAILABLE FOR ALL 400v MODELS (P.O.A.)