

WX • WB


CENTRIFUGAL - SITE WATER



WX and **WB** are self-priming, centrifugal pumps manufactured by Honda and fitted with their 4-stroke, recoil start, petrol engines.

The **WX10** model features a rotary slinger engine lubrication device, to prevent damage from inadequate lubrication during use at an angle. It has an easy-carry handle and rubber feet on the base plate, for engine noise and vibration absorption. Capable of a high head, it is good for irrigation and dust suppression, but with being light and compact it is also useful for general drainage, transfer and flood defence.

WB20 and **WB30** have the Oil Alert engine protection system fitted to prevent damage from inadequate lubrication during use with low oil, or at an angle. Both models have easy-carry frames and they have rubber feet, for engine noise and vibration absorption. Capable of pumping large volumes of clean and dirty water they are good for site drainage, land drainage, transfer and flood defence. To assist manual handling of the model **WB30**, a two wheeled site trolley is available as an optional extra.



Residue pumping kit: engine pumps, with their traditional strainers, will always leave a few inches deep of water behind when pumping off a flat surface. For use with the **WX10**, this kit will enable the pumping of water levels down to 3mm and the floor tool can be moved from puddle to puddle while the engine is still running. Suction lift is up to 6 metres, but 4 metres is recommended. The tool is 140mm wide and the kit comprises a floor tool (with an integral strainer) and a 4 metre suction hose.

Operating conditions: Maximum recommended suction lift: 6 mtrs | Oil alert engine protection (WB)

Fluid: Clean water | Dirty water

Application: Hire fleets | Construction | Utilities | Drainage | Irrigation | Flood defence



WX - WB	Type	Fuel	Starting
	Centrifugal	Petrol	Recoil

Pump	Inlet & outlet	Pump body	Volute (WX)	Volute (WB)
	Cast aluminium	Cast aluminium	Cast aluminium	Grey cast iron
	Impeller (WX)	Impeller (WB)	Mechanical seal	
Cast aluminium	Grey cast iron	Carbon ceramic		

Handling & Hose fittings	Base plate & handle (WX)	Frame (WB)	Trolley (optional)
	Steel & tubular steel	Tubular steel	Tubular steel & solid rubber wheels
	Included fittings		
Hose couplings, sealing washers, hose clips & strainer			



WX10



WB20

item code	model	inlet (mm)	outlet (mm)	engine	fuel	HP	oil alert	flow (l/min)	head (mtrs)	solids (mm)	w x l x h (mm)	dry weight (kgs)
13-20-1002	WX10	25	25	GX25	petrol	1.5	no	140	36	5	220x325x300	6.0
13-20-1001	WB20	50	50	GX120	petrol	4	yes	620	32	6	365x455x420	21.0
13-20-1000	WB30	75	75	GX160	petrol	5.5	yes	1100	28	6	385x510x455	26.0
26-85-1001	optional extra: residue pumping adaptor kit for 25mm centrifugal pumps only											1.0
-	optional extra: site trolley (WB30)											12.4

* GX25 engine is 1 year