

DCC

30 LITRES PER MINUTE



The **DCC** is a low voltage (D.C.) self-priming pump, with a bypass valve suitable for diesel and biodiesel only. It has a carry handle and is supplied with battery cable, crocodile clips, integral fuse and a switch. Included is a pumping kit that comprises discharge hose, inlet hose, battery connectors, delivery nozzle* and foot-valve and strainer.

Some cars will not accept this size of nozzle (please check with our sales department for guidance)

**It MUST NOT pump petrol, high viscosity liquids, chemicals, solvents or products with a low flash point. It is supplied free-standing, but a full frame is available as an optional extra for ease of handling and added protection.*

Operating instructions: Intermittent duty cycle: 30 mins | Max. ambient temp: 40°C | Max suction lift: 2 mtrs

Fluid: Red diesel | White diesel | Biodiesel | Temperature: -20°C to 55°C

Application: Hire fleets | Plant & transport | Agriculture | Vehicle fleets

| | | | |
|-----|---------|---------|-------|
| DCC | Type | Liquids | Power |
| | Surface | Diesels | DC |

| | | | | |
|------|-----------|-------|---------------|-------------|
| Pump | Pump body | Rotor | Sliding vanes | Front cover |
| | Cast iron | Steel | Acetal resin | Steel |

| | | | |
|-------|-----------------------|-----------|-----------------------------|
| Motor | Motor sleeve & handle | Enclosure | Power cable |
| | Steel | IP55 | PVC x 2 mtr + battery clips |

| | | |
|----------|-------------|--|
| Hose Kit | Inlet hose | 1" mBSP x 20mm x 2 mtr hose, foot-valve & strainer |
| | Outlet hose | 1" mBSP x 20mm x 4 mtr hose |
| | Nozzle | Manual shut-off, aluminium, 1" fBSP swivel connector |



DCC12 c/w kit

| item code | model | inlet (mm) | outlet (mm) | amps | volt | flow (l/min) | head (mtrs) | w x l x h (mm) | dry weight (kgs) |
|------------|---------------|------------|-------------|------|------|--------------|-------------|----------------|------------------|
| 19-25-1000 | DCC12 c/w kit | 20 | 20 | 22 | 12 | 30 | 10 | 112x200x145 | 4 |
| 19-25-1001 | DCC24 c/w kit | 20 | 20 | 12 | 24 | 30 | 10 | 112x200x145 | 4 |