

# FLOATING TREE

24 HOUR RUNNING



**Floating Tree** creates a stunning water display in any large pond or lake. Powered by a powerful submersible pump, coupled to the underside of three ballast tanks, the clearer water near the surface is pumped through an integral nozzle, creating a decorative fountain of up to 150cm high and 450cm wide. A minimum clear water depth of 60cm above damaging mud, silt, sediment and debris should be maintained during use, as it floats on the surface. It is simple to assemble, install and has three anchoring points.


**Fluid:** Water in ponds & lakes | Temperature: 0 - 40°C

**Application:** Ponds | Water features | Oxygenation | Decorative displays | Elegant centre-pieces

Floating Tree	<b>Ballast tanks</b>	<b>Nozzle</b>	<b>Pump bracket</b>
	Polypropylene & glass fibre	Polypropylene & glass fibre	Polypropylene & glass fibre

Pump	<b>Impeller</b>	<b>Shaft seal</b>	<b>Outlet</b>
	Open	Single Mechanical	Polypropylene
	<b>Outer cover &amp; handle</b>	<b>Pump casing</b>	<b>Impeller</b>
	Polypropylene & glass fibre	Polypropylene & glass fibre	Nylon & glass fibre
	<b>Shaft</b>	<b>Shaft seal</b>	<b>Strainer</b>
	S/S 410	Silicon carbide & Viton	Polypropylene & glass fibre

Motor	<b>Poles, protection</b>	<b>Enclosure</b>	<b>Insulation</b>
	2 pole, IP68	Oil	Class B
	<b>Thermal protection</b>	<b>Starting</b>	<b>Motor cover</b>
	Integral	Internal capacitor	Aluminium



**Integral nozzle**



**Floating Tree**

item code	model	kW	volt	dia x h (mm)	fountain height (cm)	fountain width (cm)	dry weight (kgs)
15-10-1034	Floating Tree	0.45	230	Ø750 x 510	50-150	100-450	11.4