

SUBMERSIBLE DEWATERING

KST


3 PHASE



The **KST** series is a range of three phase drainage pumps for commercial and industrial applications.

Fluid: Rain water | Ground water | Water carrying sand | Temperature: 0 - 40°C

Application: Hire fleets | Construction | Utilities | Tunnelling | Processing



KST	Impeller	Shaft seal	Level switch
	Open	Double mechanical	Manual control

Pump	Handle	Outlet	Pump body c/w flange	Impeller
	S/S 410	Polypropylene	Grey cast iron	Grey cast iron
	Suction cover	Shaft seal	Lubrication	Shaft
	Grey cast iron	Carbon ceramic	Oil	S/S 410
	Strainer (KST-05 & 08)	Strainer (KST-20 to 100)		
S/S 304	Grey cast iron			

Motor	Poles, protection	Insulation	Thermal protection	Starting
	2 pole, IP68	Class B	Integral	D.O.L.
	Motor frame	Head cover	Power cable, 20mtr (KST-05 & 08, 10mtr)	
	S/S 304	Grey cast iron	Rubber	



KST-08



KST-50

item code	model	Manual or Auto	outlet (mm/BSPM)	kW	volt	flow (l/min)	head (mtrs)	free passage (mm)	w x l x h (mm)	dry weight (kgs)
15-10-1065	KST-05	M	50	0.4	400	260	10	5	156x226x340	14.5
15-10-1061	KST-08	M	50	0.75	400	380	13	6	175x285x457	21.2
15-10-1020	KST-20	M	75	1.5	400	600	16	9	205x375x530	31.0
15-10-1010	KST-30	M	75	2.2	400	800	18	11	255x465x535	42.5
15-10-1011	KST-50	M	4"	3.7	400	1000	21	11	255x465x565	48.3
15-10-1103	KST-75	M	4"	5.5	400	1300	23	11	330x570x700	60.1
15-10-1079	KST-100	M	6"	7.5	400	1600	25	11	330x570x720	70.4