

SUBMERSIBLE DRAINAGE

FAMILY 12


PUMPING DOWN TO 1mm



The **Family 12** has a top discharge design for partial immersion applications and where space is limited. A residue adaptor is supplied as standard, which enables the pumping of water down to 1mm. For use in domestic and light industrial applications, but not recommended for ponds or water features. Available as manual operation only.

Fluid: Clean water | Temperature: 0 - 40°C

Application: Sprinkling | Horticulture | Water butts | Tanks | Transfer



FAMILY 12	Impeller	Shaft seal	Level switch
	Vortex	Single mechanical	Manual control

Pump	Outer cover & handle	Pump body & outlet	Pump casing	Impeller
	Resin AAS	Resin AAS	Resin AAS	Resin AAS
	Shaft	Shaft seal	Lubrication	Strainer
	S/S 420	Silicon carbide	Oil	Resin AAS

Motor	Poles, protection	Insulation	Thermal protection	Starting
	2 pole, IP68	Class E	Integral	Internal capacitor
	Motor casing	Power cable (10 mtr)		
	Aluminium	Rubber		



FAMILY 12

item code	model	Manual or Auto	outlet (mm)	kW	volt	flow (l/min)	head (mtrs)	free passage (mm)	dia x h (mm)	dry weight (kgs)
10-10-1262	Family 12	M	15 & 25	0.10	230	80	6	6	Ø157x224	3.4