


SUBMERSIBLE SEWAGE


GC (32mm) COMPACT GRINDER



The **GC-07** and **GC-10** are innovative grinder pumps that are compact and incorporate a cutting system in a superior grade of stainless steel for reliability. Designed for pumping sewage, containing fibrous material, into conventional drainage, through a small bore pipe. Suitable for domestic and light industrial applications, where space, performance and price combine to be key areas of selection. Available as manual or with a pendant float switch, for automatic operation (230v only).

Fluid: Sewage | Water with suspended material | Temperature: 0 - 40°C

Application: Domestic | Welfare units | Basement systems | Liting stations | Portable sanitation



GC (32mm)	Impeller	Shaft seal	Level switch (automatic)
	Vortex	Double mechanical	Pendant (optional)

Pump	Lifting ring (GC-07)	Handle (GC-10)	Outlet	Pump case & outlet flange
	S/S 304	S/S 304 & rubber	Polypropylene	Grey cast iron
	Impeller (GC-07)	Impeller (GC-10)	Cutting ring	Cutter
	Nylon & glass fibre	Ductile iron	S/S 440C	S/S 440C
	Shaft	Shaft seal	Lubrication	Suction cover & stand
	S/S 304	Sil-carbide & Carb-ceramic	Oil	Grey cast iron
Level switch				Polypropylene

Motor	Poles, protection	Insulation	Thermal protection	Starting 1ph/3ph
	2 pole, IP68	Class B	Integral	Capacitor/D.O.L.
	Head cover	Motor casing	Power cable (10mtr) & switch cable	
	Grey cast iron	Grey cast iron	Rubber	



GC-10



GC-10A

item code	model	Manual or Auto	outlet (mm)	kW	volt	flow (l/min)	head (mtrs)	w x l x h (mm)	dry weight (kgs)
15-10-1082	GC-07	M	32	0.38	230	140	10	170x215x340	12.9
15-10-1101	GC-10	M	32	0.75	230	160	15	210x270x460	20.4
15-10-1084	GC-10	M	32	0.75	400	160	15	210x270x460	20.4
15-10-1055	GC-10A	A	32	0.75	230	160	15	210x270x460	20.8