

GUIDE RAIL KITS • FLANGES

OPTIONAL CONNECTIONS



APP auto-couplings : in grey iron, for raising and lowering the pump without emptying the chamber, to ease inspection and maintenance. Set comprises guide support, guide hook, duck-foot bend, female BSP outlet flange, with fixings and gaskets to join and seal the flanges. Single (TOS-G1) and dual rail installation. *TOS-X3 has a horizontal duck-foot to enable the elbow (and the fixings) from the pump to be utilised and not discarded. Alternative to TOS-L3 & TOS-L4.



TOS-G1

| item code | rails qty x ø | type (outlet, FBSP) |
|------------|------------------|------------------------|
| 15-85-1006 | 1 x DN25 | TOS-G1(1½") |
| 15-85-1009 | 2 x DN25 | TOS-50H (2") |
| 15-85-1001 | 2 x DN25 | TOS-SGH (2") |
| 15-85-1003 | 2 x DN25 | TOS-G3 (2½") |
| 15-85-1004 | 2 x DN25 | TOS-S3 (3") |
| 15-85-1008 | 2 x DN25 | TOS-X3* (3") |
| 15-85-1000 | 2 x DN25 | TOS-L3 (3") |
| 15-85-1002 | 2 x DN25 | TOS-L4 (4") |
| 15-85-1007 | 2 x DN40 | TOS-X4 (4") |



TOS-50H



TOS-S3



TOS-X3



Threaded Flange

Threaded flanges : DIN standard 2566 flange with female thread, PN10/16 in steel.

| item code | type |
|-----------|---------------------------------------|
| 13934003 | DN40 x 1½" PCD110mm, Ø 16mm x 4 holes |
| 13935003 | DN50 x 2" PCD125mm, Ø 18mm x 4 holes |
| 13936503 | DN65 x 2½" PCD145mm, Ø 18mm x 4 holes |
| 13938003 | DN80 x 3" PCD160mm, Ø 20mm x 8 holes |
| 139310003 | DN100 x 4" PCD180mm, Ø 20mm x 8 holes |

Flange seals : PN10/16 in NBR.



Flange Seals

| item code | type |
|-----------|-----------------------|
| 13944003 | DN40 x 50mm x 92mm |
| 13945003 | DN50 x 61mm x 107mm |
| 13946503 | DN65 x 77mm x 127mm |
| 13948003 | DN80 x 90mm x 142mm |
| 139410003 | DN100 x 115mm x 162mm |