



PRESSURE KIT

PARTS

A range of components to enable replacement of parts in, or the assembly of, pressure boosting sets and systems, or for assembly of bespoke booster sets.


Membranes are manufactured to DIN4807. Sizes 2 to 8 litres are in butyl rubber, while 24 litres+ are in EPDM.

Pressure gauges, with side or rear connections, for applications up to 12 bar.

Pressure switches, with range adjustment, for applications up to 16 bar.

Flexible hoses, with 10 bar working pressure, includes one female swivel BSP and one male fixed BSP fitting in brass alloy (CW617N). Braiding in galvanised steel tube, with EPDM inner pipe.

Multiway fittings, in brass, with BSP thread, for connecting a flexible hose, gauge and switch.



FLEXIBLE BRAIDED HOSE				
item code	connector	length (mm)	connection	weight (kgs)
12-65-1014	elbow	300	½"	0.3
12-65-1009	elbow	520	1"	0.6
12-65-1005	straight	600	1"	0.5
12-65-1012	elbow	650	1"	0.5
12-65-1006	straight	800	1"	0.6
12-65-1010	straight	1,000	1¼"	1.4
12-65-1013	straight	1,500	1¼"	1.5

PRESSURE GAUGES			
item code	pressure (bar)	connection position x MBSP	weight (kgs)
12-65-1004	6	rear x ¼"	0.1
12-65-1007	6	side x ¼"	0.1
12-65-1003	12	side x ¼"	0.1



BRASS MULTIWAY FITTINGS			
item code	connector	size (BSP)	weight (kgs)
12-65-1008	3 way	1" x 1" x 1"	0.2
12-65-1001	5 way	1" x 1" x 1" x ¼" x ¼"	0.3

PRESSURE SWITCHES				
item code	type	pressure adjustment (bar)	volts	weight (kgs)
12-65-1002	PM5	1-5	230	0.4
12-65-1011	PT5	1-5	400	0.4
12-65-1000	PM12	2-12	230	0.4
12-65-1015	Fantini B12DN	5-16	230	0.5