EASTMAN

Butvar® B-76

181462

Version Revision Date: SDS Number: Date of last issue: -

1.1 07/25/2019 150000095419 Date of first issue: 09/06/2016 PRD SDSUS / Z8 / 0260 N46 / 0039337972 / 0001083937

SECTION 1. IDENTIFICATION

Product name : Butvar® B-76

Product code : 00000000050128762

Manufacturer or supplier's details

Company name of supplier : Solutia Inc.

A Subsidiary of Eastman Chemical Company

Address : 575 Maryville Centre Drive

Saint Louis MO 63141

Emergency telephone : CHEMTREC: +1-800-424-9300, +1-703-527-3887 CCN7321

Recommended use of the chemical and restrictions on use

Recommended use : Adhesive

Binding agent coatings Ink and toners

Restrictions on use : None known.

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with 29 CFR 1910.1200

Combustible dust

GHS label elements

Signal Word : Warning

Hazard Statements : If small particles are generated during further processing,

handling or by other means, may form combustible dust

concentrations in air.

Precautionary Statements : Disposal:

P501 Dispose of contents/ container to an approved waste dis-

posal plant.

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Components

Chemical name	CAS-No.	Concentration (% w/w)
polyvinyl butyral	27360-07-2 or	>= 96

EASTMAN

Butvar® B-76

181462

1.1 PRD

Version Revision Date: SDS Number:

07/25/2019 150000095419 SDSUS / Z8 / 0260 Date of last issue: -

Date of first issue: 09/06/2016 N46 / 0039337972 / 0001083937

63148-65-2

SECTION 4. FIRST AID MEASURES

If inhaled : Move to fresh air.

Treat symptomatically.

If symptoms persist, call a physician.

In case of skin contact : Wash off with soap and water.

If symptoms persist, call a physician.

Cool skin rapidly with cold water after contact with molten

material.

Do not peel solidified product off the skin. Burns must be treated by a physician.

In case of eye contact : In the case of contact with eyes, rinse immediately with plenty

of water and seek medical advice.

If swallowed : Seek medical advice.

Most important symptoms and effects, both acute and

delayed

The molten product can cause serious burns.

Notes to physician : Treat symptomatically.

SECTION 5. FIRE-FIGHTING MEASURES

Suitable extinguishing media : Water spray

Dry chemical

Carbon dioxide (CO2)

Unsuitable extinguishing

media

Do not use a solid water stream as it may scatter and spread

fire.

Specific hazards during fire

fighting

Avoid generating dust; fine dust dispersed in air in sufficient

concentrations, and in the presence of an ignition source is a

potential dust explosion hazard.

Further information : Minimize dust generation and accumulation.

Special protective equipment

for fire-fighters

Wear an approved positive pressure self-contained breathing

apparatus in addition to standard fire fighting gear.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emer-

gency procedures

Wear appropriate personal protective equipment.

Local authorities should be advised if significant spillages

cannot be contained.

Environmental precautions : Avoid release to the environment.

EASTMAN

Butvar® B-76

181462

Version Revision Date: SDS Number: Date of last issue: -

1.1 07/25/2019 150000095419 Date of first issue: 09/06/2016 PRD SDSUS / Z8 / 0260 N46 / 0039337972 / 0001083937

Methods and materials for containment and cleaning up

Sweep up and shovel into suitable containers for disposal.

SECTION 7. HANDLING AND STORAGE

Advice on protection against

fire and explosion

Minimize dust generation and accumulation.

Advice on safe handling : Wash thoroughly after handling.

Use only in area provided with appropriate exhaust ventilation.

Minimize dust generation and accumulation.

Conditions for safe storage : Keep tightly closed.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Ingredients with workplace control parameters

Contains no substances with occupational exposure limit values.

Engineering measures : Good general ventilation (typically 10 air changes per hour)

should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne

levels to an acceptable level.

Personal protective equipment

Respiratory protection : Use respiratory protection unless adequate local exhaust

ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines. Wear respiratory protection when its use is identified for

certain contributing scenario.

Hand protection

Remarks : Wear suitable gloves. When handling hot material, use heat

resistant gloves.

Eye protection : Safety glasses

Wear a face shield when working with molten material.

Skin and body protection : Wear suitable protective clothing.

Protective measures : Ensure that eye flushing systems and safety showers are

located close to the working place.

Hygiene measures : Handle in accordance with good industrial hygiene and safety

practice.

EASTMAN

Butvar® B-76

181462

1.1 PRD

Version Re

Revision Date: 07/25/2019

SDS Number: 150000095419 SDSUS / Z8 / 0260

Date of last issue: -

Date of first issue: 09/06/2016 N46 / 0039337972 / 0001083937

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : granules

Color : white

Odor : characteristic

Odor Threshold : not determined

pH : not determined

Softening point : 284 - 392 °F / 140 - 200 °C

Boiling point/boiling range : not determined

Flash point : No data available

Evaporation rate : not determined

Flammability (solid, gas) : May form combustible dust concentrations in air during proce-

ssing, handling or other means.

Burning rate : 230 s

Method: ASTM D635-56T

Upper explosion limit / Upper

flammability limit

not determined

Lower explosion limit / Lower

flammability limit

not determined

Vapor pressure : not determined

Relative vapor density : not determined

Relative density : 1.083 (73 °F / 23 °C)

Method: ASTM D 792-50

Bulk density : 220 - 250 kg/m3

Solubility(ies)

Water solubility : insoluble

Partition coefficient: n-

octanol/water

No data available

Autoignition temperature : Dust 716 °F / 380 °C

Decomposition temperature : not determined

Viscosity

Viscosity, dynamic : not determined

EASTMAN

Butvar® B-76

181462

1.1 PRD

Version Revision Date:

07/25/2019

SDS Number: 150000095419 SDSUS / Z8 / 0260

Date of last issue: -

Date of first issue: 09/06/2016 N46 / 0039337972 / 0001083937

Viscosity, kinematic : not determined

Explosive properties : No data available

Oxidizing properties : No data available

Dust deflagration index (Kst) : 100 - 200 m.b_/s

Dust explosion class : St1

Minimum ignition energy : 46 - 240 mJ

SECTION 10. STABILITY AND REACTIVITY

Reactivity : None reasonably foreseeable.

Chemical stability : Stable under normal conditions.

Possibility of hazardous reac-

tions

Stable

Conditions to avoid : Minimize dust generation and accumulation.

Incompatible materials : Strong oxidizing agents

Hazardous decomposition

products

Carbon monoxide Carbon dioxide (CO2)

SECTION 11. TOXICOLOGICAL INFORMATION

Acute toxicity

Not classified based on available information.

Product:

Acute oral toxicity : Remarks: No data available

Acute inhalation toxicity : Remarks: No data available

Acute dermal toxicity : Remarks: No data available

Skin corrosion/irritation

Not classified based on available information.

Product:

Remarks : No data available

Serious eye damage/eye irritation

Not classified based on available information.

Product:

Remarks : No data available

EASTMAN

Butvar® B-76

181462

1.1 PRD

Version Revisio

Revision Date: 07/25/2019

SDS Number: 150000095419 SDSUS / 78 / 0260

Date of last issue: -

Date of first issue: 09/06/2016 N46 / 0039337972 / 0001083937

Respiratory or skin sensitization

Skin sensitization

Not classified based on available information.

Respiratory sensitization

Not classified based on available information.

Product:

Remarks : No data available

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

Not classified based on available information.

Product:

Remarks : This information is not available.

IARC No ingredient of this product present at levels greater than or equal to 0.1% is

identified as probable, possible or confirmed human carcinogen by IARC.

OSHANo component of this product present at levels greater than or equal to 0.1% is

on OSHA's list of regulated carcinogens.

NTP No ingredient of this product present at levels greater than or equal to 0.1% is

identified as a known or anticipated carcinogen by NTP.

Reproductive toxicity

Not classified based on available information.

Product:

Effects on fertility : Remarks: No data available

STOT-single exposure

Not classified based on available information.

Product:

Remarks : No data available

STOT-repeated exposure

Not classified based on available information.

Product:

Remarks : No data available

Aspiration toxicity

Not classified based on available information.

EASTMAN

Butvar® B-76

181462

Version Revision Date: SDS Number: Date of last issue: -

1.1 07/25/2019 150000095419 Date of first issue: 09/06/2016 PRD SDSUS / Z8 / 0260 N46 / 0039337972 / 0001083937

Product:

No data available

Information on likely routes of exposure

Product:

Inhalation : Remarks: None known.

Skin contact : Remarks: The molten product can cause serious burns.

Eye contact : Remarks: The molten product can cause serious burns.

Ingestion : Remarks: None known.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

No data available

Persistence and degradability

No data available

Bioaccumulative potential

No data available

Mobility in soil

No data available

Other adverse effects

No data available

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : Dispose of in accordance with local regulations.

SECTION 14. TRANSPORT INFORMATION

International Regulations

IATA-DGR

Not regulated as a dangerous good

IMDG-Code

Not regulated as a dangerous good

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

Domestic regulation

49 CFR

Not regulated as a dangerous good

EASTMAN

Butvar® B-76

181462

Version Revision Date: SDS Number: Date of last issue: -

1.1 07/25/2019 150000095419 Date of first issue: 09/06/2016 PRD SDSUS / Z8 / 0260 N46 / 0039337972 / 0001083937

SECTION 15. REGULATORY INFORMATION

EPCRA - Emergency Planning and Community Right-to-Know

CERCLA Reportable Quantity

This material does not contain any components with a CERCLA RQ.

SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 302 Extremely Hazardous Substances Threshold Planning Quantity

This material does not contain any components with a section 302 EHS TPQ.

SARA 311/312 Hazards : Combustible dust

SARA 313 : This material does not contain any chemical components with

known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

California Prop. 65

This product does not contain any chemicals known to the State of California to cause cancer, birth, or any other reproductive defects.

The ingredients of this product are reported in the following inventories:

DSL : All components of this product are on the Canadian DSL

AICS : On the inventory, or in compliance with the inventory

ENCS : On the inventory, or in compliance with the inventory

KECI : On the inventory, or in compliance with the inventory

PICCS : On the inventory, or in compliance with the inventory

IECSC : On the inventory, or in compliance with the inventory

TCSI : On the inventory, or in compliance with the inventory

TSCA : All substances listed as active on the TSCA inventory

TSCA list

No substances are subject to a Significant New Use Rule.

No substances are subject to TSCA 12(b) export notification requirements.

EASTMAN

Butvar® B-76

181462


Version Revision Date: SDS Number: Date of last issue: -

1.1 07/25/2019 150000095419 Date of first issue: 09/06/2016 PRD SDSUS / Z8 / 0260 N46 / 0039337972 / 0001083937

SECTION 16. OTHER INFORMATION

Further information

NFPA 704:



Special hazard.

HMIS® IV:



HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. The "*" represents a chronic hazard, while the "/" represents the absence of a chronic hazard.

Full text of other abbreviations

AICS - Australian Inventory of Chemical Substances; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada): ECx - Concentration associated with x% response: EHS - Extremely Hazardous Substance: ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC -International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan): ISO - International Organisation for Standardization: KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships: MSHA - Mine Safety and Health Administration: n.o.s. - Not Otherwise Specified: NFPA - National Fire Protection Association: NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG -

EASTMAN

Butvar® B-76

181462

Version Revision Date: SDS Number: Date of last issue: -

 1.1
 07/25/2019
 150000095419
 Date of first issue: 09/06/2016

 PRD
 SDSUS / Z8 / 0260
 N46 / 0039337972 / 0001083937

United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Revision Date : 07/25/2019

The information provided in this Material Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

US / Z8