



SAFETY DATA SHEET

THE DOW CHEMICAL COMPANY*

Product name: PARALOID™ B-44S 40% Resin

Issue Date: 08/29/2018

Print Date: 01/12/2019

THE DOW CHEMICAL COMPANY* encourages and expects you to read and understand the entire (M)SDS, as there is important information throughout the document. We expect you to follow the precautions identified in this document unless your use conditions would necessitate other appropriate methods or actions.

1. IDENTIFICATION

Product name: PARALOID™ B-44S 40% Resin

Recommended use of the chemical and restrictions on use

Identified uses: Coatings product

COMPANY IDENTIFICATION

THE DOW CHEMICAL COMPANY*
Agent for Rohm and Haas Chemicals LLC
400 ARCOLA ROAD
COLLEGEVILLE PA 19426-2914
UNITED STATES

Customer Information Number:

800-258-2436
SDSQuestion@dow.com

EMERGENCY TELEPHONE NUMBER

24-Hour Emergency Contact: 1 800 424 9300

Local Emergency Contact: 800-424-9300

2. HAZARDS IDENTIFICATION

Hazard classification

GHS classification in accordance with 29 CFR 1910.1200

Flammable liquids - Category 2

Skin irritation - Category 2

Skin sensitisation - Category 1

Carcinogenicity - Category 2

Reproductive toxicity - Category 2

Specific target organ toxicity - single exposure - Category 3

Specific target organ toxicity - repeated exposure - Category 2 - Inhalation

Aspiration hazard - Category 1

Label elements

Hazard pictograms



Signal word: **DANGER!**

Hazards

Highly flammable liquid and vapour.
May be fatal if swallowed and enters airways.
Causes skin irritation.
May cause an allergic skin reaction.
May cause drowsiness or dizziness.
Suspected of causing cancer.
Suspected of damaging fertility or the unborn child.
May cause damage to organs through prolonged or repeated exposure if inhaled.

Precautionary statements

Prevention

Obtain special instructions before use.
Do not handle until all safety precautions have been read and understood.
Keep away from heat/sparks/open flames/hot surfaces. No smoking.
Keep container tightly closed.
Ground/bond container and receiving equipment.
Use explosion-proof electrical/ ventilating/ lighting equipment.
Use only non-sparking tools.
Take precautionary measures against static discharge.
Do not breathe dust/ fume/ gas/ mist/ vapours/ spray.
Wash skin thoroughly after handling.
Use only outdoors or in a well-ventilated area.
Contaminated work clothing should not be allowed out of the workplace.
Wear protective gloves/ protective clothing/ eye protection/ face protection.

Response

IF SWALLOWED: Immediately call a POISON CENTER/doctor.
IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/doctor if you feel unwell.
IF exposed or concerned: Get medical advice/ attention.
Do NOT induce vomiting.
If skin irritation or rash occurs: Get medical advice/ attention.
Take off contaminated clothing and wash before reuse.
In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

Storage

Store in a well-ventilated place. Keep container tightly closed.
Store in a well-ventilated place. Keep cool.
Store locked up.

Disposal

Dispose of contents/ container to an approved waste disposal plant.

Other hazards

No data available

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical nature: Acrylic polymer solvent based

This product is a mixture.

Component	CASRN	Concentration
Acrylic polymer(s)	Not hazardous	>= 39.0 - 41.0 %
Individual residual monomers	Not Required	<= 0.25 %
Ethyl acrylate	140-88-5	<= 0.4 %
Toluene	108-88-3	>= 59.0 - 61.0 %

4. FIRST AID MEASURES

Description of first aid measures

Inhalation: Move to fresh air. Give artificial respiration if breathing has stopped. In case of shortness of breath, give oxygen. Call a physician immediately.

Skin contact: Wash off with soap and plenty of water. If symptoms persist, call a physician. Remove contaminated clothing. Wash contaminated clothing before re-use. Do not take clothing home to be laundered.

Eye contact: Rinse immediately with plenty of water for at least 15 minutes. Get prompt medical attention.

Ingestion: Do NOT induce vomiting. Drink 1 or 2 glasses of water. Get prompt medical attention. If vomiting occurs spontaneously, keep airway clear. Never give anything by mouth to an unconscious person.

Most important symptoms and effects, both acute and delayed:

Aside from the information found under Description of first aid measures (above) and Indication of immediate medical attention and special treatment needed (below), any additional important symptoms and effects are described in Section 11: Toxicology Information.

Indication of any immediate medical attention and special treatment needed

Notes to physician: Acute massive exposure to toluene can cause transient hematuria and albuminuria. Cardiac arrhythmias can occur after massive inhalation.

5. FIREFIGHTING MEASURES

Suitable extinguishing media: Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.

Unsuitable extinguishing media: No data available

Special hazards arising from the substance or mixture

Hazardous combustion products: No data available

Unusual Fire and Explosion Hazards: Vapors can travel to a source of ignition and flash back. Heated material can form flammable or explosive vapors with air. Closed containers may rupture via pressure build-up when exposed to fire or extreme heat. During a fire, irritating and highly toxic gases and/or fumes may be generated during combustion or decomposition.

Advice for firefighters

Fire Fighting Procedures: EXPLOSION HAZARD. Fight advanced fires from a protected location. Cool closed containers exposed to fire with water spray. Remain upwind. Avoid breathing smoke.

Special protective equipment for firefighters: In the event of fire, wear self-contained breathing apparatus.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures: Appropriate protective equipment must be worn when handling a spill of this material. See SECTION 8, Exposure Controls/Personal Protection, for recommendations. If exposed to material during clean-up operations, see SECTION 4, First Aid Measures, for actions to follow.

Environmental precautions: WARNING: KEEP SPILLS AND CLEANING RUNOFFS OUT OF MUNICIPAL SEWERS AND OPEN BODIES OF WATER.

Methods and materials for containment and cleaning up: Eliminate all ignition sources. Evacuate personnel to safe areas. Ventilate the area. Floor may be slippery; use care to avoid falling. Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Sweep up or vacuum up spillage and collect in suitable container for disposal. No sparking tools should be used. Avoid breathing vapor. NOTE: Spills on porous surfaces can contaminate groundwater.

7. HANDLING AND STORAGE

Precautions for safe handling: Vapors can be evolved when material is heated during processing operations. See SECTION 8, Exposure Controls/Personal Protection, for types of ventilation required. Use non-sparking tools and grounding cables when transferring. Wash after handling and shower at end of work period. CONTAINERS MAY BE HAZARDOUS WHEN EMPTY. Since emptied containers retain product residue follow all (M)SDS and label warnings even after container is emptied.

Conditions for safe storage: Avoid temperature extremes during storage; ambient temperature preferred. Store away from excessive heat (e.g. steampipes, radiators), from sources of ignition and from reactive materials. Material can burn; limit indoor storage to approved areas equipped with automatic sprinklers. Store out of direct sunlight in a cool place. Keep containers tightly closed in a

cool, well-ventilated place. Avoid all ignition sources. Ground all metal containers during storage and handling.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

If exposure limits exist, they are listed below. If no exposure limits are displayed, then no values are applicable.

Component	Regulation	Type of listing	Value/Notation
Ethyl acrylate	ACGIH	TWA	5 ppm
	ACGIH	STEL	15 ppm
	OSHA Z-1	TWA	100 mg/m ³ 25 ppm
	OSHA Z-1	TWA	SKIN
	CAL PEL	PEL	20 mg/m ³ 5 ppm
	CAL PEL	STEL	100 mg/m ³ 25 ppm
Toluene	ACGIH	TWA	20 ppm
	OSHA Z-2	TWA	200 ppm
	OSHA Z-2	CEIL	300 ppm
	OSHA Z-2	Peak	500 ppm

Biological occupational exposure limits

Components	CAS-No.	Control parameters	Biological specimen	Sampling time	Permissible concentration	Basis
Toluene	108-88-3	Toluene	In blood	Prior to last shift of workweek	0.02 mg/l	ACGIH BEI
		Toluene	Urine	End of shift (As soon as possible after exposure ceases)	0.03 mg/l	ACGIH BEI
		o-Cresol	Urine	End of shift (As soon as possible after exposure ceases)	0.3 mg/g Creatinine	ACGIH BEI

Exposure controls

Engineering controls: Use explosion-proof local exhaust ventilation with a minimum capture velocity of 100 ft/min (0.5 m/sec) at the point of vapor evolution. Refer to the current edition of Industrial Ventilation: A Manual of Recommended Practice published by the American Conference of Governmental Industrial Hygienists for information on the design, installation, use, and maintenance of exhaust systems.

Protective measures: Facilities storing or utilizing this material should be equipped with an eyewash facility and a safety shower.

Individual protection measures

Eye/face protection: Chemical resistant goggles must be worn. Eye protection worn must be compatible with respiratory protection system employed.

Skin protection

Hand protection: Chemical-resistant gloves should be worn whenever this material is handled. The glove(s) listed below may provide protection against permeation.

(Gloves of other chemically resistant materials may not provide adequate protection): Nitrile rubber butyl-rubber Solvent-resistant gloves Gloves should be removed and replaced immediately if there is any indication of degradation or chemical breakthrough. Rinse and remove gloves immediately after use. Wash hands with soap and water.

Other protection: Use chemically resistant apron or other impervious clothing to avoid prolonged or repeated skin contact. Where splashing is possible, full chemically resistant protective clothing (e.g. acid suit) and boots are required.

Respiratory protection: A respiratory protection program meeting OSHA 1910.134 and ANSI Z88.2 requirements or equivalent must be followed whenever workplace conditions warrant a respirator's use. None required if airborne concentrations are maintained below the exposure limit listed in Exposure Limit Information. Up to 10 times the exposure limit: Wear a properly fitted NIOSH approved (or equivalent) half-mask, air-purifying respirator. Up to 1000 ppm organic vapor: Wear a properly fitted NIOSH approved (or equivalent) full-facepiece, air-purifying respirator, OR full-facepiece, airline respirator in the pressure demand mode. Above 1000 ppm organic vapor or Unknown: Wear a properly fitted NIOSH approved (or equivalent) self-contained breathing apparatus in the pressure demand mode, OR full-facepiece, airline respirator in the pressure demand mode with emergency escape provision. Air-purifying respirators should be equipped with NIOSH approved (or equivalent) organic vapor cartridges and N95 filters. If oil mist is present, use R95 or P95 filters.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance

Physical state	liquid
Color	colourless clear
Odor	Sour, burnt odor
Odor Threshold	No data available
pH	Not Applicable
Melting point/range	-95.00 °C (-139.00 °F) Toluene
Freezing point	No data available
Boiling point (760 mmHg)	110.60 °C (231.08 °F) Toluene
Flash point	closed cup 7.00 °C (44.60 °F) <i>PENSKY MARTENS CLOSED CUP</i>
Evaporation Rate (Butyl Acetate = 1)	1.90 Toluene
Flammability (solid, gas)	Not Applicable
Lower explosion limit	1.20 % vol Toluene
Upper explosion limit	7.10 % vol Toluene
Vapor Pressure	22.0000000 mmHg at 20.00 °C (68.00 °F) Toluene
Relative Vapor Density (air = 1)	3.1000 Toluene
Relative Density (water = 1)	0.9800

Water solubility	practically insoluble
Partition coefficient: n-octanol/water	No data available
Auto-ignition temperature	480.00 °C (896.00 °F) Toluene
Decomposition temperature	No data available
Dynamic Viscosity	1,100.000 - 2,000.000 mPa.s
Kinematic Viscosity	No data available
Explosive properties	No data available
Oxidizing properties	No data available
Molecular weight	No data available
Percent volatility	59.00 - 61.00 %

NOTE: The physical data presented above are typical values and should not be construed as a specification.

10. STABILITY AND REACTIVITY

Reactivity: No data available

Chemical stability: No data available

Possibility of hazardous reactions: This material is considered stable. However, avoid contact with ignition sources (e.g. sparks, open flame, heated surfaces).
Product will not undergo polymerization.

Conditions to avoid: No data available

Incompatible materials: Avoid contact with the following: Strong oxidizing agents Strong acids and strong bases

Hazardous decomposition products: There are no known hazardous decomposition products for this material.

11. TOXICOLOGICAL INFORMATION

Toxicological information appears in this section when such data is available.

Acute toxicity

Acute oral toxicity

Product test data not available. Refer to component data.

Acute dermal toxicity

Product test data not available. Refer to component data.

Acute inhalation toxicity

Product test data not available. Refer to component data.

Skin corrosion/irritation

Product test data not available. Refer to component data.

Serious eye damage/eye irritation

Product test data not available. Refer to component data.

Sensitization

Product test data not available. Refer to component data.

Specific Target Organ Systemic Toxicity (Single Exposure)

Product test data not available. Refer to component data.

Specific Target Organ Systemic Toxicity (Repeated Exposure)

Product test data not available. Refer to component data.

Carcinogenicity

Product test data not available. Refer to component data.

Teratogenicity

Product test data not available. Refer to component data.

Reproductive toxicity

Product test data not available. Refer to component data.

Mutagenicity

Product test data not available. Refer to component data.

Aspiration Hazard

Product test data not available. Refer to component data.

COMPONENTS INFLUENCING TOXICOLOGY:

Acrylic polymer(s)

Acute oral toxicity

Single dose oral LD50 has not been determined.

Acute dermal toxicity

The dermal LD50 has not been determined.

Acute inhalation toxicity

The LC50 has not been determined.

Skin corrosion/irritation

Essentially nonirritating to skin.

Serious eye damage/eye irritation

Essentially nonirritating to eyes.

Sensitization

For skin sensitization:
No relevant data found.

For respiratory sensitization:
No relevant data found.

Specific Target Organ Systemic Toxicity (Single Exposure)

The substance or mixture is not classified as specific target organ toxicant, single exposure.

Specific Target Organ Systemic Toxicity (Repeated Exposure)

No relevant data found.

Carcinogenicity

No relevant data found.

Teratogenicity

No relevant data found.

Reproductive toxicity

No relevant data found.

Mutagenicity

No relevant data found.

Aspiration Hazard

No aspiration toxicity classification

Ethyl acrylate

Acute oral toxicity

LD50, Rat, male, 1,120 mg/kg

Acute dermal toxicity

LD50, Rat, male, 3,049 mg/kg

Acute inhalation toxicity

LC50, Rat, 4 Hour, vapour, <9.137 mg/l OECD Test Guideline 403

Skin corrosion/irritation

Brief contact may cause moderate skin irritation with local redness.
Prolonged contact may cause skin burns. Symptoms may include pain, severe local redness, swelling, and tissue damage.

Serious eye damage/eye irritation

May cause severe eye irritation.
May cause severe corneal injury.
Vapor may cause eye irritation experienced as mild discomfort and redness.

Sensitization

Skin contact may cause an allergic skin reaction.
Has demonstrated the potential for contact allergy in mice.

For respiratory sensitization:
No relevant data found.

Specific Target Organ Systemic Toxicity (Single Exposure)

May cause respiratory irritation.
Route of Exposure: Inhalation

Target Organs: Respiratory Tract

Specific Target Organ Systemic Toxicity (Repeated Exposure)

In animals, effects have been reported on the following organs:
Nasal tissue.

Carcinogenicity

An increased incidence of stomach tumors was seen in animals given daily oral doses of ethyl acrylate. Tumors were judged to result from irritation. Long-term studies by more relevant routes of exposure (skin, inhalation) were negative. Workers exposed during 1933-1945 to very high vapor concentrations of ethyl acrylate and methyl methacrylate, and to volatile by-products of the ethyl acrylate/methyl methacrylate polymerization process, showed an increase in deaths due to colorectal cancer. Such increases were not observed in workers exposed after that time. Although suggestive, these findings do not establish a causal relationship between high level exposure to these acrylates and colorectal cancer.

Teratogenicity

Did not cause birth defects or any other fetal effects in laboratory animals.

Reproductive toxicity

For similar material(s): In animal studies, did not interfere with reproduction.

Mutagenicity

In vitro genetic toxicity studies were negative in some cases and positive in other cases. Animal genetic toxicity studies were predominantly negative.

Aspiration Hazard

May be harmful if swallowed and enters airways.

Toluene**Acute oral toxicity**

LD50, Rat, 5,580 mg/kg

Acute dermal toxicity

LD50, Rabbit, 12,267 mg/kg

Acute inhalation toxicity

Symptoms may include headache, dizziness and drowsiness, progressing to incoordination and unconsciousness. Alcohol consumption and exertion may increase the adverse effects of toluene. LC50, Rat, male, 4 Hour, vapour, 25.7 mg/l

LC50, Rat, female, 4 Hour, vapour, 30 mg/l

Skin corrosion/irritation

Brief contact may cause slight skin irritation with local redness.

Prolonged contact may cause moderate skin irritation with local redness.

May cause drying and flaking of the skin.

Serious eye damage/eye irritation

May cause slight eye irritation.

May cause slight temporary corneal injury.

Vapor may cause eye irritation experienced as mild discomfort and redness.

Vapor may cause lacrimation (tears).

Sensitization

Did not cause allergic skin reactions when tested in guinea pigs.

For respiratory sensitization:
No relevant data found.

Specific Target Organ Systemic Toxicity (Single Exposure)

May cause drowsiness or dizziness.
Route of Exposure: Inhalation
Target Organs: Central nervous system

Specific Target Organ Systemic Toxicity (Repeated Exposure)

In animals, effects have been reported on the following organs:
central nervous system (CNS) effects
Excessive exposure may cause neurologic signs and symptoms.
Toluene has caused hearing loss in laboratory animals upon exposure to high concentrations.
Intentional misuse by deliberately inhaling toluene may cause nervous system damage, hearing loss, liver and kidney effects and death.

Carcinogenicity

Did not cause cancer in laboratory animals.

Teratogenicity

In laboratory animals, toluene has been toxic to the fetus at doses toxic to the mother; it has caused birth defects in mice when administered orally, but not by inhalation. Based on Structure-Activity Relationship (SAR), this material is predicted to interfere with fertility or cause birth defects.

Reproductive toxicity

In animal studies, did not interfere with reproduction.

Mutagenicity

The majority and most reliable of the many genetic toxicity studies on toluene, both in vitro and in animals, indicate that it is not genetically toxic.

Aspiration Hazard

May be fatal if swallowed and enters airways.

Carcinogenicity

Component
Ethyl acrylate

List
IARC

Classification

Group 2B: Possibly carcinogenic to humans

12. ECOLOGICAL INFORMATION

Ecotoxicological information appears in this section when such data is available.

General Information

There is no data available for this product.

Toxicity

Acrylic polymer(s)

Acute toxicity to fish

No relevant data found.

Ethyl acrylate

Acute toxicity to fish

Material is moderately toxic to aquatic organisms on an acute basis (LC50/EC50 between 1 and 10 mg/L in the most sensitive species tested).

LC50, Cyprinodon variegatus (sheepshead minnow), flow-through test, 96 Hour, 2.0 mg/l

Acute toxicity to aquatic invertebrates

EC50, Daphnia magna (Water flea), flow-through test, 48 Hour, 7.9 mg/l

Acute toxicity to algae/aquatic plants

EC50, Pseudokirchneriella subcapitata (green algae), static test, 72 Hour, Growth inhibition (cell density reduction), 4.5 mg/l, OECD Test Guideline 201 or Equivalent

Toxicity to bacteria

EC10, activated sludge, Respiration inhibition, 72 Hour, > 100 mg/l

Chronic toxicity to aquatic invertebrates

NOEC, Daphnia magna (Water flea), flow-through test, 21 d, number of offspring, 0.19 mg/l

Toluene

Acute toxicity to fish

Material is moderately toxic to aquatic organisms on an acute basis (LC50/EC50 between 1 and 10 mg/L in the most sensitive species tested).

LC50, Oncorhynchus mykiss (rainbow trout), semi-static test, 96 Hour, 5.8 mg/l

Acute toxicity to aquatic invertebrates

LC50, water flea Ceriodaphnia dubia, semi-static test, 48 Hour, 3.78 mg/l

Acute toxicity to algae/aquatic plants

EbC50, Pseudokirchneriella subcapitata (green algae), 72 Hour, Biomass, 12.5 mg/l, OECD Test Guideline 201

Toxicity to bacteria

IC50, Bacteria, 16 Hour, 29 mg/l

Chronic toxicity to fish

NOEC, Fish, flow-through test, 40 d, growth, 1.4 mg/l

Chronic toxicity to aquatic invertebrates

NOEC, Ceriodaphnia dubia (water flea), 7 d, number of offspring, 0.74 mg/l

Toxicity to soil-dwelling organisms

LC50, Eisenia fetida (earthworms), 150 - 280 mg/kg

Persistence and degradability

Acrylic polymer(s)

Biodegradability: No relevant data found.

Ethyl acrylate

Biodegradability: Material is readily biodegradable. Passes OECD test(s) for ready biodegradability. Material is inherently biodegradable (reaches > 20% biodegradation in OECD test(s) for inherent biodegradability).

10-day Window: Pass

Biodegradation: 80 - 90 %

Exposure time: 28 d

Method: OECD Test Guideline 310 or Equivalent

10-day Window: Not applicable

Biodegradation: > 60 %

Exposure time: 11 d

Method: OECD Test Guideline 302B or Equivalent

Theoretical Oxygen Demand: 1.92 mg/mg

Biological oxygen demand (BOD)

Incubation Time	BOD
5 d	18 %
10 d	27 %
20 d	50 %

Photodegradation

Test Type: Half-life (indirect photolysis)

Sensitization: OH radicals

Atmospheric half-life: 0.984 d

Method: Estimated.

Toluene

Biodegradability: Material is readily biodegradable. Passes OECD test(s) for ready biodegradability.

10-day Window: Not applicable

Biodegradation: 100 %

Exposure time: 14 d

Method: OECD Test Guideline 301C or Equivalent

Theoretical Oxygen Demand: 3.13 mg/mg Calculated.

Photodegradation

Test Type: Half-life (indirect photolysis)

Sensitization: OH radicals

Atmospheric half-life: 2 d

Method: Estimated.

Bioaccumulative potential

Acrylic polymer(s)

Bioaccumulation: No relevant data found.

Ethyl acrylate

Bioaccumulation: Bioconcentration potential is low (BCF < 100 or Log Pow < 3).
Partition coefficient: n-octanol/water(log Pow): 1.18 OECD Test Guideline 107 or Equivalent
Bioconcentration factor (BCF): 2 Fish Estimated.

Toluene

Bioaccumulation: Bioconcentration potential is low (BCF < 100 or Log Pow < 3).
Partition coefficient: n-octanol/water(log Pow): 2.73 Measured
Bioconcentration factor (BCF): 13.2 - 90 Fish Measured

Mobility in soil**Acrylic polymer(s)**

No relevant data found.

Ethyl acrylate

Potential for mobility in soil is very high (Koc between 0 and 50).
Partition coefficient (Koc): 12 Estimated.

Toluene

Potential for mobility in soil is very high (Koc between 0 and 50).
Partition coefficient (Koc): 37 - 178 Estimated.

13. DISPOSAL CONSIDERATIONS

Disposal methods: Incinerate liquid and contaminated solids in accordance with local, state, and federal regulations.
 (See 40 CFR 268)

Contaminated packaging: Empty containers should be taken to an approved waste handling site for recycling or disposal.

14. TRANSPORT INFORMATION

DOT

Proper shipping name	Resin solution
UN number	UN 1866
Class	3
Packing group	II
Reportable Quantity	Toluene

Classification for SEA transport (IMO-IMDG):

Proper shipping name	RESIN SOLUTION
UN number	UN 1866
Class	3
Packing group	II
Marine pollutant	No
Transport in bulk according to Annex I or II	Consult IMO regulations before transporting ocean bulk

**of MARPOL 73/78 and the
IBC or IGC Code****Classification for AIR transport (IATA/ICAO):**

Proper shipping name	Resin solution
UN number	UN 1866
Class	3
Packing group	II

This information is not intended to convey all specific regulatory or operational requirements/information relating to this product. Transportation classifications may vary by container volume and may be influenced by regional or country variations in regulations. Additional transportation system information can be obtained through an authorized sales or customer service representative. It is the responsibility of the transporting organization to follow all applicable laws, regulations and rules relating to the transportation of the material.

15. REGULATORY INFORMATION

Superfund Amendments and Reauthorization Act of 1986 Title III (Emergency Planning and Community Right-to-Know Act of 1986) Sections 311 and 312

Flammable (gases, aerosols, liquids, or solids)
 Skin corrosion or irritation
 Respiratory or skin sensitisation
 Carcinogenicity
 Reproductive toxicity
 Specific target organ toxicity (single or repeated exposure)
 Aspiration hazard

Superfund Amendments and Reauthorization Act of 1986 Title III (Emergency Planning and Community Right-to-Know Act of 1986) Section 313

Components	CASRN
Ethyl acrylate	140-88-5
Toluene	108-88-3

Comprehensive Environmental Response, Compensation, and Liability Act of 1980 (CERCLA) Section 103

Components	CASRN	RQ (RCRA Code)
Toluene	108-88-3	1000 lbs RQ
Toluene	108-88-3	100 lbs RQ (F005)
Toluene	108-88-3	1000 lbs RQ
Toluene	108-88-3	100 lbs RQ (F005)

Pennsylvania

Any material listed as "Not Hazardous" in the CAS REG NO. column of SECTION 2, Composition/Information On Ingredients, of this MSDS is a trade secret under the provisions of the Pennsylvania Worker and Community Right-to-Know Act.

California (Proposition 65)

This product contains trace levels of a component or components known to the state of California to cause cancer:

Components	CASRN
Ethyl acrylate	140-88-5

California (Proposition 65)

This product contains a component or components known to the state of California to cause birth defects or other reproductive harm:

Components	CASRN
Toluene	108-88-3

California (Proposition 65)

This product contains trace levels of a component or components known to the state of California to cause cancer and birthdefects or other reproductive harm:

Components	CASRN
Benzene	71-43-2

United States TSCA Inventory (TSCA)

All components of this product are in compliance with the inventory listing requirements of the U.S. Toxic Substances Control Act (TSCA) Chemical Substance Inventory.

16. OTHER INFORMATION

Hazard Rating System

HMIS

Health	Flammability	Physical Hazard
3*	3	0

* = Chronic Effects (See Hazards Identification)

Revision

Identification Number: 10077861 / 1001 / Issue Date: 08/29/2018 / Version: 4.1
 Most recent revision(s) are noted by the bold, double bars in left-hand margin throughout this document.

Legend

ACGIH	USA. ACGIH Threshold Limit Values (TLV)
ACGIH BEI	ACGIH - Biological Exposure Indices (BEI)
CAL PEL	California permissible exposure limits for chemical contaminants (Title 8, Article 107)
CEIL	Acceptable ceiling concentration
OSHA Z-1	USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants
OSHA Z-2	USA. Occupational Exposure Limits (OSHA) - Table Z-2
Peak	Acceptable maximum peak above the acceptable ceiling concentration for an 8-hr shift

PEL	Permissible exposure limit
SKIN	Absorbed via skin
STEL	Short term exposure limit
TWA	8-hour, time-weighted average

Full text of other abbreviations

AICS - Australian Inventory of Chemical Substances; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Information Source and References

This SDS is prepared by Product Regulatory Services and Hazard Communications Groups from information supplied by internal references within our company.

THE DOW CHEMICAL COMPANY* urges each customer or recipient of this (M)SDS to study it carefully and consult appropriate expertise, as necessary or appropriate, to become aware of and understand the data contained in this (M)SDS and any hazards associated with the product. The information herein is provided in good faith and believed to be accurate as of the effective date shown above. However, no warranty, express or implied, is given. Regulatory requirements are subject to change and may differ between various locations. It is the buyer's/user's responsibility to ensure that his activities comply with all federal, state, provincial or local laws. The information presented here pertains only to the product as shipped. Since conditions for use of the product are not under the control of the manufacturer, it is the buyer's/user's duty to determine the conditions necessary for the safe use of this product. Due to the proliferation of sources for information such as manufacturer-specific (M)SDSs, we are not and cannot be responsible for (M)SDSs obtained from any source other

than ourselves. If you have obtained an (M)SDS from another source or if you are not sure that the (M)SDS you have is current, please contact us for the most current version.
US