

Material Safety Data Sheet

May be used to comply with OSHA's Hazard Communication Standard, 29 CFR 1910.1200. Standard must be consulted for specific requirements.

U.S. Department of Labor

Occupational Safety and Health Administration
(Non-Mandatory Form)
Form Approved
OMB No. 1218-0072

IDENTITY (as Used on Label and List)
Paraloid B-67 Marking Varnish White

Note: Blank spaces are not permitted. If any item is not applicable or no information is available, the space must be marked to indicate that.

Section I

Manufacturer's name Museum Services Corporation	Emergency Telephone Number 651-450-8954
Address (Number, Street, City, State and ZIP Code) 385 Bridgepoint Way South Saint Paul, MN 55075	Telephone Number for Information 651-450-8954
	Date Prepared 11/16/2022
	Signature of Preparer (optional)

Section II—Hazardous Identification

Hazard classification

This material is hazardous under the criteria of the Federal OSHA Hazard Communication Standard 29CFR 1910.1200.

Flammable liquids - Category 3

Reproductive toxicity - Category 2

Specific target organ toxicity - repeated exposure - Category 1 - Inhalation

Aspiration hazard - Category 1

Label elements

Hazard pictograms



Signal word: **DANGER!**

Hazards

Flammable liquid and vapour.

May be fatal if swallowed and enters airways.

Suspected of damaging fertility or the unborn child.

Causes damage to organs (Central nervous system) through prolonged or repeated exposure if inhaled.

Precautionary statements

Prevention

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Keep container tightly closed.

Ground/bond container and receiving equipment.

Use explosion-proof electrical/ ventilating/ lighting/ equipment.

Use only non-sparking tools.

Take precautionary measures against static discharge.

Do not breathe dust/ fume/ gas/ mist/ vapors/ spray.

Wash skin thoroughly after handling.

Do not eat, drink or smoke when using this product.

Wear protective gloves/ eye protection/ face protection.

Use personal protective equipment as required.

Response

IF SWALLOWED: Immediately call a POISON CENTER or doctor/ physician.
IF ON SKIN (or hair): Remove/ Take off immediately all contaminated clothing. Rinse skin with water/ shower.
IF exposed or concerned: Get medical advice/ attention. Do NOT induce vomiting.
In case of fire: Use dry sand, dry chemical or alcohol-resistant foam for extinction.

Storage

Store in a well-ventilated place. Keep cool. Store locked up.

Disposal

Dispose of contents/ container to an approved waste disposal plant.

Other hazards

no data available

Section III—Composition/Information on Ingredients

Component	CASRN	Concentration	
Acrylic Polymer(s)	NA	20%	
Mineral Spirits	8052-41-3	75%	
Titanium Dioxide Pigment	13463-67-7	5%	

Section IV—First Aid Measures**Description of first aid measures**

Inhalation: Move to fresh air. Give artificial respiration if breathing has stopped. In case of shortness of breath, give oxygen. Consult a physician.

Skin contact: Remove contaminated clothing. Wash off with soap and plenty of water. If symptoms persist, call a physician. Do not take clothing home to be laundered.

Eye contact: Rinse with plenty of water. If eye irritation persists, consult a specialist.

Ingestion: Do NOT induce vomiting. Drink 1 or 2 glasses of water. IMMEDIATELY see a physician. If vomiting occurs spontaneously, keep airway clear. Never give anything by mouth to an unconscious person.

Most important symptoms and effects, both acute and delayed: Aside from the information found under Description of first aid measures (above) and Indication of immediate medical attention and special treatment needed (below), any additional important symptoms and effects are described in Section 11: Toxicology Information.

Indication of any immediate medical attention and special treatment needed

Notes to physician: Product contains a petroleum distillate that may cause CNS symptoms.

Section V—Fire and Explosion Hazard Data

Extinguishing Media - Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.

Special Fire Fighting Procedures – no data available

Unusual Fire and Explosion Hazards - Vapors can travel to a source of ignition and flash back. Heated material can form flammable or explosive vapors with air. Closed containers may rupture via pressure build-up when exposed to fire or extreme heat. During a fire, irritating and highly toxic gases and/or fumes may be generated during combustion or decomposition.

Advice for firefighters (Fire Fighting Procedures): EXPLOSION HAZARD. Fight advanced fires from a protected location. Cool closed containers exposed to fire with water spray. Remain upwind. Avoid breathing smoke.

Special protective equipment for firefighters: In the event of fire, wear self-contained breathing apparatus.

Section VI—Accidental Release Measures

Personal precautions, protective equipment and emergency procedures: Appropriate protective equipment must be worn when handling a spill of this material. See SECTION 8, Exposure Controls/Personal Protection, for recommendations. If exposed to material during clean-up operations, see SECTION 4, First Aid Measures, for actions to follow.

Environmental precautions: WARNING: KEEP SPILLS AND CLEANING RUNOFFS OUT OF MUNICIPAL SEWERS AND OPEN BODIES OF WATER.

Methods and materials for containment and cleaning up: Eliminate all ignition sources. Evacuate personnel to safe areas. Ventilate the area. Floor may be slippery; use care to avoid falling. Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Sweep up or vacuum up spillage and collect in suitable container for disposal. No sparking tools should be used. Avoid breathing vapor. NOTE: Spills on porous surfaces can contaminate groundwater.

Section VII—Handling and Storage

Precautions for safe handling: Use non-sparking tools and grounding cables when transferring. Wash after handling and shower at end of work period. CONTAINERS MAY BE HAZARDOUS WHEN EMPTY. Since emptied containers retain product residue, follow all MSDS and label warnings even after container is emptied.

Conditions for safe storage: Avoid temperature extremes during storage; ambient temperature preferred. Store away from excessive heat (e.g. steam pipes, radiators), from sources of ignition and from reactive materials. Material can burn; limit indoor storage to approved areas equipped with automatic sprinklers. Store out of direct sunlight in a cool place. Keep containers tightly closed in a cool, well-ventilated place. Avoid all ignition sources. Ground all metal containers during storage and handling.

Section VIII—Exposure Control /Personal Protection

Respiratory Protection (*Specify Type*): A respiratory protection program meeting OSHA 1910.134 and ANSI Z88.2 requirements or equivalent must be followed whenever workplace conditions warrant a respirator's use. None required if airborne concentrations are maintained below the exposure limit listed in Exposure Limit Information.

Engineering Controls: Use explosion-proof local exhaust ventilation with a minimum capture velocity of 100 ft/min (0.5 m/sec) at the point of vapor evolution. Refer to the current edition of Industrial Ventilation: A Manual of Recommended Practice published by the American Conference of Governmental Industrial Hygienists for information on the design, installation, use, and maintenance of exhaust systems.

Protective measures: Facilities storing or utilizing this material should be equipped with an eyewash facility and a safety shower.

Protective Gloves: Chemical-resistant gloves should be worn whenever this material is handled. The glove(s) listed below may provide protection against permeation. (Gloves of other chemically resistant materials may not provide adequate protection): Nitrile rubber. Butyl-rubber. Solvent-resistant gloves. Gloves should be removed and replaced immediately if there is any indication of degradation or chemical breakthrough. Rinse and remove gloves immediately after use. Wash hands with soap and water.

Eye Protection: Chemical resistant goggles must be worn. Eye protection worn must be compatible with respiratory protection system employed.

Section IX—Physical and Chemical Properties

Appearance

Physical state liquid

Color colourless clear

Odor Sweet odor

Odor Threshold no data available

pH no data available

Melting point/range no data available

Freezing point no data available

Boiling point (760 mmHg) 158.00 °C (316.40 °F) Initial

Flash point Pensky-Martens closed cup 37 °C (99 °F)

Evaporation Rate (Butyl Acetate= 1) <1.00

Flammability (solid, gas) Not Applicable

Lower explosion limit 0.90 % vol estimated

Upper explosion limit 6.00 % vol estimated

Vapor Pressure 1.0000000 mmHg at 20.00 °C (68.00 °F) estimated

Relative Vapor Density (air = 1) >1.0000

Relative Density (water = 1) 0.8900

Water solubility practically insoluble

Partition coefficient: noctanol/water - no data available

Auto-ignition temperature no data available

Decomposition temperature no data available

Dynamic Viscosity 800 - 1,600 mPa.s

Kinematic Viscosity no data available

Explosive properties no data available

Oxidizing properties no data available

Liquid Density 0.88 g/cm³

Molecular weight no data available

Percent volatility 54.00 - 56.00 %

NOTE: The physical data presented above are typical values and should not be construed as a specification.

Section X—Stability and Reactivity

Reactivity: no data available

Chemical stability: no data available

Possibility of hazardous reactions: This material is considered stable. However, avoid contact with ignition sources (e.g. sparks, open flame, heated surfaces). Product will not undergo polymerization.

Conditions to avoid: no data available

Incompatible materials: Avoid contact with the following: Strong oxidizing agents Strong acids and strong bases

Hazardous decomposition products: There are no known hazardous decomposition products for this material.

Section XI—Toxicological Information

Toxicological information appears in this section when such data is available.

Acute toxicity

Acute oral toxicity - LD50, Rat, > 5,000 mg/kg

Acute dermal toxicity - LD50, Rabbit, > 3,000 mg/kg

Acute inhalation toxicity - Product test data not available.

Skin corrosion/irritation - slight irritation

Serious eye damage/eye irritation - slight irritation

Sensitization - Product test data not available.

Specific Target Organ Systemic Toxicity (Single Exposure) - Product test data not available.

Specific Target Organ Systemic Toxicity (Repeated Exposure) - Product test data not available.

Carcinogenicity - Product test data not available.

Teratogenicity - Product test data not available.

Reproductive toxicity - Product test data not available.

Mutagenicity - Product test data not available.

Aspiration Hazard - Product test data not available.

COMPONENTS INFLUENCING TOXICOLOGY:

Acrylic polymer(s)

Acute inhalation toxicity - The LC50 has not been determined.

Mineral Spirits

Acute inhalation toxicity -Prolonged excessive exposure may cause adverse effects. Excessive exposure may cause irritation to upper respiratory tract (nose and throat). May cause central nervous system effects. (LC50, Rat, vapour, > 14 mg/l)

Sensitization - Did not cause allergic skin reactions when tested in guinea pigs.

For respiratory sensitization: - No relevant data found.

Specific Target Organ Systemic Toxicity (Single Exposure) - Evaluation of available data suggests that this material is not an STOT-SE toxicant.

Specific Target Organ Systemic Toxicity (Repeated Exposure) - -In humans, effects have been reported on the following organs: Bone Marrow,

Liver. In animals, effects have been reported on the following organs: central nervous system damage Kidney. Kidney effects and/or tumors have been observed in male rats. These effects are believed to be species specific and unlikely to occur in humans.

Carcinogenicity - No specific, relevant data available for assessment.

Teratogenicity - For similar material(s): Did not cause birth defects or any other fetal effects in laboratory animals.

Reproductive toxicity - For similar material(s): In animal studies, did not interfere with reproduction.

Mutagenicity - In vitro genetic toxicity studies were negative. Animal genetic toxicity studies were negative.

Aspiration Hazard - May be fatal if swallowed and enters airways.

Section XII—Ecological Information

Ecotoxicological information appears in this section when such data is available.

General Information

There is no data available for this product.

Toxicity

Acrylic polymer(s)

Acute toxicity to fish - No relevant data found.

Mineral Spirits

Acute toxicity to aquatic invertebrates - LC50, crustacean *Chaetogammarus marinus*, 96 Hour, 3.5 mg/l

Acute toxicity to algae/aquatic plants - ErC50, *Pseudokirchneriella subcapitata* (green algae), 72 Hour, 1.2 mg/l

Chronic toxicity to aquatic invertebrates - NOEC, *Daphnia magna* (Water flea), 21 d, 0.1 mg/l

Persistence and degradability

Acrylic polymer(s)

Biodegradability: No relevant data found.

Mineral Spirits

Biodegradability: Material is expected to be readily biodegradable.

Acrylic polymer(s)

Bioaccumulation: No relevant data found.

Mineral Spirits

Bioaccumulation: Bioconcentration potential is moderate (BCF between 100 and 3000 or Log Pow between 3 and 5).

Partition coefficient: n-octanol/water(log Pow): 5.01 Measured

Section XIII—Disposal Considerations

Disposal methods: Incinerate liquid and contaminated solids in accordance with local, state, and federal regulations. (See 40 CFR 268)

Contaminated packaging: Empty containers should be taken to an approved waste handling site for recycling or disposal.

Section XIV—Transport Information

DOT

Proper shipping name Resin solution

UN number UN 1866

Class 3

Packing group III

Classification for SEA transport (IMO-IMDG):

Proper shipping name RESIN SOLUTION

UN number UN 1866

Class 3

Packing group III

Marine pollutant Mineral spirits

Transport in bulk

according to Annex I or II

of MARPOL 73/78 and the

IBC or IGC Code

Consult IMO regulations before transporting ocean bulk

Classification for AIR transport (IATA/ICAO):

Proper shipping name Resin solution

UN number UN 1866

Class 3

Packing group III

This information is not intended to convey all specific regulatory or operational requirements/information relating to this product. Transportation classifications may vary by container volume and may be influenced by regional or country variations in regulations. Additional transportation system information can be obtained through an authorized sales or customer service representative. It is the responsibility of the transporting organization to follow all applicable laws, regulations and rules relating to the transportation of the material.

Section XV—Regulatory Information

OSHA Hazard Communication Standard - This product is considered hazardous under the OSHA Hazard Communication Standard (29 CFR1910.1200).

Superfund Amendments and Reauthorization Act of 1986 Title III (Emergency Planning and Community Right-to-Know Act of 1986) Sections 311 and 312

Acute Health Hazard, Fire Hazard

Superfund Amendments and Reauthorization Act of 1986 Title III (Emergency Planning and Community Right-to-Know Act of 1986) Section 313

This product does not contain a chemical which is listed in Section 313 at or above de minimis concentrations.

Pennsylvania - Any material listed as "Not Hazardous" in the CAS REG NO. column of SECTION 2, Composition/Information On Ingredients, of this MSDS is a trade secret under the provisions of the Pennsylvania Worker and Community Right-to-Know Act.

California (Proposition 65) - This product contains trace levels of a component or components known to the state of California to cause cancer:

Components (CASRN) - Naphthalene (91-20-3)

United States TSCA Inventory (TSCA) - All components of this product are in compliance with the inventory listing requirements of the U.S. Toxic Substances Control Act (TSCA) Chemical Substance Inventory.

Section XVI—Other Information

Hazard Rating System

HMIS

Health	Flammability	Physical Hazard
1	3	0

Revision

Version: 2.0

Information Source and References

This SDS is from information supplied by internal references within our company.

Museum Services Corporation urges each customer or recipient of this SDS to study it carefully and consult appropriate expertise, as necessary or appropriate, to become aware of and understand the data contained in this SDS and any hazards associated with the product. The information herein is provided in good faith and believed to be accurate as of the effective date shown above. However, no warranty, express or implied, is given. Regulatory requirements are subject to change and may differ between various locations. It is the buyer's/user's responsibility to ensure that their activities comply with all federal, state, provincial or local laws. The information presented here pertains only to the product as shipped. Since conditions for use of the product are not under the control of the manufacturer, it is the buyer's/user's duty to determine the conditions necessary for the safe use of this product. Due to the proliferation of sources for information such as manufacturer specific SDSs, we are not and cannot be responsible for (M)SDSs obtained from any other sources. If you have obtained an SDS from another source or if you are not sure that the SDS you have is current, please contact us for the most current version.