

## Material Safety Data Sheet

May be used to comply with OSHA's Hazard Communication Standard, 29 CFR 1910.1200. Standard must be consulted for specific requirements.

## U.S. Department of Labor

Occupational Safety and Health Administration  
(Non-Mandatory Form)  
Form Approved  
OMB No. 1218-0072

IDENTITY (as Used on Label and List)  
**Paraloid B-72 Marking Varnish**

*Note: Blank spaces are not permitted. If any item is not applicable or no information is available, the space must be marked to indicate that.*

### Section I

Manufacturer's name Museum Services Corporation	Emergency Telephone Number 651-450-8954
Address (Number, Street, City, State and ZIP Code) 385 Bridgepoint Way South Saint Paul, MN 55075	Telephone Number for Information 651-450-8954
	Date Prepared 06/29/2016
	Signature of Preparer (optional)

### Section II—Hazardous Identification

Hazard classification

This material is hazardous under the criteria of the Federal OSHA Hazard Communication Standard 29CFR 1910.1200.

Flammable liquids - Category 2

Skin irritation - Category 2

Reproductive toxicity - Category 2

Specific target organ toxicity - single exposure - Category 3

Specific target organ toxicity - repeated exposure - Category 2 - Inhalation

Aspiration hazard - Category 1

#### Label elements

##### Hazard pictograms



Signal word: **DANGER!**

#### Hazards

Flammable liquid and vapour.

May be fatal if swallowed and enters airways.

Suspected of damaging fertility or the unborn child.

Causes damage to organs (Central nervous system) through prolonged or repeated exposure if inhaled.

#### Precautionary statements

##### Prevention

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Keep container tightly closed.

Ground/bond container and receiving equipment.

Use explosion-proof electrical/ ventilating/ lighting/ equipment.

Use only non-sparking tools.

Take precautionary measures against static discharge.

Do not breathe dust/ fume/ gas/ mist/ vapours/ spray.

Wash skin thoroughly after handling.

Do not eat, drink or smoke when using this product.

Wear protective gloves/ eye protection/ face protection.

Use personal protective equipment as required.

---

**Response**

IF SWALLOWED: Immediately call a POISON CENTER or doctor/ physician.  
IF ON SKIN (or hair): Remove/ Take off immediately all contaminated clothing. Rinse skin with water/ shower.  
IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/ physician if you feel unwell.  
IF exposed or concerned: Get medical advice/ attention.  
Do NOT induce vomiting.  
If skin irritation occurs: Get medical advice/ attention.  
Take off contaminated clothing and wash before reuse.  
In case of fire: Use dry sand, dry chemical or alcohol-resistant foam for extinction.

**Storage**

Store in a well-ventilated place. Keep container tightly closed. Keep cool.  
Store locked up.

**Disposal**

Dispose of contents/ container to an approved waste disposal plant.

**Other hazards**

no data available

---

**Section III—Composition/Information on Ingredients**

Component	CASRN	Concentration	
Acrylic Polymer(s)	NA	20%	
Acetone	67-64-1	80%	

---

**Section IV—First Aid Measures****General advice**

Take proper precautions to ensure your own health and safety before attempting rescue and providing first aid.  
Consult a physician. Show this safety data sheet to the doctor in attendance. Move out of dangerous area.

**Skin**

Wash skin with soap and copious amounts of water. Seek medical attention.

**Inhalation**

Remove person to fresh air. If signs/symptoms continue, get medical attention. Give oxygen or artificial respiration as needed.

**Eyes**

Thoroughly flush the eyes with large amounts of clean low-pressure water for at least 15 minutes, occasionally lifting the upper and lower eyelids. If irritation persists, seek medical attention.

**Ingestion**

DO NOT induce vomiting. If vomiting does occur, have victim lean forward to prevent aspiration. Rinse mouth with water. Seek medical attention. Never give anything by mouth to an unconscious individual.

---

**Section V—Fire and Explosion Hazard Data**

Extinguishing Media - SMALL FIRE: Use dry chemicals, CO<sub>2</sub>, water spray or alcohol-resistant foam. LARGE FIRE: Use water spray, water fog or alcohol-resistant foam. Cool all affected containers with flooding quantities of water.

Special Fire Fighting Procedures – no data available

Unusual Fire and Explosion Hazards -Vapors can travel to a source of ignition and flash back. Heated material can form flammable or explosive vapors with air. Closed containers may rupture via pressure build-up when exposed to fire or extreme heat. During a fire, irritating and highly toxic gases and/or fumes may be generated during combustion or decomposition.

**Advice for firefighters (Fire Fighting Procedures):** EXPLOSION HAZARD. Fight advanced fires from a protected location. Cool closed containers exposed to fire with water spray. Remain upwind. Avoid breathing smoke.

**Special protective equipment for firefighters:** In the event of fire, wear self-contained breathing apparatus.

---

---

**Section VI—Accidental Release Measures**

---

**Personal precautions, protective equipment and emergency procedures:** Appropriate protective equipment must be worn when handling a spill of this material. See SECTION 8, Exposure Controls/Personal Protection, for recommendations. If exposed to material during clean-up operations, see SECTION 4, First Aid Measures, for actions to follow.

**Environmental precautions:** WARNING: KEEP SPILLS AND CLEANING RUNOFFS OUT OF MUNICIPAL SEWERS AND OPEN BODIES OF WATER.

**Methods and materials for containment and cleaning up:** Eliminate all ignition sources. Evacuate personnel to safe areas. Ventilate the area. Floor may be slippery; use care to avoid falling. Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Sweep up or vacuum up spillage and collect in suitable container for disposal. No sparking tools should be used. Avoid breathing vapor. NOTE: Spills on porous surfaces can contaminate groundwater.

---

**Section VII—Handling and Storage**

---

**Precautions for safe handling:** Use non-sparking tools and grounding cables when transferring. Wash after handling and shower at end of work period.

CONTAINERS MAY BE HAZARDOUS WHEN EMPTY. Since emptied containers retain product residue, follow all MSDS and label warnings even after container is emptied.

**Conditions for safe storage:** Avoid temperature extremes during storage; ambient temperature preferred. Store away from excessive heat (e.g. steam pipes, radiators), from sources of ignition and from reactive materials. Material can burn; limit indoor storage to approved areas equipped with automatic sprinklers. Store out of direct sunlight in a cool place. Keep containers tightly closed in a cool, well-ventilated place. Avoid all ignition sources. Ground all metal containers during storage and handling.

---

**Section VIII—Exposure Control /Personal Protection**

---

**Respiratory Protection (Specific Type)** A respiratory protection program meeting OSHA 1910.134 and ANSI Z88.2 requirements or equivalent must be followed whenever workplace conditions warrant a respirator's use. None required if airborne concentrations are maintained below the exposure limit listed in Exposure Limit Information.

**Engineering Controls:** Use explosion-proof local exhaust ventilation with a minimum capture velocity of 100 ft/min (0.5 m/sec) at the point of vapor evolution. Refer to the current edition of Industrial Ventilation: A Manual of Recommended Practice published by the American Conference of Governmental Industrial Hygienists for information on the design, installation, use, and maintenance of exhaust systems.

**Protective measures:** Facilities storing or utilizing this material should be equipped with an eyewash facility and a safety shower.

**Protective Gloves:** Chemical-resistant gloves should be worn whenever this material is handled. The glove(s) listed below may provide protection against permeation. (Gloves of other chemically resistant materials may not provide adequate protection): Nitrile rubber. Butyl-rubber. Solvent-resistant gloves. Gloves should be removed and replaced immediately if there is any indication of degradation or chemical breakthrough. Rinse and remove gloves immediately after use. Wash hands with soap and water.

**Eye Protection:** Chemical resistant goggles must be worn. Eye protection worn must be compatible with respiratory protection system employed.

---

**Section IX—Physical and Chemical Properties**

---

**Appearance**

**Physical state** liquid

**Color** colourless clear

**Odor** Sweet. Alcohol-like.

**Odor Threshold** no data available

**pH** no data available

**Melting point/range** no data available

**Freezing point** no data available

**Boiling point (760 mmHg)** 158.00 °C ( 316.40 °F) Initial

**Flash point Pensky-Martens closed cup** 37 °C ( 99 °F)

**Flammability (solid, gas)** Not Applicable  
**Lower explosion limit** 0.90 % vol estimated  
**Upper explosion limit** 6.00 % vol estimated  
**Vapor Pressure** 1.0000000 mmHg at 20.00 °C (68.00 °F) estimated  
**Relative Vapor Density (air = 1)** >1.0000  
**Relative Density (water = 1)** 0.8900  
**Water solubility** practically insoluble  
**Partition coefficient: noctanol/water** no data available  
**Auto-ignition temperature** no data available  
**Decomposition temperature** no data available  
**Dynamic Viscosity** 800 - 1,600 mPa.s  
**Kinematic Viscosity** no data available  
**Explosive properties** no data available  
**Oxidizing properties** no data available  
**Liquid Density** 0.88 g/cm<sup>3</sup>  
**Molecular weight** no data available  
**Percent volatility** 54.00 - 56.00 %

NOTE: The physical data presented above are typical values and should not be construed as a specification.

---

## Section X—Stability and Reactivity

---

**Reactivity:** no data available

**Chemical stability:** no data available

**Possibility of hazardous reactions:** This material is considered stable. However, avoid contact with ignition sources (e.g. sparks, open flame, heated surfaces). Product will not undergo polymerization.

**Conditions to avoid:** Heat, flames, and sparks. Extreme temperatures and direct sunlight.

**Incompatible materials:** Avoid contact with the following: Alkali metals, Ammonia, Oxidizing agents, Peroxides, Strong Inorganic Acids

**Hazardous decomposition products:** Hazardous decomposition products formed under fire conditions. Carbon oxides

---

## Section XI—Toxicological Information

---

*Toxicological information appears in this section when such data is available.*

### Acute toxicity

#### Acute oral toxicity

LD50, Rat, > 5,000 mg/kg

#### Acute dermal toxicity

LD50, Rabbit, > 3,000 mg/kg

#### Acute inhalation toxicity

Product test data not available.

### Skin corrosion/irritation

slight irritation

**Serious eye damage/eye irritation**

slight irritation

**Sensitization**

Product test data not available.

**Specific Target Organ Systemic Toxicity (Single Exposure)**

Product test data not available.

**Specific Target Organ Systemic Toxicity (Repeated Exposure)**

Product test data not available.

**Carcinogenicity**

Product test data not available.

**Teratogenicity**

Product test data not available.

**Reproductive toxicity**

Product test data not available.

**Mutagenicity**

Product test data not available.

**Aspiration Hazard**

Product test data not available.

**COMPONENTS INFLUENCING TOXICOLOGY:****Acrylic polymer(s)****Acute oral toxicity**

Single dose oral LD50 has not been determined.

**Acute dermal toxicity**

The dermal LD50 has not been determined.

**Acute inhalation toxicity**

The LC50 has not been determined.

**Acetone****Acute inhalation toxicity**

Prolonged excessive exposure may cause adverse effects. Excessive exposure may cause irritation to upper respiratory tract (nose and throat). May cause central nervous system effects.

LC50, Rat, vapour, 50,100 mg/m<sup>3</sup>, 8 hours

**Sensitization**

LD50, Guinea Pig, 7,426 mg/kg

**For respiratory sensitization:**

No relevant data found.

**Specific Target Organ Systemic Toxicity (Single Exposure)**

Evaluation of available data suggests that this material is not an STOT-SE toxicant.

**Specific Target Organ Systemic Toxicity (Repeated Exposure)**

No relevant data found.

**Carcinogenicity**

No specific, relevant data available for assessment.

**Teratogenicity**

For similar material(s): Did not cause birth defects or any other fetal effects in laboratory animals.

**Reproductive toxicity**

For similar material(s): In animal studies, did not interfere with reproduction.

**Mutagenicity**

In vitro genetic toxicity studies were negative. Animal genetic toxicity studies were negative.

**Aspiration Hazard**

May be fatal if swallowed and enters airways.

---

**Section XII—Ecological Information**

*Ecotoxicological information appears in this section when such data is available.*

**General Information**

There is no data available for this product.

**Toxicity**

**Acrylic polymer(s)**

**Acute toxicity to fish**

No relevant data found.

**Acetone**

**Acute Fish Toxicity**

LC50 / 96 hours Rainbow Trout 5,540 mg/L

Persistence and degradability

**Acrylic polymer(s)**

**Biodegradability:** No relevant data found.

**Acetone**

**Biodegradability:** No data available

**Bioaccumulative potential**

**Acrylic polymer(s)**

**Bioaccumulation:** No relevant data found.

**Mineral Spirits**

**Bioaccumulation:** No data available

---

**Section XIII—Disposal Considerations**

**Disposal methods:** Incinerate liquid and contaminated solids in accordance with local, state, and federal regulations. (See 40 CFR 268)

**Contaminated packaging:** Empty containers should be taken to an approved waste handling site for recycling or disposal.

---

**Section XIV—Transport Information**

**DOT**

**Proper shipping name** Resin solution

**UN number** UN 1090

**Class** 3

**Packing group** II

**Classification for SEA transport (IMO-IMDG):**

**Proper shipping name** RESIN SOLUTION

**UN number** UN 1090

**Class** 3

**Packing group** II

**Marine pollutant** No

**Transport in bulk**

**according to Annex I or II**

**of MARPOL 73/78 and the**

**IBC or IGC Code**

Consult IMO regulations before transporting ocean bulk

**Classification for AIR transport (IATA/ICAO):**

**Proper shipping name** Resin solution

**UN number** UN 1866

**Class** 3

**Packing group** III

This information is not intended to convey all specific regulatory or operational requirements/information relating to this product. Transportation classifications may vary by container volume and may be influenced by regional or country variations in regulations. Additional transportation system information can be obtained through an authorized sales or customer service representative. It is the responsibility of the transporting organization to follow all applicable laws, regulations and rules relating to the transportation of the material.

---

**Section XV—Regulatory Information**

**SARA 302 Components**

SARA 302: No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.

**SARA 313 Components**

SARA 313: This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

**SARA 311/312 Hazards**

Acute Health Hazard

Chronic Health Hazard

Fire Hazard

**CERCLA**

Acetone CAS-No. 67-64-1, RQ: 5,000 lbs

**Massachusetts Right To Know Components**

Acetone CAS-No. 67-64-1 Revision Date 2007-03-01

Pennsylvania Right To Know Components  
Acetone CAS-No. 67-64-1 Revision Date 2007-03-01

New Jersey Right To Know Components  
Acetone CAS-No. 67-64-1 Revision Date 2007-03-01

California Prop 65 Components  
This product does not contain any chemicals known to State of California to cause cancer, birth defects, or any other reproductive harm.

---

## Section XVI—Other Information

---

### Hazard Rating System

#### HMIS

Health	Flammability	Physical Hazard
1	3	0

### Revision

Version: 1.0

### Information Source and References

This SDS is from information supplied by internal references within our company.

Museum Services Corporation urges each customer or recipient of this SDS to study it carefully and consult appropriate expertise, as necessary or appropriate, to become aware of and understand the data contained in this SDS and any hazards associated with the product. The information herein is provided in good faith and believed to be accurate as of the effective date shown above. However, no warranty, express or implied, is given. Regulatory requirements are subject to change and may differ between various locations. It is the buyer's/user's responsibility to ensure that their activities comply with all federal, state, provincial or local laws. The information presented here pertains only to the product as shipped. Since conditions for use of the product are not under the control of the manufacturer, it is the buyer's/user's duty to determine the conditions necessary for the safe use of this product. Due to the proliferation of sources for information such as manufacturer specific SDSs, we are not and cannot be responsible for (M)SDSs obtained from any other sources. If you have obtained an SDS from another source or if you are not sure that the SDS you have is current, please contact us for the most current version.