

# SAFETY DATA SHEET



Date of issue/Date of revision 18 September 2015

Version 2

## Section 1. Identification

Product name : Lo-Vel™ 6200 Flatting Agent  
 Product code : 8000437  
 Other means of identification : Synthetic Precipitated Silicas; Hydrated Amorphous Silica; Silicon Dioxide; SiO<sub>2</sub>  
 Product type : Solid.

### Relevant identified uses of the substance or mixture and uses advised against

Product use : Industrial applications.  
 Use of the substance/  
 mixture : Fillers (for paints, rubbers, adhesives, plastic etc.) - Reinforcing fillers  
 Fillers (for paints, rubbers, adhesives, plastic etc.) - Extenders  
 Uses advised against : Not applicable.

Supplier : PPG Industries, Inc.  
 One PPG Place  
 Pittsburgh, PA 15272  
  
 PPG Industries Chemicals BV  
 PO Box 181, 9930 - AD,  
 Delfzijl, The Netherlands

Emergency telephone number : (412) 434-4515 (U.S.)

Technical Phone Number : 1-800-243-6745 (Silica) 8am-5pm Eastern time

## Section 2. Hazards identification

OSHA/HCS status : While this material is not considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200), this SDS contains valuable information critical to the safe handling and proper use of the product. This SDS should be retained and available for employees and other users of this product.

Classification of the substance or mixture : Not classified.

### GHS label elements

Signal word : No signal word.  
 Hazard statements : No known significant effects or critical hazards.

### Precautionary statements

Prevention : Not applicable.  
 Response : Not applicable.

Product code 8000437 Date of issue 18 September 2015 Version 2  
 Product name Lo-Vel™ 6200 Flatting Agent

## Section 2. Hazards identification

Storage : Not applicable.  
 Disposal : Not applicable.  
 Supplemental label elements : Not applicable.  
 Hazards not otherwise classified : None known.

## Section 3. Composition/information on ingredients

Substance/mixture : Substance  
 Product name : Lo-Vel™ 6200 Flatting Agent  
 Other means of identification : Synthetic Precipitated Silicas; Hydrated Amorphous Silica; Silicon Dioxide; SiO<sub>2</sub>

### CAS number/other identifiers

CAS number : 112926-00-8

Ingredient name	%	CAS number
Silica, amorphous, precipitated and gel	> 87	112926-00-8

Contains no detectable crystalline silica (detection limit <0.1% by weight).

SUB codes represent substances without registered CAS Numbers.

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

**There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.**

Occupational exposure limits, if available, are listed in Section 8.

## Section 4. First aid measures

If ingestion, irritation, any type of overexposure or symptoms of overexposure occur during or persists after use of this product, contact a POISON CONTROL CENTER, EMERGENCY ROOM OR PHYSICIAN immediately; have Safety Data Sheet information available. Never give anything by mouth to an unconscious or convulsing person.

### Description of necessary first aid measures

**Eye contact** : Remove contact lenses, irrigate copiously with clean, fresh water, holding the eyelids apart for at least 10 minutes and seek immediate medical advice.  
**Inhalation** : Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel.  
**Skin contact** : Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognized skin cleanser. Do NOT use solvents or thinners.  
**Ingestion** : If swallowed, seek medical advice immediately and show this container or label. Keep person warm and at rest. Do NOT induce vomiting.

### Most important symptoms/effects, acute and delayed

#### Potential acute health effects

**Eye contact** : No significant irritation expected other than possible mechanical irritation.

Product code 8000437

Date of issue 18 September 2015 Version 2

Product name Lo-Vel™ 6200 Flatting Agent

**Section 4. First aid measures**

- Inhalation** : Exposure to airborne concentrations above statutory or recommended exposure limits may cause irritation of the nose, throat and lungs.
- Skin contact** : Prolonged or repeated contact may dry skin and cause irritation.
- Ingestion** : No known significant effects or critical hazards.

**Over-exposure signs/symptoms**

- Eye contact** : Adverse symptoms may include the following:  
irritation  
redness
- Inhalation** : Adverse symptoms may include the following:  
coughing  
Respiratory tract irritation
- Skin contact** : Adverse symptoms may include the following:  
dryness
- Ingestion** : No specific data.

**Indication of immediate medical attention and special treatment needed, if necessary**

- Notes to physician** : Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.
- Specific treatments** : No specific treatment.
- Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training.

See toxicological information (Section 11)

**Section 5. Fire-fighting measures****Extinguishing media**

- Suitable extinguishing media** : Use an extinguishing agent suitable for the surrounding fire.
- Unsuitable extinguishing media** : None known.

- Specific hazards arising from the chemical** : When transferring material into flammable solvents, use proper grounding to avoid electrical sparks.
- Hazardous thermal decomposition products** : Under normal conditions of storage and use, hazardous decomposition products should not be produced.
- Special protective actions for fire-fighters** : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.
- Special protective equipment for fire-fighters** : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

Product code 8000437

Date of issue 18 September 2015 Version 2

Product name Lo-Vel™ 6200 Flattening Agent

## Section 6. Accidental release measures

### Personal precautions, protective equipment and emergency procedures

- For non-emergency personnel** : No action shall be taken involving any personal risk or without suitable training. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Product forms slippery surface when combined with water.
- For emergency responders** : If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".
- Environmental precautions** : Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

### Methods and materials for containment and cleaning up

- Small spill** : Vacuum or sweep up material and place in a designated, labeled waste container. Product forms slippery surface when combined with water.
- Large spill** : Vacuum or sweep up material and place in a designated, labeled waste container. Product forms slippery surface when combined with water.
- Reference to other sections** : See Section 1 for emergency contact information.  
See Section 8 for information on appropriate personal protective equipment.  
See Section 13 for additional waste treatment information.

## Section 7. Handling and storage

### Precautions for safe handling

- Protective measures** : Put on appropriate personal protective equipment (see Section 8).
- Advice on general occupational hygiene** : Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. When transferring material into flammable solvents, use proper grounding to avoid electrical sparks. Avoid alteration of product properties before use. Calcining (which may result in crystalline formation) or mixing with additives may alter toxicological properties.  
See also Section 8 for additional information on hygiene measures.
- Conditions for safe storage, including any incompatibilities** : Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Do not store in unlabeled containers.

Product code 8000437

Date of issue 18 September 2015 Version 2

Product name Lo-Vel™ 6200 Flatting Agent

**Section 8. Exposure controls/personal protection****Control parameters****Occupational exposure limits**

Ingredient name	Exposure limits
Silica, amorphous, precipitated and gel	None.

**Key to abbreviations**

A = Acceptable Maximum Peak	S = Potential skin absorption
ACGIH = American Conference of Governmental Industrial Hygienists.	SR = Respiratory sensitization
C = Ceiling Limit	SS = Skin sensitization
F = Fume	STEL = Short term Exposure limit values
IPFI = Internal Permissible Exposure Limit	TD = Total dust
OSHA = Occupational Safety and Health Administration.	TLV = Threshold Limit Value
R = Respirable	TWA = Time Weighted Average
Z = OSHA 29CFR 1910.1200 Subpart Z - Toxic and Hazardous Substances	

**Consult local authorities for acceptable exposure limits.**

**Recommended monitoring procedures** : If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to appropriate monitoring standards. Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

**Appropriate engineering controls** : Good general ventilation should be sufficient to control worker exposure to airborne contaminants.

**Environmental exposure controls** : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

**Individual protection measures**

**Hygiene measures** : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

**Eye/face protection** : Safety glasses with side shields.

**Skin protection**

**Hand protection** : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.

**Gloves** : Leather, Cloth, Rubber

**Body protection** : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

**Other skin protection** : Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

**Respiratory protection** :

Product code 8000437

Date of issue 18 September 2015 Version 2

Product name Lo-Vel™ 6200 Flattig Agent

## Section 8. Exposure controls/personal protection

Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. If workers are exposed to concentrations above the exposure limit, they must use appropriate, certified respirators. Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary.

## Section 9. Physical and chemical properties

### Appearance

Physical state	: Powder., Solid., or Granular solid.
Color	: White.
Odor	: Odorless.
Odor threshold	: Not available.
pH	: 5 to 7 (5 %suspension)
Melting point	: Not applicable.
Boiling point	: Not applicable.
Flash point	: Closed cup: Not applicable.
Auto-ignition temperature	: Not available.
Decomposition temperature	: Not available.
Flammability (solid, gas)	: Not available.
Lower and upper explosive (flammable) limits	: Not available.
Evaporation rate	: Not applicable.
Vapor pressure	: Not applicable.
Vapor density	: Not applicable.
Relative density	: 2.1 (silicon dioxide)
Density ( lbs / gal )	: 7.53
Solubility	: Insoluble
Water Solubility at room temperature	: Not applicable.
Partition coefficient: n-octanol/water	: Not available.
Viscosity	: Not Applicable
Volatility	: 0% (w/w)
% Solid. (w/w)	: 100

## Section 10. Stability and reactivity

Reactivity	: No specific test data related to reactivity available for this product or its ingredients.
Chemical stability	: The product is stable.
Possibility of hazardous reactions	: Under normal conditions of storage and use, hazardous reactions will not occur.

Product code 8000437

Date of issue 18 September 2015 Version 2

Product name Lo-Vel™ 6200 Flattening Agent

**Section 10. Stability and reactivity**

**Conditions to avoid** : High temperature (>800 C) treatment (calcining).  
Avoid alteration of product properties before use. Calcining (which may result in crystalline formation) or mixing with additives may alter toxicological properties.

Refer to protective measures listed in sections 7 and 8.

**Incompatible materials** : Reactive or incompatible with the following materials: acids, oxidizing materials, strong alkalis.

**Hazardous decomposition products** : Under normal conditions of storage and use, hazardous decomposition products should not be produced.

**Section 11. Toxicological information****Information on toxicological effects****Acute toxicity**

**Conclusion/Summary** :  No known significant effects or critical hazards.

**Irritation/Corrosion****Conclusion/Summary**

**Skin** :  No known significant effects or critical hazards.

**Eyes** :  No known significant effects or critical hazards.

**Respiratory** :  No known significant effects or critical hazards.

**Sensitization****Conclusion/Summary**

**Skin** :  No known significant effects or critical hazards.

**Respiratory** :  No known significant effects or critical hazards.

**Mutagenicity**

**Conclusion/Summary** :  No known significant effects or critical hazards.

**Carcinogenicity**

**Conclusion/Summary** :  No known significant effects or critical hazards.

**Classification**

Product/ingredient name	OSHA	IARC	NTP
Silica, amorphous, precipitated and gel	-	3	-

Carcinogen Classification code:

IARC: 1, 2A, 2B, 3, 4

NTP: Known to be a human carcinogen; Reasonably anticipated to be a human carcinogen

OSHA: +

Not listed/not regulated: -

**Reproductive toxicity**

**Conclusion/Summary** :  No known significant effects or critical hazards.

**Teratogenicity**

**Conclusion/Summary** :  No known significant effects or critical hazards.

Product code 8000437

Date of issue 18 September 2015 Version 2

Product name Lo-Vel™ 6200 Flatting Agent

## Section 11. Toxicological information

### Specific target organ toxicity (single exposure)

Not available.

### Specific target organ toxicity (repeated exposure)

Not available.

**Target organs** : Contains material which may cause damage to the following organs: upper respiratory tract, eyes.

### Aspiration hazard

Not available.

### Information on the likely routes of exposure

#### Potential acute health effects

- Eye contact** : No significant irritation expected other than possible mechanical irritation.
- Inhalation** : Exposure to airborne concentrations above statutory or recommended exposure limits may cause irritation of the nose, throat and lungs.
- Skin contact** : Prolonged or repeated contact may dry skin and cause irritation.
- Ingestion** : No known significant effects or critical hazards.

#### Over-exposure signs/symptoms

- Eye contact** : Adverse symptoms may include the following:  
irritation  
redness
- Inhalation** : Adverse symptoms may include the following:  
coughing  
Respiratory tract irritation
- Skin contact** : Adverse symptoms may include the following:  
dryness
- Ingestion** : No specific data.

### Delayed and immediate effects and also chronic effects from short and long term exposure

- Conclusion/Summary** : An epidemiological study was conducted which included 165 precipitated silica workers who had been exposed an average time span of 8.6 years. Of these 165 workers, 44 had been exposed for an average of 18 years. No adverse effects were noted in complete medical examinations (including chest roentgenograms) of these workers. Pulmonary function decrements were correlated only with smoking and age but not with the degree or duration of dust exposures. Laboratory studies have also been conducted in small animals via inhalation of levels of precipitated silica dust of up to 126 mg/cu.m. per periods from six months to two years. Although precipitated silica was temporarily deposited in the animals' lungs, most of the deposited material was cleared soon after the dust exposure ended. The results of all studies performed by, or known to, PPG indicate a very low order of pulmonary activity for synthetic precipitated silicas. PPG recommends that persons with breathing problems or lung disease should not work in dusty areas unless a physician approves and certifies their fitness to wear respiratory protection.

### Short term exposure

- Potential immediate effects** : No significant irritation expected other than possible mechanical irritation.
- Potential delayed effects** : Prolonged or repeated contact may dry skin and cause irritation.

### Long term exposure



Product code 8000437

Date of issue 18 September 2015 Version 2

Product name Lo-Vel™ 6200 Flattening Agent

**Section 11. Toxicological information**

**Potential immediate effects** : Repeated or prolonged inhalation of dust may lead to chronic respiratory irritation.

**Potential delayed effects** : Repeated or prolonged inhalation of dust may lead to chronic respiratory irritation.

**Potential chronic health effects**

**General** : No known significant effects or critical hazards.

**Carcinogenicity** : No known significant effects or critical hazards.

**Mutagenicity** : No known significant effects or critical hazards.

**Teratogenicity** : No known significant effects or critical hazards.

**Developmental effects** : No known significant effects or critical hazards.

**Fertility effects** : No known significant effects or critical hazards.

**Numerical measures of toxicity****Acute toxicity estimates**

Not available.

**Section 12. Ecological information****Toxicity**

Product/ingredient name	Result	Species	Exposure
Silica, amorphous, precipitated and gel	NOEC >1000 ppm	Daphnia - Daphnia magna	24 hours
	Acute NOEC >10000 ppm Fresh water	Fish	96 hours Static
	Acute NOEC >10000 ppm	Fish - Brachydanio rerio	4 days Static

**Persistence and degradability**

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
Silica, amorphous, precipitated and gel	-	-	Not readily

**Bioaccumulative potential**

Product/ingredient name	LogP <sub>ow</sub>	BCF	Potential
Silica, amorphous, precipitated and gel	-	0	low

**Mobility in soil**

**Soil/water partition coefficient (K<sub>oc</sub>)** : Not available.

Product code 8000437 Date of issue 18 September 2015 Version 2  
 Product name Lo-Vel™ 6200 Flattening Agent

## Section 13. Disposal considerations

**Disposal methods** : The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements.

Disposal should be in accordance with applicable regional, national and local laws and regulations.

Refer to Section 7: HANDLING AND STORAGE and Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION for additional handling information and protection of employees. Section 6. Accidental release measures

## 14. Transport information

	DOT	IMDG	IATA
UN number	Not regulated.	Not regulated.	Not regulated.
UN proper shipping name	-	-	-
Transport hazard class (es)	☐	-	-
Packing group	-	-	-
Environmental hazards	No.	No.	No.
Marine pollutant substances	Not applicable.	Not applicable.	Not applicable.

### Additional information

DOT : None identified.  
 IMDG : None identified.  
 IATA : None identified.

Special precautions for user : ☐

## Section 15. Regulatory information

### United States

United States inventory (TSCA 8b) : All components are listed or exempted.

U.S. Federal regulations :

#### SARA 302/304

SARA 304 RQ : Not applicable.

#### Composition/information on ingredients

No products were found.

#### SARA 311/312

Classification : Not applicable.

#### Composition/information on ingredients

No products were found.

Product code 8000437

Date of issue 18 September 2015 Version 2

Product name Lo-Vel™ 6200 Flatting Agent

**Section 16. Other information****Hazardous Material Information System (U.S.A.)**

Health : 1 Flammability : 0 Physical hazards : 0

(\*) - Chronic effects

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings are not required on MSDSs under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered mark of the National Paint & Coatings Association (NPCA). HMIS® materials may be purchased exclusively from J. J. Keller (800) 327-6868.

The customer is responsible for determining the PPE code for this material.

**National Fire Protection Association (U.S.A.)**

Health : 1 Flammability : 0 Instability : 0

Date of previous issue : 12/19/2014

Organization that prepared the MSDS : EHS

**Key to abbreviations**

: ATE = Acute Toxicity Estimate  
 BCF = Bioconcentration Factor  
 GHS = Globally Harmonized System of Classification and Labelling of Chemicals  
 IATA = International Air Transport Association  
 IBC = Intermediate Bulk Container  
 IMDG = International Maritime Dangerous Goods  
 LogPow = logarithm of the octanol/water partition coefficient  
 MARPOL 73/78 = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)  
 UN = United Nations

☒ Indicates information that has changed from previously issued version.

**Disclaimer**

*The information contained in this data sheet is based on present scientific and technical knowledge. The purpose of this information is to draw attention to the health and safety aspects concerning the products supplied by PPG, and to recommend precautionary measures for the storage and handling of the products. No warranty or guarantee is given in respect of the properties of the products. No liability can be accepted for any failure to observe the precautionary measures described in this data sheet or for any misuse of the products.*