



Spunfab[®] PA1541 Technical Data Sheet

| Type | Melting Range, DSC (ASTM D3418) | Heat Resistance, (QWI-1008) 20g load | Plasticizer Migration Resistance | PVC Adhesion | Wash Resistance | High Frequency Weldable |
|-------------|---------------------------------|--------------------------------------|----------------------------------|--------------|-----------------|-------------------------|
| Copolyamide | 87 - 100°C | 95 °C | Yes | No | 40 °C | Yes |

Spunfab PA1541 is a copolyamide adhesive web made from 100% adhesive resin. No bodying modifiers or blowing agents are added. This product is low temperature activating and has excellent wet-out to a variety of fabrics, foams, leathers, and other applications requiring low temperature activation. It is also washable, dry cleanable and radio frequency activatable.

This information is derived from reference materials and/or test data that are believed to be reliable. NOTHING HEREIN SHALL BE DEEMED A WARRANTY OR REPRESENTATION, EXPRESSED OR IMPLIED, WITH RESPECT TO THE USE OF SUCH INFORMATION OR GOODS DESCRIBED FOR ANY PARTICULAR PURPOSE ALONE OR IN COMBINATION WITH OTHER GOODS AND OR PROCESSES, OR THAT THEIR USE DOES NOT CONFLICT WITH EXISTING PATENT RIGHTS. No license is granted to practice any patented invention. It is offered solely for your consideration investigation and verification.

Keuchel Associates Inc. / Spunfab Ltd. Certified to ISO 9001:2000, with design
 175 Muffin Lane, Cuyahoga Falls, Ohio 44223 ph: (330) 945-9455 fax: (330) 945-7588 www.spunfab.com