



MULTI-ROOM INNOVATIVE SOLUTIONS  
HIGH STATIC



DUCT09 & DUCT12



DUCT18 & DUCT24

Compact and powerful, the high static slim duct offers the ultimate in flexibility and discretion. Concealed above suspended ceilings or within open closet spaces to deliver conditioned air via extended ducting and suitable ceiling or wall grilles.

## Features and Benefits

- ▶ High Static Pressure Capability (selectable up to .8" Esp)
- ▶ Slim Line Construction 11.8" High
- ▶ Outside Air Capability
- ▶ Unique IAQ Filter Available
- ▶ Internal Condensate Pump
- ▶ Sentry Float Switch
- ▶ IR Remote and XK19 Wired Controllers included
- ▶ Gree I-Feel Mode

MODELS		DUCT09HP230V1BD	DUCT12HP230V1BD	DUCT18HP230V1BD	DUCT24HP230V1BD
System Type		Heat Pump			
<b>SYSTEM PERFORMANCE</b>					
Cooling Capacity*	Btu/h	9,000	12,000	18,000	24,000
Heating Capacity*	Btu/h	9,500	13,000	19,000	27,000
Airflow (Min-Max)	CFM	188/324	212/353	288/589	406/736
Internal Static Pressure (STD-MAX)	InWg	.24/.6	.24/.6	.36/.8	.36/.8
Sound Pressure Level (Min-Max)	dB(A)	25/36	26/38	26/39	28/42
Dehumidification	pt/hr	1.7	3.0	3.8	5.3
Unit Dimensions (W x D x H)	in	32.7 x 29.7 x 11.8	32.7 x 29.7 x 11.8	44.5 x 29.7 x 11.8	44.5 x 29.7 x 11.8
Package Dimensions (W x D x H)	in	35.3 x 31.8 x 13.6	35.3 x 31.8 x 13.6	47.5 x 32 x 14.2	47.5 x 32 x 14.2
Weight (Net/Gross)	lbs	70/83.8	70/83.8	92.6/107	92.6/107
<b>INSTALLATION</b>					
Line Set Size (Liquid - Gas)	in	1/4 - 3/8	1/4 - 1/2	3/8 - 5/8	3/8 - 5/8
Limited Warranty		5 Years on Parts			

\* Min / Max capacities will be determined by the Outdoor unit's capacities if diversity factors are not applicable.  
Capacities for each zone will be 10% higher Min capacity and 10% lower Max capacity than the 1 to 1 system capacities listed in the brochure.