


Position	Qty.	Description
	1	<p>UPS 25-80 N 180</p>  <p style="text-align: center;">Note! Product picture may differ from actual product</p> <p>Product No.: 95906439</p> <p>The pump is of the canned rotor type, i.e. pump and motor form an integral unit without shaft seal and with only two gaskets for sealing. The bearings are lubricated by the pumped liquid. The pump has 3-step speed selector. The pump is characterized by:</p> <ul style="list-style-type: none"> * Ceramic shaft and radial bearings. * Carbon axial bearing. * Stainless steel rotor can and bearing plate. * Corrosion-resistant impeller, Composite, PES/PP. * Stainless steel pump housing. <p>The motor is a 1-phase motor. No additional motor protection is required.</p> <p>Liquid: Pumped liquid: Water Liquid temperature range: -25 .. 110 °C Liquid temperature during operation: 60 °C Density: 983.2 kg/m³</p> <p>Technical: TF class: 110</p> <p>Materials: Pump housing: Stainless steel DIN W.-Nr. 1.4301 AISI 304 Impeller: Composite, PES/PP</p> <p>Installation: Amb. max at 80 dgr C liquid: 40 °C Maximum operating pressure: 10 bar Pipe connection: G 1 1/2 Pressure rating: PN 10 Port-to-port length: 180 mm</p> <p>Electrical data: Power input in speed 1: 110 W Power input in speed 2: 155 W Max. power input: 165 W Mains frequency: 50 Hz Rated voltage: 1 x 230 V</p>



Company name:

Created by:

Phone:

Date:

20/06/2018

Position	Qty.	Description
		Current in speed 1: 0.5 A Current in speed 2: 0.7 A Current in speed 3: 0.7 A Capacitor size - run: 4 µF Enclosure class (IEC 34-5): X2D Insulation class (IEC 85): F Others: Net weight: 4.4 kg Gross weight: 5.2 kg Shipping volume: 0.008 m ³ Danish VVS No.: 380633100 Swedish RSK No.: 5803099 Finnish: LVI NO 4615614 Norwegian NRF no.: 9042217