


Position	Qty.	Description
	1	<p data-bbox="320 338 550 365"><b>Unilift AP12.40.06.3</b></p> <div data-bbox="403 398 619 775" style="text-align: center;">  </div> <p data-bbox="711 770 1193 792" style="text-align: right;"><b>Note! Product picture may differ from actual product</b></p> <p data-bbox="320 801 686 860">Product No.: <a href="#">96001652</a> Submersible drainage pump type</p> <p data-bbox="320 891 874 1034">Vertical single-stage stainless steel submersible pump with vertical discharge port and integrated submersible 3-phase totally enclosed motor in insulation class F. The pump is fitted with a suction strainer.</p> <p data-bbox="320 1070 794 1182">The impeller is a SEMI OPEN impeller for 12 mm free passage suitable for pumping groundwater, surface water, rain water and similar.</p> <p data-bbox="320 1218 855 1303">The pump has a double shaft seal and an intermediate oil chamber pre-filled with non-toxic special oil.</p> <p data-bbox="320 1339 842 1451">The pump has a riser pipe, a cooling jacket for continuous cooling of the motor by the pumped liquid and long-life deep-groove greased-for-life ball bearings.</p> <p data-bbox="320 1487 855 1662">The pump is ready for use as it is fitted with carrying handle and is supplied with a 10 m mains cable. The mains cable is of the plug type with glass sealing compound in the socket to prevent penetration of humidity into the stator windings.</p> <p data-bbox="320 1697 919 1809"><b>Liquid:</b> Pumped liquid: Any Newtonian liquid Liquid temperature range: 0 .. 55 °C Density: 998.2 kg/m<sup>3</sup></p> <p data-bbox="320 1845 823 1930"><b>Technical:</b> Type of impeller: SEMI OPEN Maximum particle size: 12 mm</p> <p data-bbox="320 1966 887 2101"><b>Materials:</b> Pump housing: Stainless steel DIN W.-Nr. 1.4301 AISI 304 Impeller: Stainless steel</p>

Position	Qty.	Description
		<p>DIN W.-Nr. 1.4301 AISI 304</p> <p><b>Installation:</b>            Pump outlet: Rp 1 1/2            Maximum installation depth: 7 m</p> <p><b>Electrical data:</b>            Power input - P1: 0.9 kW            Mains frequency: 50 Hz            Rated voltage: 3 x 400 V            Rated current: 1.6 A            Cos phi - power factor: 0,83            Rated speed: 2815 rpm            Enclosure class (IEC 34-5): IP68            Insulation class (IEC 85): F            Length of cable: 10 m            Type of cable plug: NONE</p> <p><b>Others:</b>            Net weight: 10.5 kg            Gross weight: 11.5 kg            Danish VVS No.: 391314111            Swedish RSK No.: 5885776</p>