


Position	Qty.	Description
	1	<p data-bbox="320 338 550 367">Unilift AP12.40.06.1</p> <div data-bbox="403 398 619 779" style="text-align: center;">  </div> <p data-bbox="710 770 1193 795" style="text-align: right;">Note! Product picture may differ from actual product</p> <p data-bbox="320 801 686 862">Product No.: 96001729 Submersible drainage pump type</p> <p data-bbox="320 891 849 1066">Vertical single-stage stainless steel submersible pump with vertical discharge port and integrated submersible 1-phase totally enclosed motor in insulation class F with thermal overload protection. The pump is fitted with a suction strainer.</p> <p data-bbox="320 1099 794 1216">The impeller is a SEMI OPEN impeller for 12 mm free passage suitable for pumping groundwater, surface water, rain water and similar.</p> <p data-bbox="320 1249 829 1335">The pump has a double shaft seal and an intermediate oil chamber pre-filled with non-toxic special oil.</p> <p data-bbox="320 1368 842 1485">The pump has a riser pipe, a cooling jacket for continuous cooling of the motor by the pumped liquid and long-life deep-groove greased-for-life ball bearings.</p> <p data-bbox="320 1518 817 1693">The pump is ready for use as it is fitted with carrying handle and is supplied with a 10 m mains cable. The mains cable is of the plug type with glass sealing compound in the socket to prevent penetration of humidity into the stator windings.</p> <p data-bbox="320 1727 917 1843">Liquid: Pumped liquid: Any Newtonian liquid Liquid temperature range: 0 .. 55 °C Density: 998.2 kg/m³</p> <p data-bbox="320 1877 821 1962">Technical: Type of impeller: SEMI OPEN Maximum particle size: 12 mm</p> <p data-bbox="320 1995 885 2103">Materials: Pump housing: Stainless steel DIN W.-Nr. 1.4301 AISI 304</p>

Position	Qty.	Description
		<p>Impeller: Stainless steel DIN W.-Nr. 1.4301 AISI 304</p> <p>Installation: Pump outlet: Rp 1 1/2 Maximum installation depth: 7 m</p> <p>Electrical data: Type of motor: PSC Power input - P1: 0.9 kW Mains frequency: 50 Hz Rated voltage: 1 x 230 V Rated current: 4.4 A Cos phi - power factor: 0,99 Rated speed: 2785 rpm Capacitor size - run: 16 µF/400 V Enclosure class (IEC 34-5): IP68 Insulation class (IEC 85): F Length of cable: 10 m Type of cable plug: AU</p> <p>Others: Net weight: 12 kg Gross weight: 12.5 kg</p>