


Position	Qty.	Description
	1	<p><b>Unilift AP12.50.11.3</b></p>  <p style="text-align: right;"><b>Note! Product picture may differ from actual product</b></p> <p>Product No.: <a href="#">96001975</a> Submersible drainage pump type</p> <p>Vertical single-stage stainless steel submersible pump with vertical discharge port and integrated submersible 3-phase totally enclosed motor in insulation class F. The pump is fitted with a suction strainer.</p> <p>The impeller is a SEMI OPEN impeller for 12 mm free passage suitable for pumping groundwater, surface water, rain water and similar.</p> <p>The pump has a double shaft seal and an intermediate oil chamber pre-filled with non-toxic special oil.</p> <p>The pump has a riser pipe, a cooling jacket for continuous cooling of the motor by the pumped liquid and long-life deep-groove greased-for-life ball bearings.</p> <p>The pump is ready for use as it is fitted with carrying handle and is supplied with a 10 m mains cable. The mains cable is of the plug type with glass sealing compound in the socket to prevent penetration of humidity into the stator windings.</p> <p><b>Liquid:</b>  Pumped liquid: Any Newtonian liquid  Liquid temperature range: 0 .. 55 °C  Density: 998.2 kg/m<sup>3</sup></p> <p><b>Technical:</b>  Type of impeller: SEMI OPEN  Maximum particle size: 12 mm</p> <p><b>Materials:</b>  Pump housing: Stainless steel  DIN W.-Nr. 1.4301  AISI 304  Impeller: Stainless steel</p>

Position	Qty.	Description
		<p>DIN W.-Nr. 1.4301 AISI 304</p> <p><b>Installation:</b>            Pump outlet: Rp 2            Maximum installation depth: 7 m</p> <p><b>Electrical data:</b>            Power input - P1: 1.9 kW            Mains frequency: 50 Hz            Rated voltage: 3 x 400 V            Rated current: 3.2 A            Cos phi - power factor: 0,88            Rated speed: 2785 rpm            Enclosure class (IEC 34-5): IP68            Insulation class (IEC 85): F            Length of cable: 10 m            Type of cable plug: NONE</p> <p><b>Others:</b>            Net weight: 15.6 kg            Gross weight: 16.4 kg            Danish VVS No.: 391314112            Swedish RSK No.: 5880114</p>